

The Biggest Thing in LCD Monitors

LCD-801 LCD-800 LCD-800D LCD-800L



LCD-800D Dual Monitors in 19" Rack Mount Kit



Active Matrix 8" Color LCD Monitor

- S-Video capability
- Mirror and upside down image picture control
- Anti-glare coating provides enhanced display
- Remote control for maximum convenience
- LCD-801: Key lock feature allows front control buttons to be disabled
- LCD-801: Power saving ON/OFF feature
- A/C adaptor included
- LCD-801 : MB-2 desk stand/ wall mount included (shown above)
- LCD-800 and LCD-800L have built-in interface for wall or arm mounting VESA 75mm FPMPLI compliant

LCD-800L Unit in Flush Mount Kit (shown above)

Dimensions (WHD): 292 x 216 x 38mm / 11.5" x 8.5" x 1.5"
 Installer's Cut-out (WH): 249 x 173mm / 9.8" x 6.8"
 Black metal.

Optional Accessories

- BP-563 Rechargeable battery pack 2600mAh NiCad battery pack (provides approximately 5 hrs. operation)
- HM-400 Under-cabinet hinge mount (shown below)
- MB-3 ABS desk stand (shown above)
- WM-302 Wall mount with swing arm & 4-way (shown below)



HM-400



WM-302

Display: 8" (diagonal) TFT LCD active matrix
 Back Light: Built-in 2 CCFT
 Input Signal: NTSC/PAL
 Resolution: 1440(H) x 468(V) dots
 Dot Pitch: 0.112(H) x 0.252(V)mm
 Brightness rating: 300 cd/m²(Nit)
 Contrast Ratio: 350:1
 Number of Pixels: 673,920 Dots
 Viewing angle L/R/T/B: 50/50/15/35
 Colors: 262,144

Color Configuration: Stripe

LCD-801: Power Requirements: 12 ~ 24VDC, 2000mA, + pin

LCD-800: Power Requirements: 12 ~ 24VDC, 1A, + pin

LCD-801: Power Consumption: 10 W (max)

LCD-800: Power Consumption: 15 W (max)

Video Input Level: 1.0 V P-P (positive) 75 Ohm

LCD-801: Dimensions (WHD): 209 x 159 x 32mm / 8.2" x 6.3" x 1.3"

LCD-800: Dimensions (WHD): 192 x 144 x 29mm / 7.6" x 5.7" x 1.1"

LCD-800D Dimensions (WHD): Occupies 4 RU (7") x 1.5"

Actual visible screen size (WH): 161.28 x 117.94mm / 6.3" x 4.6"

Operating temperature: 50 ~ 104°F or 10 ~ 40°C

Storage temperature: -25 ~ 140°F or -32 ~ 60°C

Operating/Storage Humidity: 85% RH (max.)

Connections: LCD-801: Cable w/ RCA video IN,

2.1mm DC IN jack,

and cable w/ S-Video jack

LCD-800 / 800D: Mini DIN cable w/ RCA video IN,

BNC video IN/OUT, S-Video

2.1 DC IN jacks

LCD-801 Weight: Net: 650 g, 22.8 oz. / Gross: Est. 2.3 kg / 5 lbs.

LCD-800 Weight: Net: 1.64 kg./ 3.61 lbs. / Gross: 2.8 kg. / 6.1 lbs.

LCD-800D Weight: Net: Est. 3.2 kg. / 7lbs. / Gross: 4.4 kg. / 9.7 lbs.

LCD-800L Weight: Net: 1.64 kg./ 3.62 lbs. / Gross: 2.88 kg. / 6.35lbs.

GSA Schedule

GS-07F-0069L, SIN: 246-42(1), 246-50

Specifications subject to change without notice

©2008 ToteVision

30K

Available through: