

ViewSonic®

VE155/VE155b LCD Monitor



The VE155 15" LCD Monitor.

An excellent upgrade from CRTs, the ViewSonic VE155 15" LCD monitor uses up to 75% less desk space and features high brightness of 260 nits and a 450:1 contrast ratio, producing sharp images, crisp text and vivid colours. Additional features include a native resolution of 1024x768, Ø-Touch Auto-Tune function, OSD and power button lock functions, integrated power supply, and slim, compact design with a folding base for easy wall mounting. Easy on the environment and the budget, the VE155 15" LCD monitor is an ideal choice for small home offices, corporate, education and government users.

- **Full 15.0" viewable screen**

The VE155 displays a full, flat 15.0" viewable area that is comparable to the viewable area of traditional 17" (various viewable) CRTs.

- **1024x768 native resolution**

Displays a crisp, clear native resolution of 1024x768 for easy-on-the-eyes viewing.

- **OnView® controls including ViewMatch® technology**

Screen adjustments are made via the OnView menu using simple on-screen controls. ViewMatch feature allows easy adjustment to color temperature and intensity for optimal screen-to-print color matching.

- **Ø-Touch™ Auto-Tune™ function**

Provides the best image by monitoring signals from the computer and automatically optimizing the monitor settings.

- **OSD key lock and power lock**

The key lock function locks the menu settings to protect from accidental or unwanted changes. The power lock prevents the monitor from being inadvertently switched off.

- **Anti-reflective coating**

Minimizes glare and reflections, reducing eyestrain for optimal viewing comfort.



ViewSonic®
See the difference.™

www.ViewSonicEurope.com

ViewSonic®

VE155/VE155b LCD Monitor



Black case version¹: VE155b

• ViewSonic Wizard

This software provides user-friendly installation. The included CD-ROM automates the set-up process to deliver optimized screen performance.

• TCO'99¹ and Energy 2002 certified

This monitor complies with the world's strictest standards of low radiation, safety, ergonomics, recycling and power management while saving cost through automatic power-saving modes.



• PC and Mac^{®2} compatible

• Kensington[®] lock-ready

Protect your assets with this attachment for an anti-theft cable.

• VESA mount compliant³

• Three-year limited warranty⁴

VE155 LCD Monitor

LCD PANEL	Type	Colour TFT active matrix XGA LCD
	Display Area	15.0" Diagonal (304mm H X 228mm V)
	PixelPitch	0.297mm
	Contrast Ratio	450:1 (max.)
	Viewing Angle	120° horizontal, 110° vertical (typical at 10:1)
	Light Source	Long life, 50,000hrs (typical)
	Response Time	30ms (typical)
	Brightness	260cd/m ² (max.)
INPUT SIGNAL	Glass Surface	Anti-glare
	Video	RGB Analog (75 ohms, 0.7/1.0 Vp-p)
	Frequency	F _H :30-62kHz, F _V :50-75Hz
COMPATIBILITY	Sync	H/V separated (TTL)
	PC	PC compatible (from VGA up to 1024x768 non-interlaced)
CONNECTOR	Mac^{®2}	Power Mac [™] (up to 1024x768)
	Signal	15-pin mini D-sub (attached)
POWER	Power	3-pin plug (IEC320)
	Voltage	AC 100-240V, 50/60Hz (auto switch), internal Power Supply
CONTROLS	Consumption	30W (max)
	Physical	Power On/Off, Menu, Up, Down, Select
OPERATING CONDITIONS	OSD	Contrast, Brightness, Auto Image Adjust, Manual Image Adjust (H Size, H/V Position, Fine Tune, Sharpness), Color Adjust (9300K, 6500K, User), Display Information (Resolution, Frequency, Model-/Serialnumber), OSD-Setup Menu (Language, Resolution Notice, H/V Position, Timeout), Memory Recall, OSD Lock, Power Lock
	Temperature	32-104°F (0-40°C)
	Humidity	10-90% (no condensation)
DIMENSIONS	Physical	356mm (W) x 344mm (H) x 200mm (D) (14.0" x 13.5" x 7.9")
	Net	3.7kgs (8.1lbs.)
WEIGHT		
REGULATIONS		TCO'99 ¹ , TÜV/GS, TÜV/Ergo, ISO 13406-2 (class 2), ISO 9241-3, ISO 9241-7, ISO 9241-8, Energy 2002, CE, CB FCC-B, UL, NEMKO, SEMKO, DEMKO, FIMKO, VCCI, BSMI, CCEE, TÜV-S, PSB, PCBC, C-Tick, Gost-R, PC'2001, IC-B
POWER MANAGEMENT		ENERGY STAR [®] , VESA [®] DPMS, TCO'99, Energy 2002
WARRANTY		Three-year limited warranty. ⁴



ViewSonic Corporation's QMS/EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.



ViewSonic®
See the difference.™

www.ViewSonicEurope.com

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux
ViewSonic Denmark
ViewSonic Finland
ViewSonic Italy
ViewSonic MEA
ViewSonic Norway
ViewSonic Spain
ViewSonic Sweden

Tel: +33 (0) 1 41 47 49 00
Tel: +45 70 22 11 71
Tel: +358 (9) 54 06 40 70
Tel: +39 (0) 28 90 79 340
Tel: +971 (0) 4 88 11 871
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ Black case version: TCO'95. ² May require optional Mac adapter. ³ Wall mount accessories are optional. ⁴ For further information see ViewSonic WebSite.
Copyright © 2002, ViewSonic Corporation. All rights reserved. Corporate names and trademarks stated herein are the property of their respective companies. Specifications subject to change without notice.
The EPA only promotes energy efficiency and does not endorse any particular company or product. VE 155 11/02-UK