

ViewSonic®

VP201m/VP201mb LCD Display



The top-of-the line 20" LCD Display

The ViewSonic VP201mb and VP201m LCD displays are the top-of-the-line choice for professionals who spend more than eight hours per day in front of their displays. When ease of cognition is essential, these 20" LCDs are a smart choice. The large 1.9 megapixel (1600 x 1200) display provides extremely legible images, making it ideal for professional applications such as engineering design and financial analysis. What's more, they come with two 3-watt bezel-integrated speakers and pivot easily between landscape and portrait mode. For power users looking for a multimedia LCD, the VP201mb or VP201m is the clear choice.

- **OPTISYNC** technology

This multi-mode input technology supports both digital (DVI) and analog (VGA) signals. The digital interface delivers optimized image quality with minimum adjustments.

- **Full 20.1" viewable screen**

- **Displays a native resolution of 1.9 megapixels (up to 1600 x 1200)**
Ultra-high pixel density for superior imaging.

- **Landscape or portrait pivot capability**

Included PerfectPortrait™ software permits the display to pivot 90° to reduce scrolling when word processing, web surfing or working on long spreadsheets.

- **ViewSonic Wizard**

The ViewSonic Wizard software enables user-friendly installation. The included CD-ROM automates the installation, optimization and registration of your new ViewSonic monitor.

- **Bezel-integrated speakers**

Two 3-watt speakers provide superior audio quality for all multimedia applications while reducing desktop space required by separate speakers.



ViewSonic®
See the difference.®

ViewSonic®

VP201m/VP201mb LCD Display



VP201m beige case version.

- Ergonomic base features tilt, swivel height and pivot adjustments

- TCO'99[†] and Energy 2000 compliant

This monitor complies with the world's strictest standards of low radiation, safety, ergonomics, recycling and power management while saving costs through automatic power saving modes.



- Plug & Play[†] for ease of installation with Windows[®] operating system

- PC and Mac[®] compatible*

- Three-year limited warranty

- VESA-compliant 100mm mounting points

When used with the optional ViewSonic Universal wall mount (WM-U1), the VP201m or VP201mb occupies no desk space.



20.1" TFT LCD TOP-OF-THE-LINE COLOR DISPLAY

LCD	Type	TFT active matrix
	Display Area	408mm x 306mm (20.1" diagonal)
	Contrast Ratio	300:1 (typ)
	Viewing Angle	160° horizontal, 160° vertical (typ)
	Light Source	Long life, 30,000 hour (min)
	Brightness	250 cd/m ² (typ @ center)
	Panel Surface	Anti-glare
INPUT	Video	RGB Analog (75 ohms, 0.7/1.0 Vp-p), Digital DVI-D
	Frequency	F _H :30~82kHz; F _V :50~75Hz
	Sync	H/V separated (TTL), composite and SOG
COMPATIBILITY	PC	PC compatibles from VGA up to 1600 x 1200 non-interlaced
	Mac[®]*	Power Mac [™] up to 1600 x 1200
CONNECTOR	Analog Input	15-pin mini D-sub
	Digital Input	VESA DVI-D 24-pin
	Power	AC to head (built-in power supply)
	Security	Kensington security port
	Audio	3.5mm stereo mini connector
AUDIO	Speakers	Two 3.0W speakers
	Amplifier	3.0W at 1kHz for THD 1%
POWER	Voltage	AC 100-240V (universal)
	Consumption	60W (typ), 70W (max)
CONTROLS	Basic	1, down, up, 2, mute, volume (+,-), power
	OnView[®]	Auto image adjust,** contrast, brightness, manual image adjust (H/V position,** H. size,** phase,** zoom), fine tune,** color adjustment (9300K, 6500K, 5400K, 5000K, user color gamma), advanced menu (scaling, sharpness, information), setup menu (input select, language, OSD position, OSD time out), memory recall
OPERATING CONDITION	Temperature	32° F to 104° F (0° C to 40° C)
	Humidity	10-90% (non-condensing)
DIMENSIONS	Physical	510.0mm (W) x 549.5mm (H) x 238.5mm (D) 20.1" x 21.6" x 9.4"
WEIGHT	Net	13.0 kgs (28.6 lbs)
OTHER		DDC1 & DDC2B
REGULATIONS		UL, CSA, FCC-B, CB, CE, IC-B, EPA, NOM, TUV/GS, VCCI, BSMI, PSB (S-Mark), C-TICK, GOST-R(PCT-BZ02), PCBC(B-Mark), EMI/B, MPRII, NEMKO, SEMKO, DEMKO, FIMKO, TCO'99, TCO'95(VP201mb), ISO13406-2, ENERGY STAR [®] Energy 2000
POWER MANAGEMENT		Meets ENERGY STAR [®] and Energy 2000 standards
WARRANTY		Three-year limited warranty on parts, labor and backlight.



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



ViewSonic®
See the difference.®