

Digital media comes to life with the ViewDock™

ViewSonic's 22" VX2245wm ViewDock™ LCD blasts through barriers with its INNOVATIVE FUNCTIONALITY and beautiful piano-black, gloss finish. Dock your iPod® and listen to tunes while you surf the Internet or do your work. The big 22" screen and super-fast 5ms video response help you excel in your games with no blurs, ghosting or jaggies to slow you down. The INTEGRATED STEREO SPEAKERS AND SUBWOOFER drive incredibly rich stereo sound to your desktop display. The VX2245wm sets new standards in multimedia displays with an 8-in-1 card reader, USB connection for your joystick/game control, integrated microphone and headphone jack. Your desktop experience will never be the same once you bring it all together with your VX2245wm ViewDock and iPod.

VX2245wm

22" WIDESCREEN
VIEWDOCK™ LCD

WITH IPOD® DOCK IN MULTIMEDIA BASE



MAKE YOUR DESKTOP A DIGITAL MEDIA DESTINATION

- > **Multimedia base with iPod dock**
Multimedia base features iPod dock, 8-in-1 card reader, microphone, headphone jack, USB port for joystick/game control, and USB port for keyboard/mouse.
- > **Full 22" viewable widescreen with 1680x1050 resolution**
- > **ClearMotiv® 5ms video response time**
Fast 5ms video response enables digital, HD broadcast-quality video.
- > **Stylish slim-bezel design with glossy, piano-black finish**
The thin bezel lets you see more without taking up valuable desktop real estate. The high neck and floating head design accentuate the visual experience.
- > **Dynamic Structure™ technology**
Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > **OptiSync® digital/analog inputs expand your connectivity**
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Ultra-high brightness and contrast**
280-nit brightness (typ) and 700:1 contrast ratio (typ) for rich, detailed images.
- > **Windows Vista approved**
- > **PC and Mac® compatible**
- > **MPR II and ENERGY STAR® qualified**

5ms



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

VX2245wm

22" WIDESCREEN LCD WITH IPOD® DOCK IN MULTIMEDIA BASE



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows Vista logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13361-01B-08/07] VX2245wm-1

LCD	Type	22" Wide Color TFT Active Matrix LCD
	Display Area	18.7" horizontal x 11.7" vertical; 22" diagonal
	Optimum Resolution	1680x1050
	Contrast Ratio	700:1 (typ)
	Viewing Angles	170° horizontal, 160° vertical @ contrast ratio > 10:1
	Response Time	5ms (typ)
	Light Source	Long life, 40,000 hrs. (typ)
	Brightness	280 cd/m2 (typ)
Panel Surface		Anti-glare
VIDEO INPUT	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/DVI-D (TMDS, 100 ohms)
	Frequency	F _H : 30~82kHz, F _V : 50~85Hz
	Sync	H/V separated (TTL), composite, sync-on-green
COMPATIBILITY	PC	VGA up to 1680x1050 non-interlaced
	Mac®*	Power Mac™ G3/G4/G5 up to 1680x1050
CONNECTOR	Analog/Digital	15-pin mini D-sub/DVI-D
	Power	3-pin AC plug (CEE22)
	Base	iPod dock, USB (A type)x4, USB (B type)x1, audio out, 2-in-1 audio in, headphone jack
AUDIO	Speakers	2x2.5-watt
	Sub-woofer	1x3-watt
POWER	Voltage	AC 100–240V, 50–60Hz (auto switch)
	Consumption	62W (typ)
CONTROLS	Basic	Power, 1, down, up, 2, sub volume
	OnView®	Auto image adjust, brightness, contrast, input select (analog, digital), ViewMatch® color adjust (sRGB, 9300K, 6500K-default, 5400K, user color - RGB), information (resolution, H. frequency, V. frequency, pixel clock, model number, serial number), manual image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
OPERATING CONDITIONS	Temperature	41–95°F (5–35°C)
	Humidity	20–80% (non-condensing)
DIMENSIONS (W x H x D)	Physical with stand	20.6" x 19.4" x 8.4" (524mm x 493mm x 212mm)
	Physical without stand	20.6" x 15.3" x 2.3" (524mm x 388mm x 58mm)
WEIGHT	Net with stand	13.7 lb. (6.2 kg)
	Net without stand	10.6 (4.8kg)
	Gross with stand	18.7 lb. (8.5 kg)
REGULATIONS		UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, NEMKO/GS (covers TUV/GS), NEMKO ERGO (covers TUV/ERGO, ISO13406-2 & MPR II), MPR II, GOST-R + 20 original copies hygienic, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, Argentina-S, Green Mark, RoHS
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of in accordance with local, state and federal laws.
POWER MANAGEMENT		Meets MPR II and ENERGY STAR® standards
PACKAGE CONTENTS		LCD display, power cable, 15-pin VGA video cable, DVI cable, Quick Start Guide, ViewSonic Wizard CD
WARRANTY		Three-year limited warranty on LCD, parts and labor.

ViewSonic®
See the difference®

For more product information, visit us on the web at ViewSonic.com