

# X-15



▶ FEATURES

- Distinctive metal housing for added strength
- NeoV Optical Glass™
- Swift 8ms response time
- High 400 cd/m<sup>2</sup> brightness
- Crisp 3000:1 dynamic contrast ratio
- DVI ready for high quality signal
- S-Video\* and CVBS\* inputs
- Hot key for preferred video mode: User, Text, Movie, Game, and Graphic
- Auto-adjustment for optimal settings
- Kensington® security socket
- VESA standard wall mount
- Available colours: black, white

▶ SPECIFICATION

|                     |  |  |
|---------------------|--|--|
| Panel               | <b>Panel Type</b>                      | TFT LCD  |
|                     | <b>Panel Size</b>                      | 15.0" (381mm)  |
|                     | <b>Max. Resolution</b>                 | XGA 1024 x 768   |
|                     | <b>Pixel Pitch</b>                     | 0.297mm  |
|                     | <b>Brightness</b>                      | 400cd/m <sup>2</sup> (Typical)   |
|                     | <b>Contrast Ratio</b>                  | 3000:1 (DCR)   |
|                     | <b>Viewing Angle (H/V)</b>             | 140°/125° (Typical)  |
|                     | <b>Display Color</b>                   | 16.7M  |
|                     | <b>Response Time</b>                   | 8ms (GTG)  |
|                     | <b>Frequency (H/V)</b>                 | H: 30kHz - 60kHz<br>V: 56Hz - 75Hz   |
| Input               | <b>Max. Pixel Clock</b>                | 80MHz  |
|                     | <b>Life Time</b>                       | 50,000hrs (Minimum)  |
|                     | <b>Analog</b>                          | 15-Pin D-Sub   |
|                     | <b>Digital</b>                         | 24-Pin DVI-D   |
| Connector           | <b>S-Video</b>                         | 4-Pin Mini Din S-Video   |
|                     | <b>CVBS</b>                            | CVBS Jack  |
|                     | <b>Power</b>                           | 3-pin AC Plug  |
|                     | <b>NeoV Optical Glass</b>              | <b>Thickness</b>   |
| Tilt                | <b>Reflection Rate</b>                 | <1%  |
|                     | <b>Transmission Rate</b>               | >96%   |
|                     | <b>Hardness</b>                        | >6H (MOH's Rating)   |
| Mounting            | <b>Tilt</b>                            | 0° ~ +20°  |
|                     | <b>VESA FPMPI</b>                      | Yes (100mm)  |
| Regulation Approval | <b>Certifications &amp; Compliance</b> | FCC, UL/CUL, TUV/Baurt, CE, BSMI, CB, ISO 13406-2, GOST, Energy Star, NOM, TUV-S, WEEE, RoHS   |
|                     | <b>VESA</b>                            | DDC-2B, DDC-CI, DPMS   |
|                     | <b>Power AC Consumption</b>            | 100 - 240V, 50 - 60Hz<br><22W (on)<br><2W (Stand-by)<br><1W (Off)  |
|                     | <b>Dimensions</b>                      | <b>Net (W x H x D)</b> 380 x 359 x 155mm (15.0" x 14.1" x 6.1")<br><b>Packing (W x H x D)</b> 488 x 447 x 219mm (19.2" x 17.6" x 8.6") |
| Weight              | <b>Net Weight</b>                      | 4.8Kg (10.6lbs)  |
|                     | <b>Gross Weight</b>                    | 7.4Kg (16.3lbs)  |
| Packing             | <b>1 Pallet</b>                        | 40 Cartons   |
|                     | <b>20' Container</b>                   | 480 Sets   |
|                     | <b>40' Container</b>                   | 1040 Sets  |

All specifications are subject to change without prior notice

