



2216Vw

Cabinet Color	Whole Black
Panel	TFT Active Matrix LCD 22" Widescreen, Diagonal 21.6" Viewable Image Size
Pixel Pitch	0.276mm x 0.276mm
Display Area	464.9mm x 290.6mm
Brightness	300 cd/m2 (typ)
Contrast Ratio	3000:1 (DCR)
Response Time	5ms (typ)
Viewing Angle	Horizontal: 160 Degrees (CR>10) Vertical: 160 Degrees (CR>10)
Compatibility	VESA, VGA, SVGA, XGA, SXGA, WSXGA+ Mac® Equipped With VGA and DVI-D Port
Scanning Frequency	Horizontal: 30K~80KHz Vertical: 55~75 Hz
Pixel Frequency	165MHz
Maximum Resolution	1680x1050@60Hz
Recommended Resolution	1680x1050@60Hz
Resolutions Supported	720x400@70Hz, 640x480@60/75Hz, 800x600@60/75Hz, 1024x768@60/70/75Hz, 1280x1024@60/75Hz, 1680x1050@60Hz
Color	16.7M
Signal Input	Analog: 0.7Vp-p(standard), 75 OHM, Positive
Digital Input	DVI-D (TMDS) with HDCP*
Connectors	Analog RGB Signal: 15-pin D-sub Male Digital Signal: 24-pin DVI-D Power: (3-Pin Plug CEE22)
Power Source	Universal 100~240VAC, 50/60Hz
Power Consumption	49Watts (Max.)
Plug & Play	DDC 1/2B/CI
EPA ENERGY STAR®	Yes
User Control	AUTO Config, Eco/down, up, Menu, Power
OSD Function	Brightness, Contrast, Eco Mode, Gammar, DCR, H/V Position, Phase, Clock, Color Temperature, Color Boost, Picture Boost, OSD Language Selection, Timeout, Menu Position, Auto Config, DDC-CI, Reset, Information, Input Select
OSD Languages	8 languages including English, French & Spanish
Regulations	cULus, FCC, CE, Certified for Windows Vista Logo, ROHS
Other Features	VESA 100mm Wall Mount Compliant*, Kensington Security Slot, DCB, DCR, Eco mode
Dimensions (WxHxD mm)	Monitor: 505.8x357.6x210 ; Carton 591x522x174
Dimensions (WxHxD inches)	Monitor: 19.9x14.3x8.3 ; Carton: 23.3x20.6x6.9
Weight	11.4 lbs (5.2kgs) Net 14.7 lbs (6.7 kgs) Gross
Loading Qty w/pallet	20' = 672 pcs.; 40' Std = 1456 pcs.
UPC Code	685417022281