


### Overview



1. Menu button
2. - adjust

3. + adjust
4. Power on/off

### Models

P9602A#ABA

### Technical Specifications

<b>Panel</b>	<b>Type</b>	19-inch Active Matrix TFT (thin film transistor)
	<b>Viewable Image Area</b> (diagonal)	19.0 in (48.25 cm) maximum, diagonal
	<b>Screen Opening</b> (W x H)	14.81 x 11.85 in (37.6 x 30.1 cm)
	<b>Viewing Angle</b> (typical)*	Up to 140 degrees horizontal/ 140 degrees vertical (10:1 minimum contrast ratio)
	<b>Brightness</b> (typical)*	Up to 250 nits (cd/m <sup>2</sup> )
	<b>Contrast Ratio</b> (typical)*	Up to 500:1 (typical)
	<b>Response Rate</b> (typical)*	16 ms (typical) (rise + fall)
	<b>Pixel Pitch</b>	0.294 mm
	<b>Color Depth Support</b>	> 16 million colors
	*All performance specifications are provided by the component manufacturers. Performance specifications represent the highest specification of all HP's component manufacturers' typical level specifications for performance. Actual performance may vary either higher or lower.	
<b>Video Input</b>	<b>Plug and Play</b>	Yes
	<b>Input Signal</b>	Attached 15-pin D-sub (analog VGA)
	<b>Input Impedance</b>	75 ohms DC ± 1.5 ohms
	<b>Sync Input</b>	TTL separate sync
	<b>Video Cable</b>	VGA
	<b>Video Cable Length</b>	5.9 ft (1.8 m); captive
<b>Signal Interface/ Performance</b>	<b>Horizontal Frequency</b>	30 to 81 kHz
	<b>Vertical Frequency</b>	56 to 76 Hz
	<b>Graphics Controller</b>	Genesis or ST or MST
	<b>Native Resolution</b>	1280 x 1024 @ 60 Hz (recommended)
	<b>Maximum Resolution</b> (Digital)	N/A
	<b>Preset VESA Graphic Modes</b> (non-interlaced)	1280 x 1024 @ 60 Hz and 75 Hz
		1024 x 768 @ 60 Hz, 70 Hz, and 75 Hz
		800 x 600 @ 60 Hz, 72 Hz, and 75 Hz
		640 x 480 @ 60 Hz, 72 Hz, and 75 Hz
	<b>Maximum Pixel Clock Speed</b>	140 MHz
	<b>User Programmable Modes</b>	15
	<b>Anti-Glare</b>	Yes
	<b>Anti-Static</b>	Yes
	<b>Default Color Temperature</b>	6500 sRGB
<b>On Screen Display (OSD) Controls</b>	<b>Buttons or Switches</b>	Power on/off 3 button OSD (menu, plus, minus)
	<b>Languages</b>	English, Spanish, French, Italian, German, Dutch
	<b>User Controls</b>	Brightness
		Contrast
		Horizontal/vertical position
		Color temperature (6500k, 9300k, Custom)
		Clock, clock phase
		Power saver, power on recall
		Mode display
		Sleep timer
Horizontal OSD position, vertical OSD position, OSD timeout		
Factory reset		

### Technical Specifications

<b>Power</b>	<b>Input Power</b>	Universal/auto-sensing, 100 to 240 VAC, 50 to 60 Hz
	<b>Maximum</b>	< 40 watts
	<b>Power Saving</b>	< 2 watts
	<b>Power Cable Length</b>	5.9 ft (1.8 m)
<b>Mechanical</b>	<b>Dimensions (H x W x D)</b>	<b>Unpacked w/ stand</b> 16.8 x 16.6 x 7.8 in (42.7 x 42.2 x 19.7 cm)
		<b>Unpacked w/o stand</b> 14.2 x 16.6 x 2.9 in (36.1 x 42.2 x 7.5 cm)
		<b>Packaged</b> 20.1 x 7.0 x 20.1 in (17.8 x:51.2 x 51.2 cm)
	<b>Weight</b>	<b>Unpacked</b> 14.4 lb (6.5 kg)
		<b>Packaged</b> 18.8 lb (8.5 kg)
	<b>Tilt Range</b>	-5 to +30 degrees vertical tilt
	<b>Swivel Range</b>	None
	<b>Height Adjustable</b>	No
	<b>Pivot Rotation</b>	No
	<b>Base</b>	Detachable
<b>Environmental</b>	<b>Temperature – Operating</b>	41° to 95° F (5° to 35° C) (non-condensing)
	<b>Temperature – Non-operating</b>	-4° to 140° F (-20° to 60° C)
	<b>Humidity – Operating</b>	20% to 80% (non-condensing)
	<b>Humidity – Non-operating</b>	5% to 90%
	<b>Altitude – Operating</b>	0 to 12,000 ft (0 to 3,658 m)
	<b>Altitude – Non-operating</b>	0 to 40,000 ft (0 to 12,100 m)
<b>Options</b>	<b>HP Desktop Access Center</b>	Optional; Features integrated microphone/headset jacks, dual function headset for phone/PC support, a MultiBay slot for adding an optical drive (sold separately), and four USB ports for easy integration of third-party digital solutions; part number DK985A. For more information, refer to the HP Desktop Access Center QuickSpecs.
<b>Other</b>	<b>Accessories Included</b>	Attached VGA Cable, AC Power Cable
	<b>User Guide Languages</b>	English, French, German, Spanish, Italian, Dutch
	<b>Warranty Languages</b>	English, French, German, Spanish, Italian, Dutch
	<b>Color</b>	Carbonite/Silver
	<b>VESA Mounting</b>	100 mm x 100 mm screw-mounting option; pedestal is attached
	<b>VESA External Mounting</b>	Yes (Standard 4 hole pattern, 100 mm)
	<b>Kensington Lock-ready</b>	Yes
<b>Certification and Compliance</b>		ISO 9241-3,7,8 VDT guidelines, ISO 13406-2 pixel defect guidelines, MPR-II, CISPR, VCCI, C-UL or CSA (Canada), ACA (Australia), TUV and GS Mark (German ergonomic), BSMI (Taiwan), CCC (China), MIC (South Korea), NOM (Mexico), Nemko, Fimko, Demko, Semko (Nordic) Eastern European approvals, CE Marking, FCC approval, Energy Star, TCO '03 (emissions, ergonomics, environment), Microsoft® Windows® certified (Microsoft® Windows® 2000 and Microsoft Windows XP), UL listed
<b>Compatibility</b>		Compatible with platforms using VESA standard video modes. Recommended for use with HP products.
<b>Service and Warranty</b>		Limited three years parts, labor, and on-site service, including backlight. Availability varies by region. Certain restrictions and exclusions apply. For details, contact HP Customer Support.

© 2004 Hewlett-Packard Development Company, L.P.

Microsoft and Windows are trademarks or registered trademarks of Microsoft Corporation in the U.S. and other countries.

HP shall not be liable for technical or editorial errors or omissions contained herein. The information is provided as is without warranty of any kind and is subject to change without notice. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. All performance specifications are provided by the component manufacturer. Performance specifications represent component manufacturer averages and actual performance may vary.

