



Electrolux

air-o-convect LPG Gas Hybrid Convection Oven 201

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



Electrolux



air-o-convect

LPG Gas Hybrid Convection Oven 201

269714 (AOS201GCD2)

LPG Gas Hybrid Convection
Oven 201 230 V/1ph/60Hz

Short Form Specification

Item No. _____

Convection oven with direct steam: 90% steam saturation in 4 minutes.
air-o-flow: fresh air is blown into the oven from the outside, after it is pre-heated it is pulled through the bi-functional fan, guaranteeing cooking evenness. Manual injection of water to add additional moisture in the cell.
air-o-clean: built-in cleaning system with four automatic pre-set cycles and one semi-automatic cleaning cycle.
Cooking cycles: hot air (25-300 °C) combined with 11 different humidity settings, ranging from browning to baking and par-steaming. 2-step cooking with the possibility to combine different cycles. Full speed and pulse ventilation controls. Food probe for precise cooking. Double-glass door with book-like opening maintains a cool external temperature and incorporates a drip pan to collect excess condensation avoiding wet floors. Halogen lighting in the cooking chamber. Side panels and interior in AISI 304 stainless steel.
Supplied with n.1 trolley rack 1/1GN, 63mm pitch and door shield.

Main Features

- Dry hot convection cycle 25 °C to 300 °C ideal for low humidity baking.
Automatic moistener (11 settings) for boiler-less steam generation.
-0 = no additional moisture (browning, au gratin, baking, pre-cooked food)
-1-2 = low moisture (small portions of meat and fish)
-3-4 = medium low moisture (large pieces of meat, reheating, roasted chicken and proving)
-5-6 = medium moisture (roasted vegetable and first step of roasted meat & fish)
-7-8 = medium-high moisture (stewed vegetables)
-9-10 = high moisture (poached meat and jacket potatoes)
- Double step cooking (first phase with moisture, second phase dry for browning).
- Core temperature probe.
- Variable fan speed (radial fan): full speed or pulse ventilation (Hold) for baking and slow cooking.
- Hold function for keeping food warm at the end of a cycle.
- Exhaust valve electronically controlled to extract excess humidity.
- Automatic and manual rapid cooling activation when going from a higher to a lower temperature.
- air-o-clean™ automatic and built-in self cleaning system (4 automatic and 1 semi-automatic cycles).
- Gas burner is certified by Gastec for high efficiency and low emissions.

Construction

- IPX 5 spray water protection certification for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Seamless hygienic cooking chamber with all rounded corners for easy cleaning.
- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Swing hinged front panel for easy service access to main components.

Optional Accessories

- Trolley with tray rack for 20x1/1GN ovens PNC 922007 ☐
and bcf, 63mm pitch (std)
- Trolley with tray rack for 16x1/1GN ovens PNC 922010 ☐
and bcf, 80mm pitch
- Trolley with rack for 54 plates for PNC 922016 ☐
20x1/1GN ovens and bcf, 74mm pitch
- Couple of grids for whole chicken 1/1GN (8PNC 922036 ☐
per grid)


APPROVAL: _____




Electrolux

air-o-convect LPG Gas Hybrid Convection Oven 201

Front




Top



CWI = Cold Water inlet
D = Drain
DO = Overflow drain pipe
EI = Electrical connection
G = Gas connection

Side



Electric

Supply voltage:

269714(AOS201GCD2)

230 V/1N ph/50/60 Hz

Circuit Breaker required

Gas

ISO 7/1 gas connection diameter: 1" MNPT

LPG:

Pressure: 11" w.c. (27.4 mbar)

Heating elements: 136360 BTU (40 kW)

Total thermal load: 136360 BTU (40 kW)

Water:

Water inlet "CW" connection: 3/4"

Total hardness: 5-50 ppm

Pressure: 1.5-4.5 bar

Drain "D": 1"1/4

Electrolux recommends the use of treated water, based on testing of specific water conditions.

Please refer to user manual for detailed water quality information.

Installation:

Clearance: 5 cm rear and right hand sides.

Suggested clearance for service access: 50 cm left hand side.

Capacity:

GN: 20 - 1/1 Gastronorm

Max load capacity: 100 kg

Key Information:

Net weight: 297 kg

Shipping weight: 322 kg

Shipping height: 1795 mm

Shipping width: 993 mm

Shipping depth: 957 mm

Shipping volume: 1.71 m³



air-o-convect
LPG Gas Hybrid Convection Oven 201

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2012.07.24



Electrolux

air-o-convect LPG Gas Hybrid Convection Oven 201

Included Accessories

- 1 of Trolley with tray rack for 20x1/1GN ovens and bcf, 63mm pitch (std) PNC 922007
- 1 of Door shield for pre-heating oven, without trolley, 20 GN 1/1 PNC 922094
- 1 of Control panel filter for 20xGN1/1 ovens PNC 922248

Optional Accessories

- Automatic water softener for ovens PNC 921305 ☐
- Resin sanitizer for water softener PNC 921306 ☐
- Trolley with tray rack for 20x1/1GN ovens and bcf, 63mm pitch (std) PNC 922007 ☐
- Trolley with tray rack for 16x1/1GN ovens and bcf, 80mm pitch PNC 922010 ☐
- Thermal blanket for 20x1/1GN PNC 922014 ☐
- Trolley with rack for 54 plates for 20x1/1GN ovens and bcf, 74mm pitch PNC 922016 ☐
- Pair of 1/1 GN AISI 304 grids PNC 922017 ☐
- Flue condenser for gas 10x2/1GN and 20x1/1GN PNC 922019 ☐
- Couple of grids for whole chicken 1/1GN (8 per grid) PNC 922036 ☐
- Pastry trolley, for 16 and 20x1/1GN ovens and bcf, 80mm pitch (16 runners). Suitable for 600x400mm pastry trays in oven PNC 922068 ☐
- Rack for 45 plates for 20x1/1GN, 90mm pitch PNC 922072 ☐
- Grid for whole chicken 1/2GN (4 per grid - 1,2kg each) PNC 922086 ☐
- Non-stick universal pan 1/1GN H=20mm PNC 922090 ☐
- Non-stick universal pan 1/1GN H=40mm PNC 922091 ☐
- Non-stick universal pan 1/1GN H=60mm PNC 922092 ☐
- Aluminium oven grill 1/1GN PNC 922093 ☐
- Door shield for pre-heating oven, without trolley, 20 GN 1/1 PNC 922094 ☐
- Kit HACCP EKIS PNC 922166 ☐
- Side external spray unit PNC 922171 ☐
- 2 fat filters for 20 1/1 and 2/1 GN combi steamers (gas and electric) and convection ovens (electric) PNC 922179 ☐
- Water filter for ovens PNC 922186 ☐
- Baking tray with 5 rows (baguette), perforated aluminium with silicon coating (400x600x38) PNC 922189 ☐
- Baking tray with 4 edges, perforated aluminium (400x600x20) PNC 922190 ☐
- Baking tray with 4 edges, aluminium (400x600x20) PNC 922191 ☐
- Baking tray with 4 rows (baguette), perforated aluminium with silicon coating (325x530x38) PNC 922192 ☐
- Baking tray with 4 edges, perforated aluminium (325x530x20) PNC 922193 ☐
- Baking tray with 4 edges, aluminium (325x530x20) PNC 922194 ☐
- Basket for detergent tank - wall mounted PNC 922209 ☐
- Frying griddle GN 1/1 PNC 922215 ☐
- Flue condenser for gas combi steamers and convection ovens PNC 922235 ☐
- 2 frying baskets for ovens PNC 922239 ☐
- Heat shield for 20x1/1GN PNC 922243 ☐
- Retractable spray unit for 20GN1/1&2/1 ovens PNC 922263 ☐
- Grid for whole chicken 1/1GN (8 per grid - 1,2kg each) PNC 922266 ☐
- Kit integrated HACCP for ovens PNC 922275 ☐



**air-o-convect
LPG Gas Hybrid Convection Oven 201**

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2012.07.24