

INSTALL INSTRUCTIONS C-VS-1100-F150 VEHICLE SPECIFIC CONSOLE 2004-2007 FORD F-150 PICK UP

TOOLS REQUIRED:

Metric Socket Set Ratcheting Wrench Panel Pulling Tool 1/8" Drill Bit Phillips Screwdriver Power Drill

HARDWARE:

QTY DESCRIPTION

#8 x ³/₄" Phillip Sheet Metal Screws
C-HK-1 (32 Torx Screws)

PART # GSM33189 CM86508

SUB ASSEMBLY:

- 1. Remove necessary components to access mounting area.
 - Armrest Pad (3 Metric Hex Head screws)
 - Forward Console Face Plate (Panel Pulling Tool)
 - Rear Console Face Plate (Panel Pulling Tool & 2 Metric Hex Head Screws)



INSTALLATION:

- 1. ATTACH HAVIS-SHIELDS CONSOLE:
 - Position console plate as shown in the above view.
 - Pre-drill mounting holes with 1/8" drill bit.
 - Attach console plate using #8 x 3/4" Sheet Metal Screws.

2. REPLACE COMPONENTS REMOVED IN SUB ASSEMBLY:

- Replace Rear Console Face Plate.
- Replace Forward Console Face Plate.
- Replace Armrest Pad.

3. INSTALL CONTROLS:

• Wire all controls prior to installation.

Note: A hole must be drilled in the bottom of the OEM console for routing of wires.

• Attach control heads to console plate using equipment brackets or filler panels with #8 x 3/8" Black Torx Screws.

Note: You may have to drill the console plate in the occasional situation that the mounting slots do not line up with the equipment bracket.

