

GHRIS

When you need big, bright, stunning images in a limited space, Christie's new FP40 is your answer.

The new Christie FP40 flat panel LCD monitor is the latest in our range of display solutions ideal for smaller corporate boardrooms and classrooms, retail and entertainment signage, transit facilities, control rooms and broadcast and surveillance applications. Anywhere you need high brightness, high resolution images in a thin, light, LCD display that illuminates your message in even the highest ambient light, the FP40 delivers a consistent, strong image.

The latest direct view LCD technology eliminates heat, image retention and burn-in challenges often seen with plasma displays. The fanless design offers silent, reliable operation. Low power consumption and long-life backlight reduce the cost of ownership. With high life expectancy and high quality large display capability, the FP40 is an ideal choice for your display application.



• Ultra-thin, high resolution LCD monitor for big, bright images

CHRISTIE

- High resolution WXGA with support for most computer and video sources
- High brightness and high contrast display is ideal for use in high ambient light conditions
- Wide viewing angle makes it easy for everyone to get the message
- Slim design allows you to put the message where it is needed
- Fast response time LCD display for sharp video reproduction
- Low power consumption and long-life backlight reduce cost of ownership
- ChristieNET<sup>™</sup> networkability for monitoring and control of all critical features
- The latest direct view LCD technology eliminates the heat and burn-in challenges often seen with plasma technology

## APPLICATIONS

- Retail signage
- Entertainment signageSmaller Boardrooms
- Broadcast
- Classrooms

- Transit facilities
- Control Rooms
- Dioaucast
- Surveillance

# FP40 • 38-FP0001-01

# Retail, entertainment signage, smaller boardrooms, classrooms, transit facilities, control rooms, broadcast and surveillance

With a wide viewing angle of 170°, native WXGA resolution and a 600:1 contrast ratio, the FP40 creates crisp, bright images that are easy to view. Lightweight and sleek in appearance, you can place the FP40 anywhere. Super-thin at just 3.5" in depth, the FP40 mounts in a horizontal or vertical orientation. All connections and controls are in the rear of the display for clean and secure installations. An optional wall mount or table top stand offers further installation flexibility. With picture in picture and a quick response time, you can display multiple sources and truly dynamic presentations.

The FP40 - a flat, compact package delivering a big, bright display.

## FEATURES



 Ideal for dynamic retail displays or transit scheduling applications.

#### Technology

- Direct View 40" Active Matrix TFT
- ResolutionWXGA, 1280 x 768 native
- Brightness
- 470 cd/m<sup>2</sup>
- Contrast Ratio • 600:1
- Less than 16ms

#### Inputs

- DVI-D (HDCP compliant), HD15, BNC (RGBHV, YCbCr), RCA (Composite), S-Video, DB9 for control
- Video CompatibilityNTSC, PAL, SECAM
- Computer Compatibility • VGA, SVGA, XGA, WXGA Optional
- Pixel Pitch
- 0.68mm (H/V)
- Aspect Ratio15:9 native



 Discreet rear placement of connections and controls keep installations clean and secure.

Horizontal Sync

Viewable Image

39.6" diagonal

Viewable Angle

Dimensions (W x L x D)

• (938mm x 610mm x 89mm)

• Universal power AC 100-240V

• 38.9" x 24.0" x 3.5"

• 50.6lbs (23.9 kg)

Power Consumption

210W (12W stand-by)

**Power Requirements** 

+/- 10%, 50/60Hz

**Operating Humidity** 

**Operating Temperature** 

40°F to 95°F (5° to 35°C)

• 30-80% (storage 10-90%)

• 170° (H/V)

Weight

21-60 kHz

Vertical Sync

• 56-75 Hz



• Single-fan design offers silent, reliable operation in high-use applications.

On-screen Menu Languages • English, German, French, Spanish

- Backlight Life60,000 hours (typical)
- Networking
- Optional ChristieNET™ wired/wireless

# Picture in PictureVideo within data

- **Optional Accessories**
- Table top stand
- Wall mount stand
  ChristieNET™
- Approvals
- UL, cUL, CSA, EMC, EMI, FCC Class A
- Warranty
- 24 months parts and labor

### **Corporate Offices**

USA 10550 Camden Drive Cypress, CA 90630 PH: 714-236-8610 FX: 714-503-3385 Toll free: (866) 880-4462 (NA only) sales-us@christiedigital.com

#### CANADA

809 Wellington Street North Kitchener, Ontario N2G 4Y7 PH: 519-744-8005 FX: 519-749-3136 Toll free: (800) 265-2171 (NA only) sales-canada@christiedigital.com

#### **Branch Offices**

UNITED KINGDOM PH: +44 118 977 8000 FX: +44 118 977 8100 sales-europe@christiedigital.com

SINGAPORE PH: +65 6877-8737 FX: +65 6877-8747 sales-singapore@christiedigital.com

FRANCE PH: +33 (0) 1 47 48 28 07 FX: +33 (0) 1 47 48 26 06 Mobile: +33 (0) 6 76 47 43 62 sales-france@christiedigital.com

GERMANY PH: +49 2161 664540 FX: +49 2161 664546 sales-europe@christiedigital.com

CHINA-Shanghai PH: +86 21 6278 7708 FX: +86 21 6278 7707 sales-china@christiedigital.com

CHINA-Beijing PH: +86 10 6561 0240 FX: +86 10 6561 0546 sales-china@christiedigital.com



Copyright 2004 Christie Digital Systems, Inc.. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Printed in Canada. MIL6258

Performance specifications are typical. Due to constant research, specifications are subject to change without notice.

Jan 04-NA

WWW.CHRISTIEDIGITAL.COM