

Built-in CleanDesign™ cooktops

	GE Profile™	
	PHP960SM PHP960DM	PHP900SM PHP900DM
ADA-compliant	●	
Features		
Ceramic-glass surface	Pattern. black	Pattern. black
Number of elements	5 induction	4 induction
Induction elements	●	
11" heating elements	1 (3700W)	1 (3700W)**
8" heating elements	1 (3200W)**	
7" heating elements	2 (2500W)**	2 (2500W)**
6" heating elements	1 (1800W)**	1 (1800W)**
Hot surface indicator lights	5	4
Precise Digital Control System™	●	
Pan presence sensor	●	
Pan size sensor	●	
Kitchen timer	●	
Control lock capability	●	
Appearance		
Color appearance*	SS	SS
Frameless	BB	BB
Stainless steel frame	SS models only	SS models only
Weight & Dimensions		
Cooktop width (in inches)	36	30
Approx. shipping wt. (lbs.)	59	49
Power/Ratings		
KW rating @ 240V	8.6	7.4
KW rating @ 208V	6.5	5.6
Amps @ 240V	50	40
Amps @ 208V	50	40

*SS = Stainless Steel, BB = Black on black.

**Highest wattage available using power share. Consult use and care manual for more information on powershare.

Cooktop dimensions (in inches)

Model	Overall			Cutout		To edge of front counter (min.)
	W	D	H	E	F	G
PHP960DM	36	20-7/8	3-1/4*	33-7/8	19-1/8	2-1/2**
PHP900DM	29-3/4	21-3/8	3-1/4*	28-1/2	19-5/8	2-1/2**

*Depth of unit at conduit connection location (rear) is 4-5/8" on model PHP960/900.

**Raised bull nose countertops may require up to 3/8" additional clearance to prevent interference with curved front.


Stainless steel cooktop dimensions (in inches)

Model	Overall			Cutout		To edge of front counter (min.)
	W	D	H	E	F	G
PHP960SM	36-1/8	21	3-1/4*	33-7/8	19-1/8	2-1/2**
PHP900SM	29-7/8	21-1/2	3-1/4*	28-1/2	19-5/8	2-1/2**

*Depth of unit at conduit connection location (rear) is 4-5/8" on model PHP960/900.

**Raised bull nose countertops may require up to 3/8" additional clearance to prevent interference with curved front.

Cooktop dimensions (in inches)



Built-in induction cooktops

Requires a 12" min. free area between the bottom of the cooktop to any combustible material, i.e. shelving. Free area not required when installing wall oven underneath cooktop. Refer to installation instructions. Unite are furnished with a 36" flexible armored cable.

30" and 36" induction cooktops are approved for use over GE, GE Profile and GE Monogram 30" and 27" single wall ovens*. Refer to cooktop and wall oven installation instructions packed with product for current dimensional data.

*Except Trivection® wall ovens.

Filler trim kit

When replacing an old GE 30" cooktop (with larger opening) with 30" models, use the following one-piece trim kit to fill in the over-size hole. Available at additional cost. JXTR32B (Black)

Installation information:

Before installing, consult installation instructions packed with product for current dimensional data.

Notes: If installing with a 36" GE Profile or GE Monogram® Telescopic Downdraft System, consult both cooktop and downdraft installation instructions packed with product before installing. Cooktop gas/electric supply may need to be re-routed to install downdraft. The countertop must be at least 26" deep with a flat surface area of 23-1/2" or more, front to back. Stainless CleanDesign and gas on glass cooktops require 23-5/8" flat surface area. In addition, other clearances to the front edge of the countertop must be considered.

Note: Consult cabinet and countertop manufacturer's specs for flush mount installation prior to install.