

imageCLASS[®] Dll0 Series

D 1 1 5 0
D 1 1 7 0

Black & White Laser Multifunction Copiers

Our Canon imageCLASS D1100 Series Laser Multifunction Copiers deliver large-office capabilities in a compact, easy-to-use package. Featuring the fastest output speeds within our Canon imageCLASS line to date, each model prints and copies at up to 30 pages per minute. Large paper supplies of up to 1,050 sheets minimize interruptions by offering the flexibility of working with a variety of paper sizes and types.

Each model offers convenient multifunction features that will consolidate all of your office machines into one durable, fast and energy efficient networkable copier.



imageCLASS D 1 1 0 0 Series



FEATURES	D1120	D1150	D1170	D1180
Digital Copier	X	X	X	X
Duplex Printer	X	X	X	X
Super G3 Fax		X	X	X
Color Scanner	X	X	X	X
Network Capabilities	X	X	X	X
Send Function			X	X
PCL Language Support				х

ORDERING INFORMATION

MFP and Accessories

 imageCLASS D1120
 3478B001AA

 imageCLASS D1150
 3478B005AA

 imageCLASS D1170
 3478B018AA

 imageCLASS D1180
 3478B022AA

 Cartridge 120 Black (yields approx. 5,000 pages based on ISO/IEC Standard)
 2617B001AA

 Cassette Feeding Unit-U1 (500-sheet Cassette)
 0732A023AA

imageCLASS D1120 Series Virtual CarePAK (2 Year On-Site CarePAK) imageCLASS D1120 Series Printed CarePAK (2 Year On-Site CarePAK) imageCLASS D1150 Series Virtual CarePAK (2 Year On-Site CarePAK) imageCLASS D1150 Series Printed CarePAK (2 Year On-Site CarePAK) imageCLASS D1170 Series Virtual CarePAK (2 Year On-Site CarePAK) imageCLASS D1170 Series Printed CarePAK (2 Year On-Site CarePAK) imageCLASS D1180 Series Virtual CarePAK (2 Year On-Site CarePAK) imageCLASS D1180 Series Printed CarePAK (2 Year On-Site CarePAK) imageCLASS D1180 Series Printed CarePAK (2 Year On-Site CarePAK)

3478B039AA

3478B035AA

3478B040AA

3478B036AA

3478B041AA

3478B037AA

3478B042AA

3478B038AA

imageCLASS D 1 1 0 0 Series

New and Powerful Features

Keeping up the Pace

As life becomes more hectic, you need a machine that can keep up. With a warm-up time of approximately 16 seconds from power on and a first copy time of approximately 8 seconds, waiting around for prints is a thing of the past. When copying or printing larger jobs, your documents will print at up to 30* pages per minute!

User-Friendly & Compact

Designed for ease of use in your home or small office environment, the D1100 Series provides access to the control panel, supplies, and paper sources right from the front of the unit. No need to reach around to locate your prints or change the consumable.

Limit Your Interruptions

Frequent changing of paper and cartridges can give you less time to concentrate on what's really important. The large paper supply (including the optional additional 500-sheet paper cassette) accommodates a variety of sizes and types of paper up to 1,050 sheets. The D1100 Series uses the Canon Single Cartridge System, which means you need to replace only one consumable. It provides high quality black and white output that yields approximately 5,000 pages based on ISO/IEC standards.

Environmentally Conscious

Reduce your power consumption with Canon's efficient Energy Saving Mode. The D1100 Series uses approximately 3 watts of energy during Energy Saving Mode and meets Energy Star Guidelines, helping you save money on energy costs.



Enhanced Features

A new feature of the D1100 Series is I.D. Card Copy. Easily create copies of your identification cards or other small documents like passports to keep for your records on a one-sided document. This feature instructs you as to how to place your card, and then aligns and prints automatically onto one page.



A Document Exchange Solution

Increase your productivity by sharing printing and faxing** (sending only) over a network. Additionally, on D1170 and D1180, you can send your scanned documents to a recipient through E-mail or File Server via our Send-Lite function.



The D1100 Series features Canon's UFRII LT printer language, and the D1180 adds PCL printer language.

Generation Green

The D1100 Series is part of the Generation Green Program which highlights the company's commitment to sustainability. Learn more at www.usa.canon.com/green.



FEATURES	D1120	D1150	D1170	D1180
Duplex Copy	Yes, Automatic (1 to 2, 2 to 1, 2 to 2)	Yes, Automatic (1 to 2, 2 to 1, 2 to 2)	Yes, Automatic (1 to 2, 2 to 1, 2 to 2)	Yes, Automatic (1 to 2, 2 to 1, 2 to 2)
Сору Туре	Monochrome Laser	Monochrome Laser	Monochrome Laser	Monochrome Laser
Copy Speed	Up to 30 cpm (letter)	Up to 30 cpm (letter)	Up to 30 cpm (letter)	Up to 30 cpm (letter)
Copy Resolution	Up to 600 x 600 dpi; 1200 x 600 dpi quality	Up to 600 x 600 dpi; 1200 x 600 dpi quality	Up to 600 x 600 dpi; 1200 x 600 dpi quality	Up to 600 x 600 dpi; 1200 x 600 dpi quality
Halftones	256 levels	256 levels	256 levels	256 levels
Warm-up Time	Approx. 16 seconds from Power On	Approx. 16 seconds from Power On	Approx. 16 seconds from Power On	Approx. 16 seconds from Power On
First Copy Time	Approx. 8 seconds	Approx. 8 seconds	Approx. 8 seconds	Approx. 8 seconds
Standard Paper Source(s)	500-sheet cassette; 50-sheet multipurpose tray	500-sheet cassette; 50-sheet multipurpose tray	500-sheet cassette; 50-sheet multipurpose tray	500-sheet cassette; 50-sheet multipurpose tray
Optional Cassette	Optional 500-sheet cassette	Optional 500-sheet cassette	Optional 500-sheet cassette	Optional 500-sheet cassette
Paper Weight	16 to 32 lb. (cassette);	16 to 32 lb. (cassette);	16 to 32 lb. (cassette);	16 to 32 lb. (cassette); 16 to 51 lb. (multipurpose tray)
Paper Output	16 to 51 lb. (multipurpose tray) 150 sheets (face down)	16 to 51 lb. (multipurpose tray) 150 sheets (face down)	16 to 51 lb. (multipurpose tray) 150 sheets (face down)	150 sheets (face down)
Reduction/Enlargement	50%, 64%, 78%, 129%, 200%	50%, 64%, 78%, 129%, 200%	50%, 64%, 78%, 129%, 200%	50%, 64%, 78%, 129%, 200%
Zoom	50-200% in 1% increments	50-200% in 1% increments	50-200% in 1% increments	50-200% in 1% increments
Document Feeder	50-sheet ¹	50-sheet ¹	50-sheet ¹	50-sheet¹
Copy Size	Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14"	Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14"	Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14"	Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14"
Copy Features	Memory Sort, Toner Saver Mode, 2 on 1,	Memory Sort, Toner Saver Mode, 2 on 1,	Memory Sort, Toner Saver Mode, 2 on 1,	Memory Sort, Toner Saver Mode, 2 on 1,
	I.D. Card Copy	I.D. Card Copy	I.D. Card Copy	I.D. Card Copy
Copy Memory	128MB (shared)	128MB (shared)	128MB (shared)	128MB (shared)
Dunlay Drint	No form	PRINTER SPECIFICATION:		V. A. II.
Duplex Print Printer Type	Yes (letter)	Yes (letter)	Yes (letter)	Yes (letter)
Printer Type	Monochrome Laser	Monochrome Laser	Monochrome Laser	Monochrome Laser
Print Speed	Up to 30 ppm (letter)	Up to 30 ppm (letter)	Up to 30 ppm (letter)	Up to 30 ppm (letter)
Print Resolution	Up to 600 x 600 dpi; 1200 x 600 dpi quality	Up to 600 x 600 dpi; 1200 x 600 dpi quality	Up to 600 x 600 dpi; 1200 x 600 dpi quality	Up to 600 x 600 dpi; 1200 x 600 dpi quality
Printer Language	Canon UFR II LT (Host-based)	Canon UFR II LT (Host-based)	Canon UFR II LT (Host-based)	PCL 5e/6, Canon UFR II LT (Host-based)
Print Memory	128MB (shared)	128MB (shared)	128MB (shared)	128MB (shared)
System Memory (on board)	128MB (shared)	128MB (shared) FAX/PC FAX SPECIFICATIO	128MB (shared)	128MB (shared)
Duplex Fax		Yes (transmission, reception)	Yes (transmission, reception)	Yes (transmission, reception)
Modem Speed		Up to 33.6 Kbps (Super G3)	Up to 33.6 Kbps (Super G3)	Up to 33.6 Kbps (Super G3)
Fax Resolution		Up to 406 x 391 dpi (super fine)	Up to 406 x 391 dpi (super fine)	Up to 406 x 391 dpi (super fine)
Memory Capacity		Up to 512 pages ²	Up to 512 pages ²	Up to 512 pages ²
Speed Dials		20 one-touch speed dials/201 coded dials	20 one-touch speed dials/201 coded dials	20 one-touch speed dials/201 coded dials
Receive Modes		Fax Only, Manual, Answering, DRPD, Fax/Tel Auto	Fax Only, Manual, Answering, DRPD, Fax/Tel Auto	Fax Only, Manual, Answering, DRPD, Fax/Tel Auto
		Switch	Switch	Switch
Fax Features		Remote RX, Delayed TX, Dual Access, Polling RX	Remote RX, Delayed TX, Dual Access, Polling RX	Remote RX, Delayed TX, Dual Access, Polling RX
Memory Backup		Standard, 15 minutes	Standard, 15 minutes	Standard, 15 minutes
PC Fax		SCANNER SPECIFICATION	Sending only	Sending only
Duplex Scan	Yes	Yes Yes	Yes	Yes
Scan Type	Color Contact Image Sensor (CIS)			
Scan Resolution		Color Contact Image Sensor (CIS)	Color Contact Image Sensor (CIS)	Color Contact Image Sensor (CIS)
	Up to 600 x 600 dpi (optical):	Color Contact Image Sensor (CIS) Up to 600 x 600 dpi (optical);	Color Contact Image Sensor (CIS) Up to 600 x 600 dpi (optical);	Color Contact Image Sensor (CIS) Up to 600 x 600 dpi (optical);
	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated)	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated)	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated)	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated)
Color Depth	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit
Color Depth Document Size	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14"	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14"	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14"	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14"
Color Depth Document Size Compatibility	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA
Color Depth Document Size	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14"	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14"	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14"
Color Depth Document Size Compatibility Output File Formats	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP
Color Depth Document Size Compatibility Output File Formats Scan to E-mail	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP
Color Depth Document Size Compatibility Output File Formats Scan to E-mail	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s)	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed ³	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed ³	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed ³	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed ³
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s) Network Interface	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA IPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed ³ 10/100 Base T	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed ³ 10/100 Base T	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed ³ 10/100 Base T	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed ³ 10/100 Base T
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s) Network Interface USB Functions	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed ³ 10/100 Base T Print/Scan	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed ³ 10/100 Base T Print/PC Fax/Scan	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed ³ 10/100 Base T Print/PC Fax/Scan
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s) Network Interface USB Functions Network Functions	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed ³ 10/100 Base T Print/Scan	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed ³ 10/100 Base T	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed ³ 10/100 Base T Print/PC Fax/Scan
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s) Network Interface USB Functions Network Functions Network Protocol	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed ³ 10/100 Base T Print/Scan Print TCP/IP	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax TCP/IP	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed ³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax TCP/IP	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed ³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax TCP/IP
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s) Network Interface USB Functions Network Functions	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed³ 10/100 Base T Print/Scan Print TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestot PageManager	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s) Network Interface USB Functions Network Functions Network Protocol	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed³ 10/100 Base T Print/Scan Print TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax/Scan Version of the speed of	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Presto! PageManager USB: Windows Vista, XP, 2000. Detwork: Server 2008, Windows Vista, Server 2003, XP, 2000
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s) Network Interface USB Functions Network Functions Network Protocol Bundled Software	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed ³ 10/100 Base T Print/Scan Print TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008,	Up to 600 x 600 dpi (optical); Up to 9600 x 600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA IPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers ovailable for download from www.cusa.canon.com	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax TCP/IP COCR, NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008,
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s) Network Interface USB Functions Network Functions Network Protocol Bundled Software OS Compatibility	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA IPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed³ 10/100 Base T Print/Scan Print TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com GENERAL SPECIFICATION	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestot PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, XP 2000 Drivers available for download from www.cusa.canon.com
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s) Network Interface USB Functions Network Functions Network Protocol Bundled Software OS Compatibility Dimensions	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA IPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed³ 10/100 Base T Print/Scan Print TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com 17.7" (W) x 18.6" (D) x 18.3" (H)	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com GENERAL SPECIFICATION 17.7" (W) x 18.6" (D) x 18.3" (H)	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TMAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com S 17.7" (W) x 18.6" (D) x 18.3" (H)	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestot PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com 17-7" (W) x 18.6" (D) x 18.3" (H)
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s) Network Interface USB Functions Network Functions Network Protocol Bundled Software OS Compatibility Dimensions Weight (with Cartridge)	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA IPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed ³ 10/100 Base T Print/Scan Print TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestot PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs	Up to 600 x 600 dpi (optical); Up to 9600 x 600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com GENERAL SPECIFICATION 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TMAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com S 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s) Network Interface USB Functions Network Functions Network Protocol Bundled Software OS Compatibility Dimensions Weight (with Cartridge) Warranty	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed ³ 10/100 Base T Print/Scan Print TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available)	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Drivers available for download from www.usa.canon.com GENERAL SPECIFICATION 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available)	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com S 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available)	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty4 (Extended Warranty available)
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s) Network Interface USB Functions Network Functions Network Frotocol Bundled Software OS Compatibility Dimensions Weight (with Cartridge) Warranty Power Consumption	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed³ 10/100 Base T Print/Scan Print TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, X p. 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode)	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB Windows Vista, X Pace 2000, New Soft® OwniPage® SE (OCR), NewSoft® Prestol PageManager GENERAL SPECIFICATION 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode)	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB. Windows Vista, X p. 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Tivers available for download from www.cusa.canon.com S 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode)	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB- Windows Vista, X 9200 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty 4(Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode)
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s) Network Interface USB Functions Network Functions Network Frotocol Bundled Software OS Compatibility Dimensions Weight (with Cartridge) Warranty Power Consumption Replacement Consumable	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed³ 10/100 Base T Print/Scan Print TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB- Windows Vista, X 9200 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode) Canon Cartridge 120 (Starter Cartridge included)	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB- Windows Vista, Xepver 2003, XP, 2000 Drivers available for download from www.cusa.canon.com GENERAL SPECIFICATION 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode) Canon Cartridge 120 (Starter Cartridge included)	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, HI-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager LUSB- Windows Vista, X p. 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com S 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode) Canon Cartridge 120 (Starter Cartridge included)	Up to 600 x 600 dpi (optical); Up to 960 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB- Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode) Canon Cartridge 120 (Starter Cartridge included)
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s) Network Interface USB Functions Network Functions Network Frotocol Bundled Software OS Compatibility Dimensions Weight (with Cartridge) Warranty Power Consumption Replacement Consumable Cartridge Type	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed³ 10/100 Base T Print/Scan Print/Scan Print TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode) Canon Cartridge 120 (Starter Cartridge included) Single Cartridge System	Up to 600 x 600 dpi (optical); Up to 9600 x 600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager LUSB: Windows Vista, X, P. 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com GENERAL SPECIFICATION 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode) Canon Cartridge 120 (Starter Cartridge included) Single Cartridge System	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager LSB. Windows Vista, X, P. 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com S 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode) Canon Cartridge 120 (Starter Cartridge included) Single Cartridge System	Up to 600 x 600 dpi (optical); Up to 960 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB- Windows Vista, X 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode) Canon Cartridge 120 (Starter Cartridge included) Single Cartridge System
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s) Network Interface USB Functions Network Functions Network Frotocol Bundled Software OS Compatibility Dimensions Weight (with Cartridge) Warranty Power Consumption Replacement Consumable Cartridge Type Cartridge 120	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed³ 10/100 Base T Print/Scan Print TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode) Canon Cartridge 120 (Starter Cartridge included) Single Cartridge System Vields approx. 5,000 pages based on ISO/IEC Standard	Up to 600 x 600 dpi (optical); Up to 9600 x 600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax/Scan TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com GENERAL SPECIFICATION 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode) Canon Cartridge 120 (Starter Cartridge included) Single Cartridge System Vields approx. 5,000 pages based on ISO/IEC Standard	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com S 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode) Canon Cartridge 120 (Starter Cartridge included) Single Cartridge System Vields approx. 5,000 pages based on ISO/IEC Standard	Up to 600 x 600 dpi (optical); Up to 960 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, X.P. 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode) Canon Cartridge 120 (Starter Cartridge included) Single Cartridge System Vields approx. 5,000 pages based on ISO/IEC Standard
Color Depth Document Size Compatibility Output File Formats Scan to E-mail Other Protocols Output File Formats Standard Interface(s) Network Interface USB Functions Network Functions Network Frotocol Bundled Software OS Compatibility Dimensions Weight (with Cartridge) Warranty Power Consumption Replacement Consumable Cartridge Type Cartridge 120 Duty Cycle	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP USB 2.0 Hi-Speed³ 10/100 Base T Print/Scan Print/Scan Print TCP/IP Canon drivers for Windows®, ScanSoft® OmniPage® SE (OCR), NewSoft® Prestol PageManager USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode) Canon Cartridge 120 (Starter Cartridge included) Single Cartridge System	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP SEND SPECIFICATIONS INTERFACE/SOFTWARE USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 dpi (interpolated) 24-bit Platen: Up to 8.5" x 14"; ADF: Up to 8.5" x 14" TWAIN, WIA JPEG, PDF, TIFF, BMP Yes Scan to SMB JPEG, Hi-compression PDF, PDF, TIFF USB 2.0 Hi-Speed³ 10/100 Base T Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax/Scan Print/PC Fax/Scan USB: Windows Vista, XP, 2000 Network: Server 2008, Windows Vista, Server 2003, XP, 2000 Drivers available for download from www.cusa.canon.com 17.7" (W) x 18.6" (D) x 18.3" (H) Approx. 48.5 lbs 1 year limited warranty* (Extended Warranty available) 1090W (Max), 3W (Energy Saver Mode) Canon Cartridge 120 (Starter Cartridge included) Single Cartridge System Vields approx. 5,000 pages based on ISO/IEC Standard Up to 20,000 pages per month

1 Based on 20 lb. paper 2 Based on ITUT #1 Chart (standard mode) 3 USB 2.0 Hi-Speed requires Windows Vista, Windows XP, 2000. 4 Warranty program is subject to certain conditions and restrictions. See the warranty card for details.













