

Duplex Copier | Laser Printer | Color Network Scanner | Super G3 Fax | Network Capabilities

# Canon

## imageCLASS® MF7480



(shown with optional cabinet)

### Advanced Network Performance with 11" x 17" Capability

- Up to 25 pages-per-minute laser output
- Duplex versatility — automatic two-sided copying, printing, faxing, and color network scanning
- 1/4 VGA Touch Screen Panel
- PCL 5e/6 and Canon UFR II-LT language support
- Built-in Ethernet port for printing, PC faxing, color network scanning, and remote user interface
- Universal Sending
- 33.6 Kbps Super G3 fax with up to 1,000 pages of reception memory<sup>1</sup>
- 2 x 250-sheet cassettes plus 80-sheet multipurpose tray
- 11" x 17" platen and 50-sheet Automatic Document Feeder<sup>2</sup>
- USB 2.0 Hi-Speed<sup>3</sup> for optimal performance
- Single Cartridge System

All the elements you will ever need in a digital multitasking machine.

The imageCLASS MF7480 incorporates a rich array of input and output features that can greatly enhance your efficiency. Equipped with features that meet the needs of document work in a digitized office, the ImageCLASS MF7480 represents the ultimate in digital multitasking machines.

#### Copy Function:

Built on a copying platform, the imageCLASS MF7480 offers many convenient copy features. Standard features such as a 50-sheet Auto Document Feeder, 11" x 17" paper support, 580 total page capacity and high yield cartridge allows most copying jobs to flow without interruption. Convenient features such as duplexing allows two-sided copying and 2/4 in 1 allows you to fit two or four pages on one side of paper. The imageCLASS MF7480 also includes other features such as zoom from 50% to 200% in 1% increments, output collating, margin/frame erase and more!

#### Print Function:

Whether local or through the network, the imageCLASS MF7480 is a laser printer as well. With a total of 3 paper input sources, you can stock any combination of paper sizes and stock from envelopes up to 11" x 17" paper. The imageCLASS MF7480 utilizes Canon's Ultra-Fast Rendering (UFR II-LT) technology, or PCL with up to 122 different fonts. Built-in two-sided printing also increases productivity, and saves paper.

#### Send/Fax Function:

Forget about interoffice mail, with the imageCLASS MF7480 you can now digitize your documents and send them directly over the network or to any email address. Sending doesn't require a dedicated computer, nor any paper or consumables which can save you time and money. Sending offers businesses a new outlook in document archiving, sending, and retrieving. It can improve the whole way you do business.



#### Remote UI Function

The Remote User Interface allows managing, editing, and checking of the machine's functions and settings over the network through a computer's web browser. You can add or edit the address book, check on copy or print jobs, customize system settings such as managing users' IDs, and more.

<sup>1</sup> Based on ITU-T #1 Chart (standard mode).

<sup>2</sup> Based on 20 lb. paper.

<sup>3</sup> USB 2.0 Hi-Speed performance requires Windows®XP Service Pack 1 or Windows®2000 Service Pack 4 with pre-installed USB 2.0 port.


# imageCLASS® MF7480



- a Duplex Automatic Document Feeder
- b Control Panel with Backlit Touch Screen Display
- c Internal Output Tray (no protruding output trays)
- d Extendable 80-sheet Multipurpose Tray Paper Tray
- e 2 x 250-sheet cassettes

## Control Panel

The control panel consists of a backlit touch screen display for setting various functions through a user friendly menu. The touch panel makes sophisticated functions simple and easy to use.



## imageCLASS® MF7480

### An array of powerful features

#### What You Can Do...

##### Enlarge/Reduce an Image to Copy to a Different Size Paper

This function is useful when enlarging or reducing an original of one standard paper size to another, such as enlarging a letter-sized original to legal size, or reducing legal to letter size. Simply select the desired paper size from the displayed keys to automatically set the optimal zoom ratio.

##### Make Two-Sided Copies


When copying many single-sided originals, printing on both the front and back sides of paper can help you save half of the paper costs.

##### Copy Multiple Originals onto One Sheet of Paper

This mode enables you to reduce multiple originals or two-sided originals to fit onto one sheet of paper. This is useful for arranging a variety of originals on one sheet of paper for easy viewing and for saving paper and space when storing printouts.

##### You Get the Big Picture


Double your productivity with an 11.75" x 17" platen. You can fit 2 letter-size (8.5" x 11") documents onto one side of an 11" x 17" sheet or four onto two sides.



#### Universal Sending

##### Scan-to many Destinations such as Email, Network Folder, File Server, Fax And I-fax

You can easily scan paper documents and send them to one or multiple recipients through e-mail, or I-fax, bringing to your work environment increased efficiency in the arena of document exchange. I-fax enables you to send a fax or e-mail via an Internet network. The ability to send documents to FTP and SMB file servers also serves to help digitize paper documents for convenient data access and management. PDF High Compression Mode allows you to send large file sizes clearly and quickly with excellent quality.



#### Multifunction Performance

##### The Network Solution

Maximize your office productivity with the imageCLASS MF7480's built-in Ethernet port. The Ethernet port empowers your workgroup with network printing for shared productivity, PC-faxing where users can fax directly from their PC, and universal sending which allows you to send documents over the network or to any e-mail address.

#### Canon Single Cartridge System

With one machine, you need to stock only **one** consumable for the many functions. Adding to the convenience is Canon's Single Cartridge System – the easy-to-replace cartridge that simplifies maintenance by combining the toner, drum and other moving parts into one unit. Every time you change the cartridge, you are also maintaining the machine, keeping it hassle-free. A full-yield cartridge is included, and for more peace of mind, the imageCLASS MF7480 also includes a 1 year limited warranty with on-site service.<sup>6</sup>



# imageCLASS® MF7480

## Technical Information

### PAPER HANDLING (FOR ALL FUNCTIONS)

PAPER FEEDING SYSTEM	<b>Paper Drawers:</b> 250 sheets <sup>1</sup> x 2 drawers <b>Stack Bypass:</b> 80 sheets <sup>1</sup> (LTR/LTRR/STMT/STMTR/EXEC/A4/A4R/B5R/B5/A5R/A5) 50 sheets <sup>1</sup> (LGL/11" x 17"/A3/B4) 50 sheets (Transparencies/Heavyweight paper, 24 lb to 32 lb bond), 10 envelopes, 1 sheet (Labels)
PAPER SIZES	<b>Paper Drawer:</b> 11" x 17", LGL, LTR, LTRR, and STMT <b>Stack Bypass:</b> 11" x 17", LGL, LTR, LTRR, STMT, STMTR, EXEC, Irregular Size (3-3/4" x 5-7/8" to 11-3/4" x 17") and Envelopes (ISO-B5, ISO-C5, COM10, DL, and Monarch)
PAPER STOCK	<b>Paper Drawer:</b> 18 lb to 24 lb bond Plain, Recycled, Color, 3-hole punch, Heavy, Bond <b>Stack Bypass:</b> 18 lb to 32 lb bond Plain, Recycled, Color, 3-hole punch, Bond, Heavy, Transparencies, Labels, Envelopes (ISO-B5, ISO-C5, COM10, DL, and Monarch)
MAXIMUM ORIGINAL SIZE	Platen: Up to 11-3/4" x 17"; ADF: Up to 11" x 17"
OUTPUT CAPACITY, ORIENTATION	Up to 250 sheets <sup>1</sup> , Face Down
SENDING ORIGINAL SIZES	11" x 17", LGL, LTR, LTRR, STMT, or STMTR; I-Fax up to LGL
RECEIVING PAPER SIZES	11" x 17", LGL, LTR, LTRR, STMT, or STMTR; I-Fax up to LGL

### COPIER SPECIFICATIONS

DUPLEX COPY/BIND TYPE	1 to 1, 2 to 1, 2 to 2/Book, Calendar
COPIER TYPE	Desktop, Monochrome Laser
WARM-UP TIME	26 seconds maximum after powering ON <sup>2</sup>
FIRST COPY TIME	6.9 seconds <sup>3</sup>
COPY SPEED (SHEETS PER MINUTE)	Up to 25 cpm (A4)
COPY RESOLUTION	Up to 600 X 600 dpi, 1200 x 600 dpi quality
NUMBER OF TONES	256 levels
REDUCTION/ENLARGEMENT	50%, 64%, 73%, 78% / 121%, 129%, 200%
ZOOM	50% - 200% in 1% increments
COPY FEATURES	2 in 1, 4 in 1, Collate
COPY MEMORY	256MB (shared)

### PRINTER SPECIFICATIONS

DUPLEX PRINT	Yes
PRINTER TYPE	Monochrome Laser
PRINT RESOLUTION	Up to 1200 x 1200 dpi, 1200 x 1200 dpi quality
PRINT SPEED (SHEETS PER MINUTE)	11" x 17": 10, LGL: 10, LTR: up to 20, LTRR: 11, STMT: 15
PRINT LANGUAGES	PCL5e, PCL6, and Canon URF II-LT
RESIDENT FONTS	<b>PCL:</b> 80 Scalable fonts, 30 Barcode fonts, 2 OCR fonts, and 10 Bitmap fonts
PRINTABLE AREA	<b>PCL5e, PCL6:</b> Reduced to 1/8" (4.23 mm) from the top, bottom, left, and right edges of the paper. <b>URF II:</b> Reduced to 1/4" (5 mm) (for Envelope: 3/8" (10 mm)) from the top, bottom, left, and right edges of the paper.
PRINT MEMORY	256MB (Shared)
SYSTEM MEMORY (ON BOARD)	256MB (Shared)

### UNIVERSAL SEND SPECIFICATIONS

DUPLEX SCAN	Yes
SCANNER TYPE	Color Contact Image Sensor (CIS)
COLOR DEPTH	24-bit
SENDING METHODS	E-mail, I-Fax, Super G3 Fax, File Server (FTP, SMB)
COMMUNICATION PROTOCOL	TCP/IP
RESOLUTIONS	<b>For Scan to E-mail:</b> 100 x 100 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x 400 dpi; 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi; <b>For Sending I-Fax:</b> 200 x 100 dpi, 200 x 200 dpi
FILE FORMATS	<b>E-mail, FTP or SMB:</b> PDF (Compact, Color, B&W), JPEG (Color), Tiff (B&W) <b>I-Fax:</b> TIFF (MH, B&W)
SYSTEM ENVIRONMENTS	Windows 98/Me/Vista (SP6a)/XP, Windows 2000 Server/Professional (SP1 or later), Windows Server 2003, Solaris Version 2.6 or later, Mac OS X 10.1.5 & up, Red Hat Linux 7.2
INTERFACES	USB 2.0, 100BASE-TX, 10BASE-T
ORIGINAL SIZES	<b>E-mail, FTP or SMB:</b> 11" x 17", LGL, LTR, LTRR, STMT, STMTR <b>I-Fax (sent as letter):</b> LGL, LTR, LTRR, STMT, STMTR
ORIGINAL TYPES	Text, Text/Photo, Photo
SERVER SOFTWARE	Microsoft Exchange Server 5.5 (SP2), Sendmail 8.11.2, Lotus Domino R4.5/R5
DESTINATIONS	E-mail, FTP, SMB, I-Fax
ADDRESS BOOK	Up to 500 entries

### FAX/PC FAX SPECIFICATIONS

DUPLEX FAX	Yes (transmission/reception)
TELEPHONE LINE USED/ NUMBER OF LINES	Public Switched Telephone Network, 1 line
SCAN LINE DENSITY (SCAN, TRANSMISSION)	200 x 100 dpi, 200 x 200 dpi, 400 x 400 dpi
TRANSMISSION SPEED	Super G3: up to 33.6 kbps
COMPRESSION METHOD	MH, MR, MMR, JBIG
TRANSMISSION TIMES	<b>JBIG:</b> Approximately 2.6 seconds <b>ECM-MMR:</b> Approximately 3.2 seconds <b>G3MR method:</b> Approximately 13 seconds <b>G3MH method:</b> Approximately 13 seconds
AUTO DIAL FUNCTION	Address Book: 300 destinations; One-touch buttons: 200 destinations
FAX MEMORY	Up to 1,000 pages <sup>4</sup>
RECEIVE MODES	Fax only, Manual, Answering
FAX FEATURES	Remote RX, Relay, Delayed TX, Dual Access
MEMORY BACKUP	Yes (1 hour)

### INTERFACE/SOFTWARE

STANDARD INTERFACE(S)	USB 2.0 Hi-Speed <sup>5</sup> , Internal Ethernet (10/100 Base T)
NETWORK FUNCTION(S)	Print, PC Fax and Send
BUNDLED SOFTWARE	Canon Printer Driver, Remote UI, NetSPOT Device Installer, NetSPOT Console
OS COMPATIBILITY	Windows® Vista™, XP, 2000, Me, 98 and Mac® OS X 10.2.8 & up

### GENERAL SPECIFICATIONS

DIMENSIONS	24.5"(W) x 26.3"(D) 29.8"(H)
WEIGHT	128 lbs. (58kg)
POWER SOURCE	120 V AC, 60 Hz, 4.6 A
MAX POWER CONSUMPTION	1,425W (max), 3.5W (Energy Saver Mode)
REPLACEMENT CONSUMABLE	Canon Cartridge 105
WARRANTY	1 year limited warranty with on-site service <sup>6</sup>

### ORDERING INFORMATION

PRODUCT	ITEM CODE
imageCLASS MF7480	2237B008AA
Cartridge 105 (yields 10,000 pages based on 5% coverage)	0265B001AA
imageCLASS MF7200/ MF7400 Cabinet	5709A006AA
imageCLASS MF7480 2-year Onsite Carepak	6521A037AA

Features and specifications are subject to change without notice.

For More Information Visit  
[www.usa.canon.com/consumer](http://www.usa.canon.com/consumer)

For the name of the nearest dealer, call:  
**1-800-OK-CANON**

Canon U.S.A., Inc. One Canon Plaza, Lake Success, NY 11042  
**1-800-OK-CANON**

- Based on 20 lb. paper.
- Activation time may vary depending on the conditions under which the machine is being used. (In all cases, at a room temperature of 68°F (20°C))
- LTR, direct, paper drawer 1
- Based on ITU-T #1 Chart (standard mode).
- USB 2.0 Hi-Speed performance requires Windows®XP Service Pack 1 or Windows®2000 Service Pack 4 with pre-installed USB 2.0 port.
- Warranty program is subject to certain conditions and restrictions. See the warranty card for full details.



©2007 Canon U.S.A., Inc. Canon and imageCLASS are registered trademarks of Canon Inc. The Super G3 logo is a trademark of Canon Inc. imageANYWARE is a trademark of Canon U.S.A., Inc. Microsoft, Windows, the Windows logo and Windows Vista are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. The Mac logo, Mac OS, and Macintosh are trademarks of Apple Computer, Inc., registered in the United States and other countries. All other product and brand names are trademarks of their respective owners. Specifications are subject to change without notice. As an ENERGY STAR partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR guidelines for energy efficiency. The limited warranty given by Canon U.S.A., Inc. is for Canon imageCLASS MF7480 model purchased and used in the United States.

**Canon**  
imageANYWARE