

# Canon

*LASER CLASS 2050P*



**WORKGROUP  
SYSTEMS**



# LASER CLASS 2050P

Canon's LASER CLASS® 2050P is the perfect fit for workgroups or small offices that require clear and accurate facsimile and laser printing capabilities as well as a remarkably small footprint. The LASER CLASS 2050P provides the quality you expect from award-winning Canon multi-function LASER CLASS devices. With a range of productivity features like face-down collated output for instant use of documents, Full Dual Access that enables you to scan and fax at the same time, and a user-friendly control panel, the LASER CLASS 2050P gives you powerful and reliable solutions for your enterprise.

## The LASER CLASS 2050P offers the following features:

- Powerful, high-speed faxing and laser printing using a standard, built-in Windows® Printer Driver for Windows 98/2000/Me and XP via a standard USB
- 3-second-per-page\* transmission speed via 33.6 Kbps modem
- Supports Super Fine Mode
- 6-page-per-minute desktop laser printing
- 6-page-per-minute fax printing with 600 dpi resolution

- 200 dpi scan resolution
- 4MB memory (up to 256 pages\*\*)
- Standard 350-sheet paper capacity—one 250-sheet Front-loading letter-/legal-sized adjustable Cassette, and one 100-sheet letter-/legal-/A4-sized MultiPurpose Tray
- Compact size, designed for desktop use
- 40-sheet Automatic Document Feeder\*\*\*
- 6,000-page-per-month print volume
- Face-down collated output
- FX3 Cartridge and handset included

## LASER CLASS 2050P Specifications

<b>Type:</b>	Desktop Transceiver
<b>Applicable Line:</b>	Public Switched Telephone Network
<b>Compatibility:</b>	G3
<b>Automatic Document Feeder:</b>	Up to 40 Letter-sized Sheets Up to 20 Legal-sized Sheets
<b>Scanning Method:</b>	Contact Image Sensor
<b>Document Sizes:</b>	Maximum: 8.5" x 14" (216mm x 355.9mm) Minimum: 5.8" x 4.1" (148mm x 105mm) Manual Document Feed: 8.5" x 39" Approx. (216mm x 1m Approx.) Manual Document Feed: 5.8" x 4.1" (148mm x 105mm)
<b>Effective Scanning Width:</b>	8.4" (214mm)
<b>Scanning Resolution:</b>	600 dpi
<b>Data Compression System:</b>	MH, MR, MMR
<b>Modem Speed:</b>	33.6/31.2/28.8/26.4/24.0/21.6/ 19.2/16.8/14.4/12.0/9.6/7.2/4.8/ 2.4 Kbps Automatic Fallback
<b>Transmission Speed:</b>	Approx. 3 Sec./Page*
<b>Printing Method:</b>	Laser Dry Electrostatic Transfer
<b>Printing Speed:</b>	Approx. 6 Pages/Min. (LTR)
<b>Halftone:</b>	64 Shades of Gray
<b>Tx/Rx Resolution:</b>	Horizontal Vertical
Super Fine Mode:	203 pels/in. x 391 lines/in. (8 pels/mm x 15.4 lines/mm)
Fine Mode/Photo Mode:	203 pels/in. x 196 lines/in. (8 pels/mm x 7.7 lines/mm)
Standard Mode:	203 pels/in. x 98 lines/in. (8 pels/mm x 3.85 lines/mm)
<b>Effective Recording Width:</b>	8.2" (208mm)
<b>Recording Paper Supply:</b>	350 Sheets: 250-sheet Cassette (LTR) 100-sheet MultiPurpose Tray (LTR/LGL)

<b>Receiving Paper Tray:</b>	50 Sheets, Face-down
<b>Recording Paper Size:</b>	Letter/Legal/A4
<b>Enhanced Imaging Quality:</b>	UHQ™ (Ultra High Quality)
<b>Printing Resolution:</b>	600 dpi
<b>Printer Cartridge:</b>	FX3 Cartridge
<b>Cartridge Yield:</b>	Approx. 2,700 Pages (based on 5% coverage)
<b>Power Consumption:</b>	Max: 660W
<b>Standby:</b>	Approx. 5W
<b>ENERGY STAR® Compliant:</b>	Yes
<b>Handset:</b>	Standard
<b>Dimensions (H x W x D) (Excluding Handset):</b>	12.0" x 15.0" x 19.1" (303.5mm x 380mm x 483mm)
<b>Weight (Excluding Handset and Tray):</b>	28.7 lb. (13kg)
<b>Environmental Conditions:</b>	Temperature: 50°F - 90.5°F (10°C - 32.5°C) Humidity: 20% - 80% RH
<b>Printing:</b>	Windows Printer Driver Included Print Speed (Black): 6 ppm Monthly Print Volume: 6000 Prints Print Resolution: 600 x 600 dpi Support OS: Windows 98/2000/Me/XP IF: USB
<b>Dialing:</b>	Automatic Dialing One-touch Speed-dialing: 24 Locations Coded Speed-dialing: 100 Locations Group Dialing: 123 Groups Each Group Can Accommodate Up to 123 Locations Maximum Dial Digits: 120 On-hook Dialing Manual Dialing with 10-button Keypad Automatic Redialing: Redial Times: 1 to 10 Times Redial Interval: 2 to 99 Min.

<b>Networking:</b>	Delayed Transmission: Up to 125 destinations and Up to 20 Reservations Memory Polling Transmission Polling Reception: Up to 125 Locations Sequential Broadcast: Up to 125 Locations Relay Broadcast Command/Delayed Relay Broadcast Command Memory Transmission/Reception: 4MB (Up to 256 pages**) Receiving Restriction Auto Receive Reduction (70% - 100%) Remote Reception by Extension Phone Transmission Reservation: Up to 20 Reservations Quick On-Line Tx LCD (Liquid Crystal Display): 20-digit x 2-line Local Copy Function: Multiple Copies Up to 99 Pages Memory Backup: One Hour (Daylight Savings Mode)
<b>Convenience:</b>	Activity Report (Up to 20 Transactions) Non-delivery Report 90 Days
<b>Report/Reference:</b>	
<b>Warranty:</b>	
* Approximate 3-second-per-page fax transmission time based on ITU-T No. 1 Chart (MMR, Standard Mode) at 33.6 Kbps modem speed when transmitting to another V.34 machine. The Public Switched Telephone Network (PSTN) currently supports 28.8 Kbps modem speeds or lower, depending on telephone line conditions.	
** Based on ITU-T No. 1 Chart (Standard Mode).	
*** 20 lb., less than 120 µm, 15-27.5° C, 20-80% RH	

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR certification are registered U.S. trademarks. Windows is a registered trademark of Microsoft Corporation in the United States and/or other countries. Canon and LASER CLASS are registered trademarks, and Canon Know How and the GENUINE logo are trademarks of Canon Inc. IMAGEANYWARE is a service mark of Canon U.S.A., Inc. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.

Specifications subject to change without notice.

**Canon** KNOW HOW™

1-800-OK-CANON  
www.usa.canon.com

Canon U.S.A., Inc.  
One Canon Plaza  
Lake Success, NY 11042

