

DSR 436 T

Powerful Digital Satellite Set-Top Box

Digital Satellite STB Series

▶ Satellite Demodulator (EN 300 421)

Waveform	QPSK
Symbol rate	17 to 30 Mbauds (variable)
Bandwidth	27/36 MHz
Freq. range	950 - 2150 MHz

LNB control:

Polarisation selection via LNB power line voltage	
Power	13/18 V - Short-circuit protected
DiSeqC	1.0

▶ MPEG Video Decoder

Standard	ISO13818-2 (MPEG-2)
Decompression	MPEG-2 Main Profile @ Main Level
Transfer rate	Up to 15 Mbps
Aspect ratio	4:3, 16:9, Pan & Scan, letter box
Video Scaling	1/4, 1/16

▶ MPEG Audio Decoder

Standard	ISO 11172-3 / ISO 13818-3
Decompression	MPEG Layers 1 & 2
Transfer rate	Up to 384 kbps
Sampling freq.	32, 44.1 and 48 kHz
Modes	Mono, Dual Channel, Joint Stereo, Stereo

▶ OSD / Graphics

Colours	From 16 colours to 65536
Transparency	16 levels
Graphics	4 layers
Overlay	MPEG still image insertion

▶ System Resources

Processor	LSI Logic SC2000 (MIPS family)
Frequency	108 MHz
System RAM	From 2 Mbytes up to 32 Mbytes
Video OSD/RAM	From 4 Mbytes up to 24 Mbytes
FLASH	From 2 Mbytes up to 8 Mbytes

▶ Teletext Processing

Transmitted teletext re-inserted in the composite video signal compliant with EN 300 472.

▶ Software

Operating system	MediaHighway™ DLI 3.xx & 4.xx Support for DVB-MHP
Access control	MediaGuard™

▶ Telephone Modem

See Options

▶ Interfaces

RF input	F-type, female
RF output	F-type, female (loopthrough)
SCART sockets	TV and VCR (with RGB loopthrough)
Audio	Twin RCA (left & right)
Telephone modem	RJ 11
Serial port	RS 232 (up to 115.2 kbps)
Smart card reader	2 x ISO 7816 1, 2 & 3
Display	4 digits x 7 segments
Front panel	6 buttons

▶ Remote Control

Infrared remote control

▶ General Data

Safety and EMC regulations compliant (CE marking)	
MTBF	> 80000 hours
Operating temperature	+10°C to +45°C
Storage temperature	-20°C to +70°C
Mains voltage	195 - 264 Volts (48/62 Hz)
Power consumption	Max. 30 W
Dimensions	360 x 230 x 65 mm

▶ Options

DVB-Common Interface
 Embedded Conax™ access control
 V23, V22/V22 bis, V32 bis or V90 telephone modem
 Multi TV (universal) remote control unit
 IEEE 1284 Sub-D25

Thomson multimedia

Broadband Access Products and Systems

46, quai Alphonse Le Gallo
 92100 Boulogne-Billancourt
 France

Tel. : 33 (0) 1 41 86 50 00

Fax : 33 (0) 1 41 86 56 59

E-mail : baps@thmulti.com

www.thomson-multimedia.com

Thomson multimedia S.A.
 with capital of €1,052,300,655
 333 773 174 R.C.S. Nanterre

© 2002 Thomson multimedia S.A. - All rights reserved.

Reproduction in whole or in part is expressly prohibited without the prior written consent of the copyright owner.

Thomson multimedia reserves the right to modify the specifications and pictures mentioned in this document at any time and without prior notice.

DSR 475 T

High Performance Digital Satellite Set-Top Box

Digital Satellite STB Series

▶ **Satellite Demodulator (EN 300 421)**

Digital Reception:

Waveform	QPSK
Symbol rate	17 to 30 Mbauds (variable)
Bandwidth	27/36 MHz
Freq. range	950 - 2150 MHz

LNB control:

Polarisation selection via LNB power line voltage	
Power	13 / 18 V - Short-circuit protected
DiSEqC	1.0

▶ **MPEG Video Decoder**

Standard	ISO13818-2 (MPEG-2)
Decompression	MPEG-2 Main Profile @ Main Level
Transfer rate	Up to 15 Mbps
Aspect ratio	4:3, 16:9, Pan & Scan, letter box

▶ **MPEG Audio Decoder**

Standard	ISO 11172-3 / ISO 13818-3
Decompression	MPEG Layers 1 & 2
Transfer rate	Up to 384 kbps
Sampling freq.	32, 44.1 and 48 kHz
Modes	Mono, Dual Channel, Joint Stereo, Stereo

▶ **OSD / Graphics**

Colours	16 colours
Transparency	16 levels
Graphics	4 layers
Overlay	MPEG stills image insertion

▶ **System Resources**

Processor	LSI Logic SC2005 (MIPS family)
Frequency	108 MHz
System RAM	From 2 Mbytes up to 32 Mbytes
Video / OSD RAM	From 2 Mbytes up to 24 Mbytes
FLASH	From 4 Mbytes up to 8 Mbytes

▶ **Teletext Processing**

Transmitted teletext re-inserted in the composite video signal compliant with EN 300 472

▶ **Software**

Operating system	MediaHighway™ DLI 3.xx & 4.xx Support for DVB-MHP
Access control	MediaGuard™ DVB - Common Interface

▶ **Telephone Modem**

See options

▶ **Interfaces**

RF input	F-type, female
SCART sockets	TV and VCR
Digital audio output	S/PDIF
Audio	Twin RCA (left & right)
Telephone modem	RJ 11
Serial port	RS 232 (up to 115.2 kbps)
Smart card reader	2 x ISO 7816 1, 2 & 3
Display	4 digits x 7 segments
Front panel	4 buttons

▶ **Remote Control**

Infrared remote control

▶ **General Data**

Safety and EMC regulations compliant (CE marking)	
MTBF	> 80000 hours
Operating temperature	+10°C to +45°C
Storage temperature	-20°C to +70°C
Mains voltage	195 - 264 Volts (48/62 Hz)
Power consumption	Max. 15 W
Stand-by consumption	2W
Dimensions	360 x 230 x 65 mm

▶ **Options**

Embedded Conax™ access control
V23, V22 / V22bis, V23bis
Multi TV (universal) remote control unit

Thomson multimedia

Broadband Access Products and Systems

46, quai Alphonse Le Gallo
92100 Boulogne-Billancourt
France

Tel. : 33 (0) 1 41 86 50 00

Fax : 33 (0) 1 41 86 56 59

E-mail : baps@thmulti.com

www.thomson-multimedia.com

Thomson multimedia S.A.
with capital of €1,052,300,655
333 773 174 R.C.S. Nanterre

© 2002 Thomson multimedia S.A. - All rights reserved.

Reproduction in whole or in part is expressly prohibited without the prior written consent of the copyright owner.

Thomson multimedia reserves the right to modify the specifications and pictures mentioned in this document at any time and without prior notice.