

HP LaserJet 3380 all-in-one printer/fax/scanner/copier



The HP LaserJet 3380 is a high-performance flatbed all-in-one with fast, professional quality black and white printing, faxing, colour scanning and digital copying for improved productivity of single users and small workgroups.

This all-in-one gives individuals and small workteams of up to 5 people in small and medium-sized businesses and corporate environments a complete and reliable office solution enabling them to print, fax, scan and copy professional quality documents easily and efficiently.

Be more productive with high-performance all-in-one-functionality and fast print and copy speeds.

- Enjoy fast, efficient printing and copying at up to 19 ppm. No waiting as Instant-on Technology delivers first page out in only 8 seconds.
- Handle complex jobs with 32 MB RAM (expandable to 96 MB), a 240 MHz processor and an additional 4 MB of fax memory for storing up to 250 pages of fax documents.
- A 50-sheet automatic document feeder enables unattended faxing and copying and, with the flatbed design, means you can copy a variety of original documents, including books and other bound materials.

Produce business quality documents which enhance your professional image.

- Produce high quality output with true 1200 dpi resolution for crisp and sharp laser printing.
- Easy-to-use scan software for high quality text and images with up to 9600 dpi enhanced resolution.
- Convert your documents to digital format for archiving or direct email transmission by only using a front-panel button.
- Transform hard copies into editable files using OCR* software.
- Share the value of this network-capable printer in a variety of environments using optional HP Jetdirect print servers.

Enjoy the versatile features of this flexible and reliable all-in-one.

- Professional, business-class faxing at up to 33.6 Kbps including delayed faxing and fax to PC.**
- Convenient multi-tasking ability gives you more efficiency, letting you scan or copy while print jobs are in progress.
- The 260-sheet input capacity supports the business needs of small workgroups.
- Clean and easy-to-replace all-in-one HP print cartridges.
- Enjoy simple, worry-free printing and copying with proven HP LaserJet reliability and a robust 10,000 page per month duty cycle.

*Optical Character Recognition software.

** Fax to PC available with Microsoft® Windows®.

Technical specifications

Print speed	Up to 19 ppm First page out: 8 secs for printing (Instant-on Technology virtually eliminating warm-up time – from cold or warm start) (Exact speed varies depending on the system configuration, software program, and document complexity)		
Processor	240 MHz, Motorola Coldfire® v 4e		
Memory	32 MB, expandable to 96 MB through one DIMM slot		
Print quality	1200 x 1200 dpi		
Print margins (A4)	Top: 4.2 mm, left: 4.2 mm, right: 4.2 mm, bottom: 4.2 mm		
Print	Technology:	Monochrome Laser	
	Languages:	HP PCL 6, HP PCL 5e, HP Postscript Level 2 Emulation	
	Economical printing:	Economode print quality setting prints text with less toner. This setting is useful when printing drafts. This setting can be used independent of other print-quality settings.	
	Typefaces/fonts:	PCL: 45 scalable TrueType fonts, PostScript: 35 scalable TrueType fonts	
	Duty cycle:	Up to 10,000 pages per month	
Fax	Modem:	33.6 Kbps (3 secs per page)	
	Telecom:	TBR-21:1998; EG 201 121:1998, FCC Part 68	
	Memory:	Up to 250 pages (4 MB)	
	Resolution:	Standard: 203 x 98 dpi, fine: 203 x 196 dpi, superfine: 300 x 300 dpi (no halftone), photo: 300 x 300 dpi (halftone enabled)	
	Quick dialing:	120 numbers, 9 one-touch front panel keys	
Scan	Type:	A4 oversize flatbed, ADF, colour scanning	
	Resolution:	600 x 600 dpi optical, 9600 x 9600 dpi enhanced	
	Bit depth:	24-bit	
	Levels of grey:	256	
	Twain version:	Twain compatible version 1.9	
	Scannable area:	Minimum media size: 127 x 127 mm (from ADF), maximum media size: 216 x 381 mm (from ADF), 216 x 356 mm (from flatbed)	
	Margins for scanned items:	Left: 4.2 mm, top: 4.2 mm, right: 4.2 mm, bottom: 5.0 mm	
Copy	Speed:	Up to 19 cpm	
	Multiple copies:	1-99 copies, with automatic collation	
	Reduce/enlarge:	25 to 400% (1% increments)	
Media handling	Input	Weight	Size
	Tray 1	Input tray: 60 to 163 g/m ² (recommended: 75 to 90 g/m ²); automatic document feeder (ADF): 60 to 90 g/m ² ; output bin: 60 to 105 g/m ² ; straight-through media path: 60 to 163 g/m ²	Standard: A4, A5, Letter, Legal, B5, C5, C6, DL; 76 x 127 to 216 x 356 mm; automatic document feeder (ADF): A4, A5; 127 x 127 to 216 x 381 mm
	Capacity:	250 (main input tray), 10 (priority feed), 50 (ADF)	
	Output:	Sheets: 125, envelopes: 15, transparencies: 100	
	Duplex printing:	Manual (driver support provided)	
Media types	Paper (plain, preprinted, prepunched, bond, colour, glossy, letterhead, light, heavy, recycled, rough), envelopes, transparencies, labels, cardstock		
Interface and connectivity	USB port – compatible with 2.0 specifications; parallel port – IEEE 1284-B Optional: HP Jetdirect external print servers and wireless print servers: HP Jetdirect 170x, 175x, 300x, 380x, 500x, en3700, bt1300		
Operating systems compatibility	Microsoft® Windows® 98 Second Edition, 2000, Me, XP; Windows NT® 4.0 print driver only; Mac OS 9.1, 9.2.x, Mac OS X v10.2.x; DOS, Linux, UNIX, OS/2 print functionality only available on web Latest drivers available from http://www.hp.com		
Network operating systems compatibility	Optional: Via HP Jetdirect 170x print server: Microsoft® Windows® 98, NT 4.0, 2000, Novell™ NetWare 3.2, 4.2, 5.x; via HP Jetdirect 175x print server: Microsoft Windows 98, Me, NT 4.0, 2000, XP, XP 64-Bit, Server 2003, Apple Mac OS 8.6 and later, via HP Jetdirect 300x, 500x print servers: Microsoft Windows 98, Me, NT 4.0, 2000, XP, Novell NetWare 3.2, 4.2, 5.x, 6, Apple Mac OS 8.6 and later, Red Hat Linux 6.x and later, SuSE Linux 6.x and later, HP-UX 10.20, 11.x, Solaris™ 2.5x, 2.6, 7, 8 (SPARC systems only), IBM® AIX 3.2.5 and later, MPE-iX; via HP Jetdirect 380x, en3700 print servers: Microsoft Windows 98, Me, NT 4.0, 2000, XP, XP 64-Bit, Server 2003, Novell NetWare 3.2, 4.2, 5.x, 6, Apple Mac OS 8.6 and later, Red Hat Linux 6.x and later, SuSE Linux 6.x and later, HP-UX 10.20, 11.x, Solaris 2.5x, 2.6, 7, 8 (SPARC systems only), IBM AIX 3.2.5 and later, MPE-iX		
Minimum system requirements	Windows® 98: Pentium® processor or better, 24 MB RAM; Windows Me: Pentium 150 MHz or better, 32 MB RAM; Windows NT® 4.0: Pentium or better, 32 MB RAM; Windows 2000: Pentium 133 MHz or better, 64 MB RAM; Windows XP: Pentium 300 MHz or better, 128 MB RAM Mac 9.1: Mac OS-based Apple computer with a PowerPC microprocessor, at least 32 MB of RAM with virtual memory set to 64 MB; Mac 9.2.x: Power Mac G4 or Macintosh Server G4 (all models), Power Macintosh G3 or Macintosh Server G3 (all models), iMac (all models), iBook (all models), Powerbook (all models later than the original PowerBook G3), at least 32 MB RAM with virtual memory set to 64 MB; Mac OS X v 10.2.x: Power Mac G5 (all models), Power Mac G4 or Macintosh Server G4 (all models), Power Macintosh G3 or Macintosh Server G3 (all models), iMac (all models), iBook (all models), Powerbook (all models later than the original PowerBook G3), 128 MB RAM		
Standard software	HP Toolbox, HP LaserJet Scan, TWAIN or WIA Scan Driver, HP LaserJet Fax, Readiris OCR (not installed with other software; separate installation required), printer drivers (HP PCL 6, HP PCL 5e, HP Postscript Level 2 Emulation), installer/uninstaller, HP Director (Macintosh), HP all-in-one Setup Assistant		
Control panel	Fax controls, alphanumeric buttons, menu and cancel controls, copy controls, scan controls, 2 line x 16-character display		
Printer management	HP Toolbox; HP Web Jetadmin, Embedded Web Server (with optional HP Jetdirect external print servers)		
Power requirements	Input voltage 220 to 240 VAC (± 10%), 50/60 Hz (± 2 Hz), 2.3 amp		
Power consumption	330 watts maximum (printing), 12 watts (standby and PowerSave), 0 watt (off)		
Dimensions (w x d x h)	Out of package: 546 x 521 x 495 mm, packaged: 600 x 496 x 595 mm		
Weight	Out of package: 15.8 kg, packaged: 18.5 kg		
Operating environment	Environmental ranges: Operating temperature: 15 to 32.5° C, operating humidity: 10 to 80% RH, storage temperature: -20 to 40° C, storage humidity: 0 to 95% RH. Noise level per ISO 9296: sound power: LwAd 6.1 B(A) LwAd (printing at 19 ppm), sound pressure: LpAm 56 dB(A) (operator position), 47 dB(A) (bystander)		
Product certifications	Safety certifications: IEC 60950: 1999/EN 60950: 2000; IEC 60825-1: 1993 + A1:1996 + A2: 2001/EN 60825-1: 1994 + A11: 1996 + A2: 2001 (Class 1 Laser/LED Product); GB4943-1995. EMC certifications: CISPR 22: 1998/EN 55022: 1998 – Class B; EN 61000-3-2: 1995/A14:2000; EN 61000-3-3: 1995; EN 55024: 1998; FCC Title 47 CFR, Part 15; Class B 2/ICES-003, Issue 3; GB9254-1998. Energy Star®		
Warranty	One-year limited warranty covers HP hardware, software, accessories, and supplies		

<http://www.hp.com>

For more information, please call your local HP sales office or representative: **Austria:** 0800 242 242, **Algeria:** (0)61 56 45 43, **Bahrain:** 800 728, **Belgium:** (078) 15 20 30 (0.0496 EUR/min), **Bulgaria:** (+359) 2960 1940, **Croatia:** (+385 1) 60 60 200, **Czech Republic:** (00 420 2) 261 108 108 (Prague), **Denmark:** 45991700 or 70101125, **Egypt:** 532 5222, **Estonia:** (+372) 6813 823, **Finland:** (+358) 0205350 or 0205 350, **France:** (1) 69 82 6060, **Germany:** 0180 532 6222 (12 Cent/min), **Greece:** (01) 678 96 00, **Hungary:** (+36) 1 382-1111, **Iceland:** (354) 570 1000, **Ireland:** + 353 1 6158200, **Israel:** (972) 9 8304848, **Italy:** (02) 92121, **Kazakhstan:** +7 (3272) 980 824, **Latvia:** (371) 800 80 12, **Lithuania:** 8 800 10000 or 8 5 2103333, **Luxembourg:** (+352) 263 160 34, **Middle East:** 00971 4 883 4427, **Morocco (African Region):** +212 22 40 47 47, **Netherlands:** (020) 5476666, **Norway:** 22 735600, **Poland:** infolinia: 0-800 122 622, **Portugal:** (808) 206 001, **Romania:** (+401) 205 3300, **Russia:** +7 (095) 797 35 00, **Saudi Arabia:** 800 124 4646, **Serbia/Montenegro:** +381 11 334 21 02, **Slovakia:** +421-2-50222111, **Slovenia:** +3861 2307 420, **South Africa:** 0800 118 883, **Spain:** (91) 634 88 00, **Sweden:** (08) 444 2000, **Switzerland:** 0848 88 44 66, **Tunisia:** 71 891 222, **Turkey:** +90 (216) 579 71 71, **UAE:** 8004910, **UK:** 08705 474747, **Ukraine:** +380 44 490 61 20.



©2004 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA 02/04 5982-3614EEE

Ordering information

Q2660A	HP LaserJet 3380 all-in-one printer/fax/scanner/copier, HP LaserJet print cartridge, getting started guide, fax guide, device software including Optical Character Recognition (OCR) software and electronic user's guide on CD-ROM, 250-sheet media input tray, ADF input tray, power cord, phone cord
---------------	---

Memory	
C7845A	32 MB SDRAM DIMM
Q1887A	64 MB SDRAM DIMM

Supplies	
C7115A	HP Ultraprecise Standard Capacity Print Cartridge, black (up to 2,500 pages*)
C7115X	HP Ultraprecise Maximum Capacity Print Cartridge, black (up to 3,500 pages*)

Cables	
C6518A	HP USB cable – 2 m
C2950A	HP IEEE parallel cable (B-type) – 2 m
C2951A	HP IEEE parallel cable (B-type) – 3 m

HP Jetdirect external print servers	
J3258B	HP Jetdirect 170x external print server (parallel/10BT)
J6035C	HP Jetdirect 175x external print server (USB-10/100Base-TX)
J3263A	HP Jetdirect 300x external print server (parallel/10/100TX)
J6061A	HP Jetdirect 380x wireless external print server (USB – 802.11b)
J3265A	HP Jetdirect 500x external print server (3 port parallel-10/100Base-TX/10Base2)
J7942A	HP Jetdirect en3700 external print server
J6072A	HP BT1300 Bluetooth® Wireless Printer Adapter (for USB or parallel)

Service & support	
H5478A/E	HP Care Pack – next business day on-site response, 3 years
H5471A/E	HP Care Pack – next business day exchange, 3 years
H2649PA/PE	HP Care Pack – post warranty, next business day on-site response, 1 year

*Based on 5% coverage

