



Battery-Powered Wireless PresentationPro

Model PA150

- Ideal for mobile presenters, classroom and athletic uses
- Lightweight with built-in handle for easy mobility
- 16-channel UHF selectability for wireless mic
- Green, red and amber LEDs on front give visual confirmation of power, signal and reception
- Rechargeable 12V sealed lead-acid battery
- Separate bass, treble controls for quality sound
- Aux in and line inputs connect with LCD projectors, multimedia players, computers and whiteboards
- CE/C-UL approved safe for school, church, government uses
- Available wireless handheld (Q316), hands-free (M316 transmitter) and wired microphones
- Includes volume / mute remote control (not shown)



The battery-powered Wireless PresentationPro is an AC/DC powered, wireless PA system. With 16 selectable UHF channels and an internal battery, it can be used as a single, portable setup for presentations, emergency response situations, police needs, in meetings and for use by rental facilities.

"Project Intercept"

Please contact us immediately if you experience any difficulties with your PA150. Our "Project Intercept" customer service program will quickly repair or replace items under warranty. Simply contact us via phone or email warranty@califone.com

Visit our website at www.califone.com to learn more about the complete line of *Califone* audio enhancing and visual technology products including: Wired and Wireless public address systems and lecterns, wireless microphones, headphones & headsets, group listening centers, multimedia players and computer peripheral products.

We are proud of helping teachers enhance student understanding and achievements since 1947, with your satisfaction as our first priority.

The PresentationPro carries a limited six-year warranty and service support available through authorized dealers nationwide. Its warranty covers school use - unlike some other PA products whose warranties would be voided if used in schools.

Distributed by:

Specifications

Rated Power Output:	15 watts RMS
Sensitivity for Rated Output:	Line: 125 mVrms Microphone: 4 mVrms Auxiliary: 250 mVrms
Frequency Response:	60 Hz - 20 kHz ± 3dB
Dispersion Angle:	90° H x 120° V
Speakers:	Woofers: 5-1/4" High efficiency Tweeter: 13mm mylar dome
Crossover:	L/C - 6dB/Octave @ 4 kHz
Inputs:	Line inputs (2): Hi-Z, RCA (summing L+R) Balanced mic: Hi or lo-Z, with phantom power (+15 volts D.C.) Unbalanced mic: Lo -Z, 1/4"-phone Auxiliary: Hi-Z Mono 1/4"-phone
Line Output:	250mv constant
AC Power Requirements:	110 - 125 VAC, 50/60 Hz
Dimensions (HWD):	6-1/4" x 10" x 8-1/2"
UHF Receiver Specifications	
Channels:	16 Selectable
Frequency:	740 - 801.80MHz
Oscillation:	Phase Lock Loop, Synthesized
Modulation:	FM (Frequency Modulation)
Sensitivity:	7 microvolts
Frequency Response:	90 Hz - 17 KHz
Wireless Transmission Range:	Approximately 160 ft.
Dynamic Range:	100 dB
Battery:	12V sealed lead-acid, rechargeable 4 hour run time, 6 hour recharge cycle
Weight:	10 pounds, shipping weight 14 lbs.
Safety Approvals:	C-UL/CE approved safe for use in school, business, government and church facilities
Warranty:	6 years from date of purchase (PA only, all other parts one year)

Califone® International Inc. 800-722-0500
www.califone.com