



Model #: SUPDM15

Corded UPS Backplate Outlet Kit - Adds AC plug-in connection and AC output receptacles to SU6000RT3U and SU6000RT3UXR UPS for use with 240V UPS output voltage configurations



Highlights

- Converts Tripp Lite's hardwire SU6000RT3U UPS systems to one with AC plug and outlets
- For use with 240V mains and UPS output voltage configurations
- 10 ft. / 3m AC input power cable with NEMA L6-30P input plug
- 3 L6-30R and 10 5-15/20R output receptacles
- Easy quick-connect wiring installs in minutes

Description

Tripp Lite's SUPDM15 corded backplate kit converts Tripp Lite's hardwire SU6000RT3U or SU6000RT3UXR UPS system into one with AC plug and outlets. 10 ft./3m input line cord with L6-30P plug enables simple connection to 240V 30A mains power. Includes 3 L6-30R and 10 5-15/20R output receptacles. Easy guick-connect wiring installs in minutes.

VOLTAGE COMPATIBILITY NOTE - SUPDM15 supports SU6000RT3U and SU6000RT3UXR applications configured for 240V nominal input voltage only (See SUPDM16 for 208V input voltage configurations).

Applications

• Ideal for 240V applications calling for Tripp Lite's SU6000RT3U and SU6000RT3UXR UPS systems where plug-in AC input and output connections are required

Features

- Converts Tripp Lite's hardwire SU6000RT3U or SU6000RT3UXR UPS system to one with an AC plug and outlets
- 10 ft./3m AC line cord with L6-30P input plug-in connection
- Includes 3 L6-30R and 10 5-15/20R output receptacles
- Easy quick-connect wiring installs in minutes

Specifications

| SYSTEM OVERVIEW | | | |
|------------------------|---|--|--|
| Voltage compatibility | Compatible with Tripp Lite's SU6000RT3U UPS systems configured for 240V nominal input voltage | | |
| OUTPUT | | | |
| Output nominal voltage | Simultaneous 240 and 120V output | | |
| Outlet quantity / type | 240V: 3 L6-30R / 120V: 10 5-15/20R | | |
| Overload protection | 120V outlets are protected by 2 separate 20A branch rated circuit breakers | | |
| INPUT | | | |
| Input connection type | NEMA L6-30P input plug | | |

| Input cord length | 10 ft. / 3m |
|---------------------------------|------------------|
| Recommended Electrical Service | 30A 240V |
| PHYSICAL | |
| Shipping weight (lbs) | 6.6 |
| Shipping weight (kg) | 3 |
| Shipping Dimensions (HWD/in) | 5.5 x 9 x 14.25 |
| Shipping Dimensions (HWD/cm) | 14 x 22.9 x 36.2 |
| Unit weight (lbs) | 6 |
| Unit weight (kg) | 2.8 |
| Unit Dimensions (HWD/in) | 2.5 x 5 x 11 |
| Unit Dimensions (HWD/cm) | 6.4 x 12.7 x 28 |
| Material of construction | Steel |
| WARRANTY | |
| Product Warranty Period | 2 years |

Related Items

| Audio Cables | | |
|--------------|---|-----------------|
| PDU1230 | Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment | Qty: [optional] |
| PDUNV | Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment | Qty: [optional] |
| PDU40TDUAL | Basic PDU / Power Distribution Unit - Safe, dual-circuit power distribution for critical networking equipment | Qty: [optional] |
| PDUMH20AT | Metered PDU with ATS - Power Distribution Unit with dual-input Auto Transfer Switching | Qty: [optional] |
| PDUMV20 | Metered PDU / Power Distribution Unit - Safe, reliable power distribution with digital current meter | Qty: [optional] |
| PDUMV40 | Metered PDU / Power Distribution Unit - Safe, dual-circuit power distribution with current meters | Qty: [optional] |
| PDUMH20ATNET | Switched, Metered PDU with ATS - Power Distribution Unit with dual-input Auto Transfer Switching, individual outlet control and SNMP network interface | Qty: [optional] |
| PDUV30HV | Basic 0U Vertical Rack PDU - Power Distribution Unit for Network Applications | Qty: [optional] |
| PDUMV30HV | Metered 0U Vertical Rack PDU - Metered Power Distribution Unit for Network Applications | Qty: [optional] |
| PDUMH30HVNET | Switched, Metered PDU with Remote Monitoring - 2U Rackmount Power Distribution Unit for Networks with Individually Switchable Outlets, Current Metering, Remote Monitoring and Control | |
| PDUMV20NET | Switched, Metered PDU with Remote Monitoring - 0U Vertical Rackmount Power Distribution Unit for Networks with Individually Switchable Outlets, Current Metering, Remote Monitoring and Control | Qty: [optional] |
| PDUMV30HVNET | Switched, Metered PDU with Remote Monitoring - 0U Vertical Rackmount Power Distribution Unit for Networks with Individually Switchable Outlets, Current Metering, Remote Monitoring and Control | Qty: [optional] |
| PDUMH20 | Metered PDU / Power Distribution Unit- Safe, reliable power distribution with digital current meter | Qty: [optional] |
| PDUV20 | Safe, reliable power distribution for critical networking equipment | Qty: [optional] |

| Power I | Distribution |
|---------|--------------|
|---------|--------------|

PDU1220

Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment

Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2787.

©2009 Tripp Lite. All Rights Reserved.