



Rinnai®

RHFE 750

INTELLIGENT FIREPLACES DIRECT-VENT MODEL WITH POWER FLUE TECHNOLOGY

FOR NEW CONSTRUCTION AND REMODEL APPLICATIONS

ELEGANCE WITH ADVANCED TECHNOLOGY

Rinnai redefines the standard with the innovative RHFE 750 power flue gas fireplace. The RHFE 750 is up to 83%* AFUE efficient through the use of a stainless steel heat exchanger and modulating gas valve with automatic blower. Personalize your look with one of four available fronts.

INNOVATIVE TECHNOLOGY AND SAFETY FEATURES

- Electronic seven-stage modulating gas valve efficiently uses only the energy necessary to maintain room temperature, while providing seven different flame patterns and heat output
- Automatically adjusts the heat output and blower speed, delivering a consistent room temperature for maximizing comfort
- Sealed combustion system minimizes indoor heat loss
- Stainless steel heat exchanger
- Thermistor for accurate temperature control
- Sensors for power failure, flame failure, overheat, and power surge

DESIGN AND CONVENIENCE

- Digital dual timer function enables fireplace to turn on and off for two set periods - great for morning and evening pre-sets
- Pre-heat mode ensures set room temperature is attained
- Full-function remote gives total control of your heat and flame output
- 3-speed fan allows even heat distribution
- On-board diagnostics and safety monitoring system
- Up to 60% heat turn-down with flame visible even on the lowest setting
- Uniquely interchangeable fronts make it easy to fit and update any décor

ADVANTAGES FOR YOU AND YOUR HOME

- Energy-efficient source of zone heating
- Maintains a comfortable level of heat - never too hot or too cold
- Four interchangeable fronts make it easy to change your style often
- Bottom air discharge for optimal heat distribution and for creating space for plasma screens, wall niches and other home décor accessories above the fireplace



FIREPLACE SHOWN WITH SILVER RADIUS GLASS FRONT



BLACK RADIUS GLASS FRONT



STREAMLINE BLACK METAL FRONT



STREAMLINE STAINLESS STEEL METAL FRONT

RINNAI — REDEFINING THE STANDARDS OF FIREPLACE DESIGN AND TECHNOLOGY

FULL OPERATION REMOTE

Full operation remote allows you to use the fireplace in either thermostat mode or manual mode.

- Adjustable flames and heat output
- Full-time clock display
- Dual timers
- ON/ Standby
- Override function
- Auto Off
- Flame Function
- Low-Battery Warning



MODEL RHFE 750




VENT TERMINATION

The Rinnai RHFE 750 utilizes a discrete 4" surface termination and flexible venting options which can be painted to match the home's exterior; almost 30% smaller than most other vents.



CUT-OUT DIMENSIONS

The Rinnai RHFE 750 can be installed with or without a zero clearance box.



Enclosure Dimensions	33.8" W 26.0 - 26.2" H 15.0" - 16.9" D
Enclosure Dimensions for Corner Install	x = 63.8" y = 45.1" z = 31.9"

SPECIFICATIONS

Framed-in Dimensions	31.49" W x 26.18" H x 17.72" D
Actual Dimensions (including surround)	36" W x 26.75" H x 15" D
Weight	154 lbs.
Maximum/Minimum Gas Rate (Input BTU's)	NG: 29,000 BTU / 11,000 BTU LP: 28,000 BTU / 11,000 BTU
AFUE Efficiency Rating	Up to 83%*
Vent System	The vent must be terminated to atmosphere or "outside" in accordance with local, state, provincial and federal codes. Only vent components listed with the appliance's certification can be used. Warranty will be voided if non-listed components are installed.
Logs	Ceramic

* NOTE: AFUE efficiency rating can be achieved with propane model and maximum vent length of 7.2 feet with no elbows.

Rinnai is continually updating and improving products; therefore, specifications are subject to change without prior notice. Local, state, provincial and federal codes must be adhered to prior to installation.

CONTACT YOUR LOCAL AUTHORIZED DEALER

Rinnai Corporation

103 International Drive
Peachtree City, GA 30269

Toll Free 1-800-621-9419

Phone: 678-829-1700

Fax: 678-364-8643

Visit Our Web sites www.rinnai.us • www.foreverhotwater.com

E-mail: marketing@rinnai.us

Rinnai®

