

New Holland 600TL Series Front-End Loader Specifications



610TL 620TL

LOADER MODEL TRACTOR COMPATIBILITY	610TL	610TL	620TL		620TL	
	TT45A 2WD	TT50A 2WD	TT60A 2WD	TT60A 4WD	TT75A 2WD	TT75A 4WD
Max. lift height, in. (mm)	109.0 (2769)	111.7 (2837)	114.5 (2908)	118.0 (2997)	114.5 (2908)	118.0 (2997)
Dump clearance, in. (mm)	90.3 (2294)	93.0 (2362)	92.5 (2350)	93.0 (2362)	92.5 (2350)	93.0 (2362)
Digging depth, in. (mm)	6.0 (152)	5.5 (140)	5.0 (127)	5.5 (140)	5.0 (127)	5.5 (140)
Lift capacity @ 500 mm from bucket pivot pin, lb. (kg)	1320 (599)	1320 (599)	NA	NA	NA	NA
Lift capacity @ 800 mm from bucket pivot pin, lb. (kg)	NA	NA	2210 (1002)	2150 (975)	2210 (1002)	2150 (975)
Breakout force @ 500 mm from bucket pivot pin, lb. (kg)	3400 (1542)	3400 (1542)	NA	NA	NA	NA
Breakout force @ 800 mm from bucket pivot pin, lb. (kg)	NA	NA	4791 (2173)	4520 (2050)	4791 (2173)	4520 (2050)
Reach @ max. lift height, in. (mm)	24.3 (617)	24.3 (617)	34.0 (864)	26.0 (660)	34.0 (864)	26.0 (660)
Bucket rollback angle, degrees	20	20	23	26	23	26
Bucket dump angle, degrees	42	42	45	47	45	47

Loader specifications may vary with tractor model, hydraulic system, tire, size, etc.

Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.