SM523-G Cup Holder Mount with Flexible Goosneck Shaft with Slim-Grip™ Smartphones

SM050-2 Slim-Grip™ Universal Phone Holder GN033-SBH SP-SM050-LF **Cup Holder Mount** Extra Long apport Legs (2 Pack) 88mm expandable to 138mm with Extra Long Support Legs

Package Contents:

- (1) GN033-SBH 5" Cup holder mount with flexible gooseneck shaft
- (1) SM050-2 Universal phone and portable device holder
- (1) SP-SM050-LF Extra Long Support Legs (2 Pack) for larger phones

 $Holder\ included\ is\ Universal,\ designed\ to\ fit\ nearly\ ALL\ non-flip\ mobile\ phones\ regardless\ of\ whether\ all\ phones\ regardless\ of\ phones\ regardless\ phones\ phones\ regardless\ phones\ phon$ protective case or silicone sleeve is attached to the phone.

- Most smartphones, mobile phones, and cell phones having heights between 80mm and 138mm tall
- Apple iPhone All models
- RIM BlackBerry All non-flip models
- HTC Phones All non-flip models
- Motorola Phones All non-flip models
- Nokia Mobile Phones All non-flip models
- Palm All non-flip models
- LG Mobile Phones All non-flip models
- Samsung All non-flip models
- Sony Ericsson All non-flip models
- Sanyo All non-flip models
- Pantech All non-flip models Google - All non-flip models

No tools required for installation.

Note: mount may not work with adjustable, "pop out" cup holders or oversize cup holder openings found in full-size pickup trucks.




Do not place mount in or near an air bag deployment zone or where it will obstruct view of the road.


All brand names and product names are trademarks or registered trademarks of their respective owners.

Cup Holder Mounting

Connect the gooseneck shaft (A) to the cup holder base (B) by Step 1. aligning the groove on the base to the ridge inside of the bottom of the shaft.




- Step 2. Place the Universal Cup Holder Mount into the designated cup holder in the vehicle. Adjust the thumb wheel adjuster (C) to open or close the cup holder prongs to fit in the cup holder.
- For oversize cup holder openings or the adjustable "pop out" cup holders use the optional self-adhesive side support pads (D). Install Step 3. the pads by removing the adhesive backing and placing it on the flat surface side of the cup holder support leg.




Install the Support Legs to the Holder

Step 1. Insert the holder support legs (A) by sliding them into the support leg grooves (B) on the top and bottom of the holder.



iPhone Holder Attachment

- Adjust the angle of the dual T head by tightening the adjustment Step 1. nut at the top of the cup holder shaft (A).
- Install the iPhone holder to the shaft by inserting the dual T-tabs Step 2. (B) on the shaft into the T-slots (C) on on the back of the holder.





Safety Precautions

Do not install Arkon products over an air bag cover or within the air bag deployment zone. Arkon Resources, Inc. assumes no responsibility of liability for injury or death as a result of car crashes and/or air bag deployment.

Arkon is not responsible for any damages caused to your car, your device, or yourself due to the installation or use of this pedestal mount.




The Mobile Mounting Specialists™

Consumer Hotline: www.arkon.com USA (800) 841-0884 Arcadia, CA 91006 USA INT'L (626) 254-9005 Designed in USA | Made in Taiwan & China Monday - Friday 9 am - 5 pm, PST © Copyright 2010 Arkon Resources, Inc.

SM523-G Cup Holder Mount with Flexible Goosneck Shaft with Slim-Grip™ for Smartphones


Insert Phone into Holder

Step 1. Secure holder with your hand for support, as spring-loaded mechanism requires significant force to operate. Hold your phone and insert into universal holder by pushing down on the bottom spring-loaded support legs with moderate amount of pressure (D). Slide the top of the device under the top support legs (E) until it fits snuggly in the holder.



Adjusting Holder to Fit Phone

Step 1. If necessary, adjust the support legs (F) on top and bottom by sliding them laterally to avoid any buttons or ports that may be on your phone.



Fitting for Larger Phones


For larger phones such as the T-Mobile G2 and Motorola Droid X, install the two included extra long support legs

Step 1. Insert the extra long support legs (A) by sliding them into the support leg grooves (B) on the top and bottom of the holder.



Insert Phone into Holder

Step 1. Secure holder with your hand for support, as spring-loaded mechanism requires significant force to operate. Hold your phone and insert into universal holder by pushing down on the bottom spring-loaded support legs with moderate amount of pressure (C). Slide the top of the device under the top support legs (D) until it fits snuggly in the holder.





Safety Precautions

Do not install Arkon products over an air bag cover or within the air bag deployment zone. Arkon Resources, Inc. assumes no responsibility of liability for injury or death as a result of car crashes and/or air bag deployment.

Arkon is not responsible for any damages caused to your car, your device, or yourself due to the installation or use of this pedestal mount.



The Mobile Mounting Specialists™

Consumer Hotline: www.arkon.com
USA (800) 841-0884 Arcadia, CA 91006 USA
INT'L (626) 254-9005 Designed in USA | Made in Taiwan & China
Monday - Friday 9am-5pm, PST © Copyright 2010 Arkon Resources, Inc.