

VSX-817-K

XM® Satellite Ready and SIRIUS® Satellite Ready 7-Channel A/V Receiver



PIONEER-EXCLUSIVE INNOVATIONS

- › **Phase Control** (Bass Management System Ensures Precision Low Frequency Output)
- › **Sound Retriever** for Improved Sound Quality of Compressed Music Files
- › **Auto MCACC Setup** with 5-band EQ
- › **Pioneer Hybrid Amplifier Design**
- › **Front Stage Surround Advance**

FEATURES FOR SUPERIOR SOUND QUALITY

- › Equal High Power for All Seven Channels (110 Watts x 7, 1 kHz, 1.0 % THD, 8 ohms)
- › New Freescale 180MIPS Processing DSP
- › 192 kHz/24-bit DAC
- › XM® HD Surround Powered by Neural Audio®

SURROUND SOUND TECHNOLOGIES

- › Built-in DTS-ES™/DTS® 96/24/DTS® NEO:6/ Dolby® Digital EX/Dolby® Pro Logic IIx Decoders
- › WMA9 Pro Decoder
- › Advanced Surround (14 modes, including Front Stage Surround Advance)
- › Dialogue Enhancement
- › Auto Surround
- › Stream Direct for Pure and Unprocessed Digital Sound

ENHANCED CONVENIENCE

- › XM® Satellite Radio Ready with OSD
- › SIRIUS® Satellite Ready with OSD
- › Pre-programmed Remote Control Unit
- › FL Dimmer (4 steps)

TERMINALS

- › A 3.5 mm Audio Jack Input on the Front Panel
- › 5.1-Channel Input
- › 4 Digital Inputs (2 Coaxial, 2 Optical)
- › Component Video Terminal (3 Inputs, 1 Output)
- › S-Video Terminal (3 Inputs/2 Outputs)
- › Front A/V Input
- › Audio (Tuner Included)/Video Inputs: 5A/4AV
- › Audio/Video Outputs: 1A/1AV + 1V
- › Large Speaker Terminals (FL/FR/C/SR/SL/SBR/SBL)

SPECIFICATIONS

- › Power Requirements: AC 120 V/60 Hz
- › Power Consumption: 370 Watts
- › Standby Power Consumption: 0.5 Watts
- › **Dimensions** (W x H x D):
16-9/16 x 6-1/4 x 13-7/8 inches (420 x 158 x 352.5 mm)
- › **Weight:** 20 lbs. 4 oz. (9.2 kg)

