



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: TLP1008TELTV

Protect It! Surge Suppressor



Highlights

- 10 outlets / 8-ft. cord
- 1 in/2 out tel/modem surge protection
1 in/1 out coaxial surge protection
- 3345 joule rating
- \$150,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

Description

Tripp Lite's TLP1008TELTV offers economical AC surge suppression for protection of workstations, PCs, telecom systems, home electronics and other sensitive equipment. The TLP1008TELTV features 10 outlets, an 8-ft. cord with a space-saving right-angle plug, and diagnostic LEDs to warn of suppressor damage. The unit has a surge suppression rating of 3345 joules to shield equipment from line noise and the strongest surges. Built-in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment. Built-in coax jacks prevent surges from damaging your cable/satellite equipment. \$150,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

PLUG/OUTLETS: Input: NEMA5-15P/Output: 10 NEMA5-15R/8-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 5 transformer-spaced outlet

SUPPRESSION: AC: 150V RMS Clamping/3345 joules/330V UL1449

Applications

- Ideal for protecting TVs, DVDs, satellites, stereos and other entertainment systems

Package Includes

- TLP1008TELTV surge suppressor
- 6-ft. RJ11 cable
- 1 set nickel-plated coax connectors
- Instruction manual and warranty information

Features

- 10 outlets with child safety covers
- 8-ft. cord with space-saving right-angle plug
- Built-in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment built-in splitter protects two devices sharing a single line; 6-ft. telephone cord included
- Surge suppression rating: 3345 joule protection
- EMI/RFI noise filtering

- 15 amp resettable circuit breaker
- Diagnostic LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
- Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- Can accommodate up to 5 transformers without blocking remaining outlets
- Built-in coax jacks prevent surges from damaging your cable/satellite equipment; 6-ft. coax cable included
- Keyhole supports for wall mounting
- \$150,000 [Ultimate Lifetime Insurance](#) (USA & Canada only) covers connected equipment
- Failsafe shutdown mode
- Lighted power switch
- Lifetime product warranty

Specifications

OVERVIEW	
Intended Application	Home/Office, Audio/Video
SYSTEM OVERVIEW	
Voltage compatibility	120 V AC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15
Output watts	1800
Outlet quantity / type	10 NEMA 5-15R
Outlet orientation	Two rows of outlets, including 5 widely spaced for transformers
Overload protection	15A resettable circuit breaker
Outlet safety covers	Includes built-in sliding outlet safety covers
Transformer accommodation	Supports 5 large transformer plug accessories without covering remaining outlets, accepts up to 8 transformers total
INPUT	
Input connection type	NEMA 5-15P
Input cord gauge, type	14 gauge, SJT
Input cord length (ft.)	8 ft.
Input cord length (m)	2.4
Recommended Electrical Service	120V (110-125V)
Input plug features	Space-saving right angle input plug
LEDS ALARMS & SWITCHES	
Diagnostic LEDs	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
Switches	Two-position on/off power switch
SURGE / NOISE SUPPRESSION	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating	3345 joules
Clamping voltage (RMS)	150V
AC suppression response time	< 1 ns
UL1499 let through rating	330V - UL Verified
EMI / RFI filtering	Up to 40dB
DATALINE SURGE SUPPRESSION	

Telephone/DSL Protection	Yes
Telephone/DSL Protection Details	1 line
Cable (Coax) Protection	Yes
Cable (Coax) Protection Details	1 line
Network (Ethernet) Protection	No
PHYSICAL	
Shipping Dimensions (HWD/in)	14.75 x 7.75 x 2.3
Shipping Dimensions (HWD/cm)	37.5 x 19.7 x 5.8
Unit weight (lbs)	2.2
Unit weight (kg)	1.0
Unit Dimensions (HWD/in)	11.6 x 5 x 2.25
Unit Dimensions (HWD/cm)	29.5 x 12.7 x 6.5
Material of construction	Plastic
Integrated keyhole mounting tabs	Keyhole mounting tabs enable wall mounting
AC line cord color	Black
Style	Strip
CERTIFICATIONS	
UL1449 1998 Rev. (AC Suppression)	UL1449
UL1363 (Power Tap)	UL1363
UL497A (Communications)	UL497A
FCC Part 68 (Communications)	FCC Part 68
cUL / CSA (Canada)	cUL
Industry Canada (Communications)	Industry Canada
Approvals	Exceeds IEEE 587 category A&B specifications
WARRANTY	
Product Warranty Period	Lifetime
Connected Equipment Coverage	\$150,000

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2635.