

CVC-645DC

Color Dome Camera With Acrylic Chrome Coating and Lined Housing



Our 1/4" color CCD dome camera with smoked housing can be mounted on the ceiling and offers unobtrusive surveillance with its' black housing. It can be rotated a full 360 degrees and tilted +/- 90 degrees for maximum viewing selection. It features 1.0 lux sensitivity with 420 line resolution and a 3.6mm wide angle lens with built-in electronic shutter. A 12V DC power supply is included.

Specifications

Resolution	420 TV Lines
Image Device	1/3" CCD Image Sensor
Minimum Illumination	1 lux
Interlace	2:1
Synchronization System	Internal
Shutter Control	Auto 1/60-1/100,000 sec.
Electronic Shutter	Built-in
Lens	3.6mm wide angle
Video Output Level	1.0 Vp-p, 75 ohms Composite
Video S/N Ratio	Greater than 48dB
Outputs/Connections	Video-RCA, Power DC jack
Operating Temperature	14°F to 122°F
Power Consumption	110ma @ 12V DC
Power Requirements	12V DC Regulated Power Supply (PSW-5) Included UL & CSA listed
Scanning Frequency	Hor. 15.75 KHz, Vert. 60 Hz
Scanning System	NTSC color 525 TV lines 60 fields/sec
Dimensions	Dome Base: 4-1/2" dia. Dome: 4" dia. x 3"(H)
Housing	High Impact Acrylic Chrome Coating with Black Smoked Base
Weight	10.5 oz.

Specifications subject to change



For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880