




# OHP-4100C

## Overhead Projector



**4100C**

### KEY FEATURES: Model 4100C

- Power to project in normal room light. Eiki 4100 Projector uses a 4,000 ANSI Lumens lamp that delivers 300% more light to the screen than conventional projectors.
- Lightest portable projector in its class. The OHP-4100 weighs only 7.3 kg.
- Distortion-free 275-320 mm, 3-element lens with fingertip lens adjustment delivers razor sharp visual images on screens from 1.5 - 7.62 m.
- Fast folding head and post saves set-up time and protects optics from dust, dirt and damage.
- Fade-proof presentations. Proper cooling is vital to LCD panel efficiency. Eiki's remarkably quiet cooling fans circulate air under the stage to keep LCD computer projection panels at peak performance.
- Designed with convenience in mind, The 4100 is even equipped with a built-in LCD panel AC Power outlet.
- Instant Lamp changer lets you shift to a spare lamp in seconds.
- Eiki projectors incorporate significant safety features, including UL listed safety fuse, interlock and 3-prong power cord.
- Eiki protects your investment with unequalled factory warranty service.
- Scratch-resistant ABS body.
- Positive alignment fresnel and front surface dichroic mirror ensures uniform reflection and even screen brightness.
- Adjustable folding projection head tilts up to 22 degrees.

### Optional Accessories

- Replacement Lamp.
- Transparency frame. (package of 50).
- Transparency Roll Feed Attachment.
- Acetate roll -15 m.
- Acetate roll 10.7 m.
- Work organizer shelf set.
- Dust Cover.
- Soft Carry Case.

### SPECIFICATIONS: Model 4100C

Type	Transmissive console projector	Construction	Stamped
ANSI Lumens	4000	Dimensions (HxWxD)	72 cm x 37 cm x 45 cm
Projection Lamp	410 Watt 82 Volt FXL	Mirror	Dichroic surface high reflection type
Estimated Lamp Life	50 Hours (Hi lamp setting)	Stage Aperture	27 cm x 27 cm
Lens Type	275 ~ 320 mm Vari-Focal Triplet	Power Switch	On/Off rocker type
Front Elevation	Up to 25 degrees, down to 5 degrees	Cooling System	Dual fan forced air system
Condenser System	Glare-free Acrylic fresnel	Weight	7.4 kg.
Projection Heads	Folding	Packaged Weight	9.5 kg.
Lamp Changer	No	Power Requirements	120 Volt, AC, 60Hz
High Lo Switch	No	Power Consumption	480 W Approx.
		Power Cord	3 m, 3-prong (grounded) attached
		Safety Compliance	cUL Listed
		Warranty - Unit	1 Year limited warranty from date of original purchase for parts and labor.

**Prices and Specifications subject to change without notice. ©2001 Eiki International, Inc. 2/13/2003**

Eiki International, Inc., 30251 Esperanza, Rancho Santa Margarita, CA 92688-2132. Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com  
 In Canada: 310 First St., Unit 2, P.O. Box 156, Midland, ON L4R 4K8. Tel: 800-563-3454, Fax: 800-567-4069, E-mail: canada@eiki.com  
 Fax-on-Demand: (Toll Free) 877-345-4329 Visit our World Wide Web site: <http://www.eiki.com>