KEG COUPLERS



Perlick Smart Couplers

- ✓ Keeps beer loss to a minimum
- ✓ Speeds service on keg changeovers
- ✓ Minimizes overfoaming

The patented Perlick Smart Coupler* combines an integral Empty Keg Sensor with a quality keg coupler to eliminate the need for wall-mounted FOB devices. It senses when a keg is empty and shuts off the beer flow, yet leaves the line fully charged with beer. This prevents gas from entering an empty line causing excessive foaming when tapping a fresh keg. Packed 25 per case. Weight: 1 lb. 8 oz. each

Part No.	Description
26000F*	For Domestic Kegs
27500F	For Imported Kegs
*U.S. Patent #5,630, 441	



Universal Empty Keg Sensor

Controls the amount of beer loss by closing off the beer flow when a keg empties. Mounts directly to the keg coupler for dual probe or imported kegs.

Part No.	Description
43739	Universal empty
	keg sensor



Retrofit Empty Keg Sensor

Existing Perlick single valve keg couplers can be retrofitted to function as Smart Couplers. Simply replace the probe with Perlick's No. 40125 empty keg sensor. Bulk-packed. Weight: 8 oz. each

Part No.	Description
40125	For domestic kegs
40119	For imported kegs



Adapter

Adapter

Cleaning Adapters

Single and dual cleaning adapters are uniquely designed to operate when Perlick's keg coupler is in the untapped (handle up) position,

allowing the system to be cleaned from the faucet through the keg coupler. Prevents solution from entering the CO₂ line, eliminating beer contamination when retaping. Brass nickel plated (Bulk Packed)

Adapter

Part No.	Description
43657*	.Single/domestic kegs
43681*	.Dual/domestic kegs
43659*	.Series/domestic kegs
43699	.Single/imported kegs
43702	.Dual/imported kegs

*Note: These adapters are designed to be used with all Perlick single valve couplers and most competitor's couplers. Must be used with Smart Couplers when cleaning lines from the faucet through the Smart Coupler.

Lo-Boy Coupler for Single Valve Domestic Kegs

Uniquely constructed to tap a keg in limited space. Just push down and twist to tap.



Part No.	Description
40030	Lo-Bo



KEG COUPLERS

G-Series Keg Couplers for Single Valve Domestic and Imported Kegs

Provided with non-rotating probe in stainless steel or nickel-plated brass. Enlarged bore and wider tip opening produces less turbulence and restriction which allows for reduced line pressure and CO2 breakout. Nickel-plated, forged brass body with three internally mounted seals.Floating ball check valve equalizes line pressure. Relief valve vents over-pressurized keg. For bent probe design, attach #2036SS elbow to external thread on keg couplers. Optional Locking Shield prevents accidental untapping. Individually packed, 25 per case. Weight 24 oz. each.

For Domestic Kegs

_	
Part No.	Descriptionr
26000G	Probe, brass, less lock
26000GS	Probe, S. St., less lock
26000G1	Probe, brass, with lock
26000GS1	Probe, S. St., with lock

For Imported Kegs

Part No.	Description
27500G	.Probe, brass, less lock
27500GS	.Probe, S. St., less lock
27500G1	.Probe, brass, with lock
27500GS1	.Probe, S. St., with lock



Lug Straightener for Single Valve Kegs

Part No.	Description
32695	Lug straightener

Keg Coupler Replacement Parts

ltem	Part No.	Description
1	40174-1	Probe - brass
1	40174-1SS	Probe - stainless steel
2	40157-1*	Probe, brass, Imported kegs
		Probe, s. st., imported kegs
		Elbow for bent probe, s. st.
		Ball retaining spring
	157R2P	• • •
6	31080-2P	Ball check
7	31089-2P	O-ring (3 per ass'y.)
	2026	
9	2068-1	Tailpiece
		Check Valve
11	43061	Coupler body
		Probe washer, imported
		Bottom seal washer
		Probe washer, domestic
		Retaining screw
		Yoke less lock-domestic
		Yoke with lock- domestic
	32474-1	

*Replacement part used exclusively for Keg Couplers for Imported Kegs.

Keg Coupler Replacement Parts





KEG COUPLERS

D-Series Keg Couplers for Single Valve Domestic and Imported Kegs

Exclusive two-piece rotating probe helps prevent twisting beer lines. Nickel-plated, forged brass body with three internally mounted seals. Floating ball check valve equalizes line pressure. Relief valve vents over-pressurized kegs. Optional Locking Shield prevents accidental untapping. Converts for domestic or imported kegs by changing probe tip. Individually packed, 25 per case. Weight 24 oz. each.

For Domestic Kegs

Part No.	Descriptionr
26000D	Probe, less lock
26000D1	Probe, with lock

For Imported Kegs

Part No.	Description
27500D	.Probe, less lock
27500D1	.Probe, with lock



No. 26000D



No. 26000D1



Lug Straightener for Single Valve Kegs

Part No.	Description
32695	Lug straightener

Keg Coupler Replacement Parts

Item 1 2		Description Probe assembly, domestic Probe assembly imported	
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15	32499 	Probe assembly, domestic Probe assembly, imported Ball retaining spring Probe center stem Buna-N O-ring Ball check, Poly Tip, domestic kegs O-ring (3 per assembly) Coupler body Bottom seal washer Probe washer, domestic Probe washer, imported Check valve Washer	- 5
17 18 19 20 20 21		Nut Retaining screw Yoke less lock, domestic Yoke less lock, imported Yoke with lock, domestic Yoke with lock, imported Elbow for bent probe	

*Replacement part used exclusively for Keg Couplers for Imported Kegs.