



:JETI 5024 UV JETSPEED RTR

:JETI 5024 UV JetSpeed Roll To Roll

The :Jeti 5024 UV JetSpeed is now available in a 4 Color configuration, featuring 24 Spectra print heads. The UV lamps instantly dries the UV-curable Premium inks, these specially formulated inks yield a wider color gamut and exhibit excellent flexibility and superior adhesion on a variety of materials fabric, canvas, vinyl, plastic film, paper and polyester including 100% PE eco-friendly opening many new markets.

Capable of printing fast high quality images at speeds of 1,177 sqft/hr (109 m²/hr) in 3-pass Billboard mode at 300 dpi, which is perfect for Outdoor application.

:JETI 5024 UV JetSpeed Roll To Roll

Designed for 24/7 productivity with a single operator intervention.

The :Jeti 5024 UV JetSpeed maximizing speeds and cost effectiveness for end-users, is the best productive digital solution for outdoor applications in speed and quality for billboards and building wraps.

The :Jeti 5024 UV JetSpeed gives the perfect print every time, with brighter images and solid colors using dedicated environmentally friendly UV-curable Premium inks, these specially formulated inks yield a wider color gamut and exhibit excellent flexibility and superior adhesion on a variety of materials including 100% PE eco-friendly.

This complete printing solution provides an economic advantage for our customers. At the forefront of the technological enhancements is the software upgrade, which can detect if any individual nozzle may be misfiring. This safe-proof technology is the first of its kind in the grand-format area.

The :Jeti 5024 UV JetSpeed also includes an automatic head capping feature (auto caps in 15 minutes if machine sets) and automated air vacuum system that eliminates manual head wiping.

Indoor communication - paper



Technical specifications

Accessories	Rewind (Take Up) Unit (built in), Roll Lifter, Safety Guards (built in)
Supported Platforms	Microsoft Windows, Apple Machintosh, Linux
Processors	P4 (3.4 GHz)
Network	10/100/1000 Mbit/sec Ethernet
Protocols	Ethertalk and TCP/IP
Monitor	420mm (17 inch) LCD Flat panel Display
Operator Console	Rotatable shelf with keyboard, mouse and monitor
Input Formats	Adobe Postscript Level 3, Pdf, Jpeg, Tiff, Eps, RGB
Rips	All our printers come with a wide choice of Rips depending on your applications and your existing workflow. Your local representative will inform you in detail
Compressed Air	80 PSI minimum - 100 PSI maximum with a 10 gallon (40 liter tank) 15 cfm peak
Inks	Shelf life is 1 year for UV Inks UV Inks will last 1-2 years depending on location
Environment	Enclosed dust free room with ambient temperatures ranging from 21°C - 25°C (69°F - 77°F) Relative Humidity 40% to 70% to operate at optimum level (Environment is critical for the printer)
Services	Please contact your local dealer to learn about Agfa Graphics' Global Services Support Network



Outdoor communication - reinforced vinyl



:JETI 5024 UV JetSpeed RTR

Technical specifications

Technology	Spectra High Performance Piezoelectric Jetting Assembly, quantity 24
Print Resolution	Prints quality at True 300 dpi - 4 color
Media Dimensions	Roll max size: 16'8" (5.1 meter) wide. Max diameter is 12" (30.48 cm) on a 3" (7.62 cm) inside core
Media Types	Reinforced vinyl, pressure sensitive vinyl, canvas, fabrics, mesh, paper and 100 % PE material.
Printing Speeds	IMPROVED SPEEDS on all resolutions, call for latest speeds on true 600 dpi and 300 dpi. Up to 1,177 sqft/hr (109 m2/hr)
Weight	8500 lbs (3855 kg) uncrated. Add 3000 lbs (1360 kg) for crating
Printer Dimensions	72" h x 51" w x 308" l (182 cm x 130 cm x 782 cm) Crated dims: 90" h x 72" w x 326" l (229 cm x 183 cm x 829 cm)
Power Consumption	25 KVA (35A)
Electrical Requirements	400Y / 230V, 3 Phase 50/60 Hz