

# TATUNG V32NAFC



New View New Style.... The Tatung 32" Integrated ATSC LCD TV

## Features

- Integrated NTSC/ATSC/Clear QAM Tuner
- Compatible with all 480i/480p/720p/1080i video formats
- Progressive Scan;3-2 pull down;Digital 3D Comb-filter
- Integrated USB port for software update
- Interactive banner for program information
- Dual HDMI (s)
- 3D look-and-feel OSD
- Handy AV side jacks
- SD media card slot (optional)

## System Spec.

- Resolution: 1366 x 768
- Contrast Ratio: 1200:1
- Response Time: 6.5 ms
- Brightness: 500 cd/m<sup>2</sup>
- Response Time: 8ms



## 32" wide LCD TV

## V32NAFC (US Model)

Items	Model Name		
Panel	Aspect Ratio	16 : 9	
	Resolution	1366 x 768 (WXGA)	
	Contrast Ratio	1200 : 1 (typ.)	
	Brightness (center)	500 cd / m <sup>2</sup> (typ.)	
	Viewing Angle (CR≥20)	170°Hor. / 170° Ver. (typ.)	
	Response Time (GTG)	6.5ms (typ.)	
TV function	Broadcasting System	Analog :NTSC M/N	Digital : ATSC/Clear QAM
	Receiving Channel	Analog :PLL181Ch,CATV 125Ch	Digital : 54MHz ~ 864MHz
	Sound System	Analog : Multi-channel TV Sound	Digital : Multi-Track Sound
	Resolution	Analog :480i	Digital : 1080i, 720p, 480p, 480i
	Data Broadcasting	Close Caption, V-Chip	
Video Input	Composite Signal	CVBS	x 2
	Y, C Signal	S-Video	x 2
	Component Signal	Y Pb Pr	x 2 (720P / 1080i , HDTV ready )
PC Input (analog)	HDMI Connection	HDMI	x 2
	VGA Connection	D-Sub 15 pin	
	Scanning Frequency	f <sub>H</sub> = 31.5 ~ 60KHz / f <sub>V</sub> = 56 ~ 75Hz	
Audio Input	Audio 1	Composite / S-Video	
	Audio 2	Component	
	Audio 3	PC	
Audio Output	Speaker (build-in)	10W + 10W (ms) @THD < 10%	
	Line Out	Left / Right ; subwoofer output	
	Digital Audio Out	S / PDIF ( for HDMI and DTV )	
Feature	Function Keys	Power , Input , Menu , Up/Down(Channel) , +/- (Volume) , Aspect	
	Video Performance	3D Comb-filter,3D De-interlace, Aspect Ratio Control (ARC) , Auto Picture Control,Video Enhance, Noise Reduction	
	Audio Performance	Subwoofer, Auto Volume Control (AVC)	
Power	Other Control	Sleep Timer, Timer Off	
	Power Supply	AC 100V ~ 240V , 50 / 60Hz	
	Power Consumption	< 180 W	
Dimensions	W x H x D	804mm * 623mm * 210mm	
Weight (Net)	Without Accessories	19.3kg	

## ATS Standard Software Features

Channel Scan	<input checked="" type="checkbox"/>
Wizard Channel Setup	<input checked="" type="checkbox"/>
Master Channel list	<input checked="" type="checkbox"/>
Channel Edit	<input checked="" type="checkbox"/>
Parental Control	<input checked="" type="checkbox"/>
Program Info banner	<input checked="" type="checkbox"/>
Digital CC – EIA608/708	<input checked="" type="checkbox"/>
Parental Control	<input checked="" type="checkbox"/>
Time Zone setting	<input checked="" type="checkbox"/>
Picture format adjustment	<input checked="" type="checkbox"/>

\*\*Product specification and design are subject to change without notice.

\*\*Product not intended for 24 hour / 7 day continuous use