



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: PS7224-20HW

Tripp Lite Power Strip - Multiple outlets wherever you need them

Highlights

- AC input hardwired via knockout on unit
- 24 outlets
- Ideal for applications requiring permanent installation



Description

Tripp Lite's PS7224-20HW Power Strip offers 20 amp multi-outlet AC power distribution in a convenient 72 inch hardwire cabinet. Includes knockout panels to accept 3/4 in. conduit fittings for hardwire installation and 24 output receptacles with 2.795 inch center-to-center spacing. Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications.

INPUT/OUTPUT: Input: Hard-wire access via knockout panels that accept 3/4 inch conduit fittings

Output: 24 outlets total, 2 NEMA 5-15/20R (20A) and 22 NEMA 5-15R (15A)

ELECTRICAL: 120V AC, 50/60Hz, 20A (no circuit breaker)

FORMAT: 72 inch strip format with 24 outlets

Applications

- Offers multiple outlet power distribution for a variety of applications, including office, workbench, industrial, networking, telecom and more.

Package Includes

- PS7224-20HW
- Instruction manual

Features

- Versatile all-metal 72 inch format with outlets arranged in a single row
- Knockout panels for 3/4 inch conduit fittings allow permanent hardwire installation
- Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications
- 24 outlets total, 2 NEMA 5-15/20R (20A) and 22 NEMA 5-15R (15A)
- 20 amp electrical capacity
- 120V AC, 50/60Hz electrical compatibility

Specifications

SYSTEM OVERVIEW

| | |
|----------------------------------|---|
| Voltage compatibility | 120VAC |
| Frequency compatibility | 50/60 Hz |
| OUTPUT | |
| Output volt amp capacity (amps) | 20A |
| Output watts | 2400 |
| Outlet quantity / type | 22 NEMA 5-15R & 2 NEMA 5-15/20R |
| Outlet spacing | 2.795 in. |
| INPUT | |
| Input connection type | 3/4 inch knockouts support hardwire input connection |
| Recommended Electrical Service | 20A 120V |
| PHYSICAL | |
| Unit Dimensions (HWD/in) | 72 x 1.5 x 1.5 |
| Unit Dimensions (HWD/cm) | 182.88 x 3.8 x 3.8 |
| Material of construction | Metal |
| Integrated keyhole mounting tabs | Mount through housing supports bolt down installation to a variety of flat surfaces |
| Receptacle Color | Almond |
| CERTIFICATIONS | |
| cUL / CSA (Canada) | cUL |
| Approvals | UL |
| WARRANTY | |
| Product Warranty Period | Lifetime |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=201.