

10.1t

INSTRUCTIONS

 Infinity®

KAPPASERIES

Thank you for purchasing the Infinity Kappa Series 10.1t tweeter. We've organized this manual to make your installation as simple and trouble-free as possible. Please read it thoroughly before proceeding. Remember to keep your sales receipt with this manual in a safe place so both are available for future reference.



IMPORTANT: Installation of automotive stereo components can require extensive experience with a variety of mechanical and electrical procedures. Although these instructions explain how to install a Kappa 10.1t in a general sense, they do not show the exact installation methods for your particular vehicle. If you do not feel you have the experience, do not attempt the installation yourself, but instead ask your Authorized Infinity Car Audio Dealer about professional installation options.

WARNING: Playing loud music in an automotive environment can permanently damage your hearing, as well as hinder your ability to hear traffic. The maximum volume levels achievable with Infinity speakers, combined with high power amplification, may exceed safe levels for extended listening. We recommend using low volume levels when driving. Infinity accepts no liability for hearing loss, bodily injury or property damage as a result of use or misuse of this product.

SPEAKER PLACEMENT

Kappa speakers are designed to be easily installed in stock speaker locations. While mounting your speakers in the original factory locations will, in most cases, provide excellent sonic results, the best sounding installations are a result of adherence to a few basic rules.

- For the most spacious stereo image, place the left and right speakers as far apart as possible.
- For enhanced center image, place the left and right speakers so they are equidistant from the listening position. If possible, try to place them as far forward as possible.
- For best treble response when tweeters are flush mounted in the I-Mount™, aim them at the listening position by adjusting the tweeter angle in the cup, tightening the small metal locking nut behind the assembly and rotating the entire assembly in its mounting location before tightening the large plastic locking nut behind the panel (see Fig 1, p.2).

INSTALLATION WARNINGS AND TIPS

- Always wear protective eyewear when using any tools.
- Turn off all audio systems and other electrical devices before you start. Disconnect the (-) negative lead from your vehicle's battery.
- Keep components in their package until final installation. When moving a speaker, always rest it with the cone or dome facing up. Never use force to install any speaker.
- Check clearances on both sides of a planned mounting surface before drilling any holes or installing any screws. Remember that the screws can extend behind the surface.
- At the installation sites, locate and make a note of all fuel lines, hydraulic brake lines, vacuum lines and electrical wiring. Use extreme caution when cutting or drilling in and around these areas.

CAUTION: In some cars, fuel tanks may be located directly beneath the rear deck. Check for adequate speaker basket clearance before considering this location!

- Before drilling or cutting holes, use a utility knife to remove unwanted fabric or vinyl, to keep material from snagging in a drill bit or saw.
- For door installations, check the clearance with the windows throughout the range of the window's travel, and verify that a mounted speaker will not interfere with the window crank or power window mechanism.
- If mounting components elsewhere, check for clearance around rear-deck torsion bars, glove box or other structural elements.
- Do not mount components where they will get wet.

TWEETER INSTALLATION




Figure 1. After installing the surface-mount plate, push the Kappa10.1t onto the mounting plate to snap it into place.




Figure 2. Use this template to flush-mount a Kappa10.1t tweeter.

A NOTE ON POWER HANDLING




Figure 3. After the Kappa10.1t tweeter is in its cup, hand tighten the nut to flush-mount the assembly on the panel.

NOTE: You must use the crossover supplied with the 10.1t tweeter. The crossover is contained in the shrink tube attached to the included speaker wire. If you must shorten the wire, do not remove the crossover, and be sure that its orientation is correct (indicated by position of connectors).

The Kappa 10.1t tweeters are designed to produce reasonable volume levels with little amplifier power. However, the addition of an amplifier to drive your speakers and a subwoofer will enhance the dynamic range of your system, and help overcome the ambient noise in a moving vehicle. Kappa speakers are designed to handle the power of a dedicated amplifier driven at or below its rated power. If an amplifier is driven far above its rated power, the output signal will "clip," and the additional power present in a clipped signal can damage any speaker. Distorted or "fuzzy" sound from your speakers is an indication that the amplifier has exceeded its rated power, and you should reduce the volume level.

GENERAL CARE

The loudspeaker grilles may be cleaned with a slightly damp cloth. Do not use any cleaners or solvents on the grilles or the speaker drivers.

SPECIFICATIONS

10.1t

| | |
|--|-------------------------------------|
| Type: | Component Tweeter |
| Speaker Impedance: | 4 ohms |
| Power Handling: | 50 watts per channel with crossover |
| Frequency Response ($\pm 3\text{dB}$): | 8kHz ~ 22kHz |
| Sensitivity: | 89Hz @ 2.83 V, 1 watt |
| Crossover Frequency: | 8000Hz |
| Cut-out Diameter Tweeter: | 1-5/8" (42 mm) |

DECLARATION OF CONFORMITY

CE

We, Infinity Systems A/S
Køgevej 194B
DK-3460 Birkerød
DENMARK

declare in own responsibility, that the product described in this owner's manual is in compliance with technical standards:
EN 50 081-1/1992
EN 50 082-1/3.1995

Steen Michaelsen
Infinity Systems A/S
Birkerød, DENMARK 298

