

SP-525BB, SP-625BB & SP-825BB

In-wall enclosed speaker systems

Model Shown
SP-825BB



Model Shown
SP-525BB

With an included back box enclosure, the Speco Technologies in-wall enclosed speaker systems are an excellent choice for applications where component protection and consistent sound quality are a concern. All models feature titanium swivel dome tweeters, broad frequency response, ample wattage handling and excellent sensitivity ratings, making the series ideal for a variety of residential and commercial applications.

Applications

- Enclosure Offers Extra Component Protection & Consistent Sound Quality
- Titanium Swivel Dome Tweeter
- Fiberglass Air Suspension Woofer
- 88 dB Sensitivity (1W/1M)
- EZ Mounting Tabs
- Fine Mesh, Paintable Grilles Included

Specifications

| | SP-525BB | SP-625BB | SP-825BB |
|----------------------|-------------------------------|-------------------------------|-------------------------------|
| Woofer | 5.25" Fiberglass | 6.5" Fiberglass | 8" Fiberglass |
| Tweeter | Titanium swivel dome | Titanium swivel dome | Titanium swivel dome |
| Frequency Response | 55 - 20 kHz. | 50 - 20 kHz. | 50 - 20 kHz. |
| RMS Rating | 40W | 60W | 80W |
| Maximum Power Rating | 80W | 100W | 120W |
| Impedance | 8 ohm (4-8 ohm compatible) | 8 ohm (4-8 ohm compatible) | 8 ohm (4-8 ohm compatible) |
| Sensitivity | 88 dB (1W/1M) | 88 dB (1W/1M) | 88 dB (1W/1M) |
| Overall Dimensions | 3.6"L x 8.3"W x 11.75"H | 4.25"L x 8.6"W x 12"H | 4.1"L x 10"W x 14"H |
| Hardware | EZ Mounting Tabs | EZ Mounting Tabs | EZ Mounting Tabs |

Specifications subject to change.



Specifications subject to change