

Lanier Worldwide, Inc.

2300 Parklake Dr., N. E.

Atlanta, GA 30345-2979

Emergency Telephone: (800) 526-4371

# MATERIAL SAFETY DATA SHEET

# **Section 1: Chemical Product and Company Information**

MSDS No. Identity: Cyan Toner for 5711 / 5811 **CP-325** Product ID: 117-0310 Issued: 9/2/99

Supersedes: None Synonyms Date: 9/2/99

& Common Lanier QA/EH&S Department 770-493-2361 Cyan Toner for Prepared by: Names: Lanier 5711, 5811 Approved by: Larry Choskey, Sr. Quality Assurance Engineer

**European Contact:** Lanier Worldwide, WSM Europe, Uses:

Lanier 5711, 5811 Color Copier Walter Fricke.

Im Taubental D-41468 Neuss, Germany

Chemical +49-2131-387-177

Mixture Formula:

# Section 2: Composition / Information on Ingredients

CAS No. **EXPOSURE LIMITS** SOURCE PERCENT N/a Polyester resin 85 - 95 % by weight N/a N/a N/a 1-5 % by weight N/a N/a Pigment

\*PEL as the product: 15mg/m<sup>3</sup> (total dust), 5mg/m<sup>3</sup> (respirable dust) \*TLV as the product: 10mg/m³ (total dust), 5mg/m³ (respirable dust)

# **Section 3: Hazards Identification**

**HMIS Rating:** 

FLAMMABILITY = 1 HEALTH = 1 REACTIVITY = 0 SPECIAL = none

Health Hazards (Acute, Chronic, Immediate and Potential): Minimum irritation to respiratory tract may occur as with exposure to any non-toxic dust. Inhalation should be avoided. May cause temporary eye discomfort.

Health Hazards of Long Term exposure (Chronic): Not known.

#### Section 4: First Aid Measures

Remove to fresh air if effects occur. Gargle with water. In case of contact, immediately flush eyes with Inhalation:

Get medical attention if needed. **Eye Contact:** water for 15 minutes. Get medical attention if

needed.

Skin Contact: Wash with soap and water. Ingestion: Dilute stomach contents with several glasses of

water. Get medical attention if needed.

## Section 5: Fire Fighting Measures

Suitable extinguishing media: CO<sub>2</sub>, dry chemical, foam or water. Unusual Fire and Explosion Hazards: Toner material, like most Extinguishing media which may not be used for safety reasons: none organic material in powdered form, is capable of creating a dust

explosion.

Flammability: Non-flammable solid The decomposition products are CO, CO<sub>2</sub>,. Avoid inhalation of smoke.

Special protective equipment for fire fighters: none

UEL: n/a LEL: n/a

### **Section 6: Accidental Release Measures**

Spill / leak Procedures: If spilled, sweep up using an approved toner vacuum with a 0.5 micron filter or smaller, such as the Atrix AAA Toner Vacuum or 3M Toner Vacuum. Use of a vacuum cleaner not rated for toner particles, could result in a fire or personal injury. Remove residue with soap and cold water.

Miscellaneous: Keep product out of sewers and watercourses.

Personal protection: Avoid inhalation of dust.

## Section 7: Handling and Storage

Special Handling: Cleanse skin after contact before breaks or meals, and end of workday.

Store in a cool, dry place. Avoid direct sunlight. Keep out of reach of children. Keep from contact with oxidizing materials. Special Storage:

Do not handle in windy areas. Flying powder may enter eyes. Minimize inhalation of dust. Cleanse skin thoroughly after

Miscellaneous: contact, before breaks and meals, and at end of work periods.

### Section 8: Exposure Control and Personal Protection Information:

Respiratory Protection: none required under normal use.

Hand Protection: none required under normal use.

#### MATERIAL SAFETY DATA SHEET

Page 2 of CP-325

Eye Protection: none required under normal use.

Ventilation: Local exhaust equipment is needed. Skin Protection: none required under normal use.

Exposure Guidelines: USA OSHA (TWA/PEL) : 15mg/m³ (Total Dust); 5mg/m³ (Respirable fraction)

ACGIH (TWA/TLV) : 10mg/m³ (Total dust); 3mg/m³ (Respirable fraction) DFG (MAK) : 4mg/m³ (Inhalable fraction); 1.5mg/m³ (Respirable fraction)

### **Section 9: Physical and Chemical Properties**

CHARACTERISTICS:

Appearance: Cyan Melting point: 100 – 150°C (softening point)

Powder Vapor pressure: Form: n/a Slight plastic odor Odor: Vapor density: n/a Solubility in Water: Negligible Evaporation rate: n/a Density: 1.0 - 1.5Boiling point: n/a

Flammability: Non-flammable solid (according to test Fat solubility: Partially soluble in toluene and xylene

methods of USA 16 CFR 1500.44 and annex V of EU Directive 84/449/EEC)

# Section 10: Stability and Reactivity

Conditions to avoid: none Materials to avoid: none Stability: Stable Hazardous decomposition products: CO and CO2 and other decomposition products when burned.

### **Section 11: Toxicological Information:**

Acute Toxicity: Inhalation: (Data from similar material without ferrite): LC50:>4.93mg/L/4hr (rats) (Mean maximum attainable concentration)

Ingestion: (Data from ingredients of toner): LD50:>5000mg/kg (rats)

Eye: (Data from ingredients of toner): Not classified as irritant, according to OSHA Haz Com Standard and EU Directive 67/548/EEC based on test data

of rabbits.

Sensitizer: No sensitizer according to Annex I of EU Directive 67/548/EEC and strong sensitizer list of FHSA.

Mutagenicity: Ames test negative

Reproductive Toxicity: No reproductive toxic substances according to Annex I of EU Directive 67/548/EEC, California Proposition 65 and DFG. Carcinogenicity: Carbon Black: IARC 2B (Possible human carcinogen based on animal testing). Not listed in NTP, OSHA(USA) regulation, California Proposition 65 and Annex I of EU Directive 67/548/EEC.

### Section 12: Environmental / Ecological Information

No information indicating any adverse ecological effects.

### **Section 13: Disposal Consideration**

Used Toner should be disposed of under conditions that meet all federal, state and local environmental regulations. Disposal regulations vary from locality to locality, therefore consult your local Lanier office or the EPA to determine the proper method for disposal. Do not incinerate loose or spilled Toner.

### **Section 14: Transportation Information**

None. This is not a hazardous product.

### **Section 15: Regulatory Information**

SARA Title III, 313: Chemical name: Chromium(III) and compound 10% weight (maximum) (as chromium(III) metal) 1% weight (maximum)

### **Section 16: Miscellaneous Information**

Judgment as to the suitability of information contained herein for user's purposes is the responsibility of the purchaser. Therefore, although reasonable care has been taken in the preparation of this information, Lanier Worldwide, Inc. extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information for application to user's intended purposes or for consequences of its use. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we do not guarantee that these are the only hazards that exist.