

## ➤ 22" WIDESCREEN LCD DISPLAY



## E-W22









## **▶ FEATURES**

- · 22" widescreen format
- WSXGA<sup>+</sup> 1680 x 1050 resolution
- NeoV Optical Glass<sup>TM</sup>
- Exquisitely elegant exterior
- · Stylish rear side design
- Swift 3ms response time
- Crisp 3000 contrast ratio
- High 300 brightness
- Dual digital and analog inputs
- Built-in HDCP for HD-format video
- 1080p support
- Built-in speakers with headphone jack
- Auto-adjustment for optimal settings
- Hot key for preferable video mode: User,
   Text, Movie, Game, and Graphic
- Kensington® security socket
- VESA standard wall mount



Panel	Panel Type	TFT LCD
	Panel Size	22.0" (559mm)
	Max. Resolution	WSXGA+ 1680 x 1050
	Pixel Pitch	0.282mm
	Brightness	300cd/m <sup>2</sup> (Typical)
	Contrast Ratio	3000:1 (DCR)
	<b>Surface Treatments</b>	Hard Coating (3H), Anti-glare
		Treatment
	Viewing Angle (H/V)	170°/160° (Typical)
	Display Color	16.7M
	Response Time	3ms (GTG)
	Frequency (H/V)	H: 24kHz - 83kHz
		V: 50Hz - 76Hz
	Max. Pixel Clock	190 MHZ
	Life Time	50,000hrs (Minimum)
Input	Analog	15-Pin D-Sub
	Digital	24-Pin DVI-D
Audio	Audio In	3.5mm Audio Line-in
	Audio Out	3.5mm Headphone Jack
	Speaker	2W x 2
Connector	Power	3-Pin AC Plug
NeoV Optical	Thickness	3.0mm (0.18")
Glass	Reflection Rate	<1%
	Transmission Rate	>96%
	Hardness	>6H (MOH's Rating)
Tilt	Tilt	+5° ~ +25°
Mounting	VESA FPMPMI	Yes (100mm)
Regulation	Certifications &	UL/CUL, FCC, NOM, CB, CE,
Approval	Compliance	TUV/Baurt, NORDIC, BSMI,
		Energy Star,
		GOST-R/HYGIENIC, WEEE,
		, , , ,
		RoHS
	VESA	
Power	VESA Power AC	RoHS DDC-2B, DDC-CI 100 - 240V, 50 - 60Hz
Power		RoHS DDC-2B, DDC-CI 100 - 240V, 50 - 60Hz <48W (On)
Power	Power AC	RoHS DDC-2B, DDC-CI 100 - 240V, 50 - 60Hz <48W (On) <2W (Stand-by)
	Power AC Consumption	RoHS DDC-2B, DDC-CI 100 - 240V, 50 - 60Hz <48W (On) <2W (Stand-by) <1W (Off)
Power  Dimensions	Power AC	RoHS DDC-2B, DDC-CI 100 - 240V, 50 - 60Hz <48W (On) <2W (Stand-by) <1W (Off) 512 x 416 x 196 mm
	Power AC Consumption Net (W x H x D)	RoHS DDC-2B, DDC-CI 100 - 240V, 50 - 60Hz <48W (On) <2W (Stand-by) <1W (Off) 512 x 416 x 196 mm (20.1" x 16.4" x 7.7")
	Power AC Consumption	RoHS DDC-2B, DDC-CI 100 - 240V, 50 - 60Hz <48W (On) <2W (Stand-by) <1W (Off) 512 x 416 x 196 mm (20.1" x 16.4" x 7.7") 594 x 564 x 204 mm
Dimensions	Power AC Consumption Net (W x H x D)	RoHS DDC-2B, DDC-CI 100 - 240V, 50 - 60Hz <48W (On) <2W (Stand-by) <1W (Off) 512 x 416 x 196 mm (20.1" x 16.4" x 7.7") 594 x 564 x 204 mm (23.4" x 22.2" x 8.0")
	Power AC Consumption  Net (W x H x D)  Packing (W x H x D)  Net Weight	RoHS DDC-2B, DDC-CI 100 - 240V, 50 - 60Hz <48W (On) <2W (Stand-by) <1W (Off) 512 x 416 x 196 mm (20.1" x 16.4" x 7.7") 594 x 564 x 204 mm (23.4" x 22.2" x 8.0") 7.9 kg (17.4 lbs)
Dimensions	Power AC Consumption  Net (W x H x D)  Packing (W x H x D)  Net Weight Gross Weight	RoHS DDC-2B, DDC-CI 100 - 240V, 50 - 60Hz <48W (On) <2W (Stand-by) <1W (Off) 512 x 416 x 196 mm (20.1" x 16.4" x 7.7") 594 x 564 x 204 mm (23.4" x 22.2" x 8.0") 7.9 kg (17.4 lbs) 9.0 kg (19.8 lbs)
Dimensions	Power AC Consumption  Net (W x H x D)  Packing (W x H x D)  Net Weight Gross Weight 1 Pallet	RoHS DDC-2B, DDC-CI 100 - 240V, 50 - 60Hz <48W (On) <2W (Stand-by) <1W (Off) 512 x 416 x 196 mm (20.1" x 16.4" x 7.7") 594 x 564 x 204 mm (23.4" x 22.2" x 8.0") 7.9 kg (17.4 lbs) 9.0 kg (19.8 lbs) 40 Sets
Dimensions Weight	Power AC Consumption  Net (W x H x D)  Packing (W x H x D)  Net Weight Gross Weight 1 Pallet 20' Container	RoHS DDC-2B, DDC-CI 100 - 240V, 50 - 60Hz <48W (On) <2W (Stand-by) <1W (Off) 512 x 416 x 196 mm (20.1" x 16.4" x 7.7") 594 x 564 x 204 mm (23.4" x 22.2" x 8.0") 7.9 kg (17.4 lbs) 9.0 kg (19.8 lbs) 40 Sets 320 Sets
Dimensions  Weight  Packing	Power AC Consumption  Net (W x H x D)  Packing (W x H x D)  Net Weight Gross Weight 1 Pallet 20' Container 40' Container	RoHS DDC-2B, DDC-CI 100 - 240V, 50 - 60Hz <48W (On) <2W (Stand-by) <1W (Off) 512 x 416 x 196 mm (20.1" x 16.4" x 7.7") 594 x 564 x 204 mm (23.4" x 22.2" x 8.0") 7.9 kg (17.4 lbs) 9.0 kg (19.8 lbs) 40 Sets 320 Sets 720 Sets
Dimensions  Weight  Packing	Power AC Consumption  Net (W x H x D)  Packing (W x H x D)  Net Weight Gross Weight 1 Pallet 20' Container	RoHS DDC-2B, DDC-CI 100 - 240V, 50 - 60Hz <48W (On) <2W (Stand-by) <1W (Off) 512 x 416 x 196 mm (20.1" x 16.4" x 7.7") 594 x 564 x 204 mm (23.4" x 22.2" x 8.0") 7.9 kg (17.4 lbs) 9.0 kg (19.8 lbs) 40 Sets 320 Sets 720 Sets









www.agneovo.com

Copyright © 2007 AG Neovo. All rights reserved. The name AG Neovo is a trademark of Associated Industries China, Inc. All other trademarks are the property of their respective owners.