

▶ 19" LCD DISPLAY

M-19



▶ FEATURES

- Distinctive exterior design with unique crystal front bezel
- Intelligent avMode™ provides preset audio-visual modes
- Exclusive iRelax™ program helps reduce eyestrain and fatigue
- Convenient USB port and power port
- Dual digital and analog inputs
- Integrated speakers with headphone jack
- Swift 8ms response time
- Crisp 500 contrast ratio
- Easy-to-reach luminance and audio hot keys for instant adjustment
- Intuitive OSD and auto-adjustment function
- Kensington® security socket
- VESA standard for wall and arm mounting
- Cable management design
- Two available colors: silver and black

▶ SPECIFICATION

Panel	Panel Type	TFT LCD	
	Panel Size	19.0" (483mm)	
	Max. Resolution	SXGA 1280 x 1024	
	Pixel Pitch	0.294mm	
	Brightness	250cd/m ² (Typical)	
	Contrast Ratio	500:1 (Typical)	
	Surface Treatments	Hard Coating (3H), Anti-glare Treatment	
	Viewing Angle (H/V)	150°/130° (Typical)	
	Display Color	16.7M	
	Response Time	8ms (GTG)	
	Frequency (H/V)	H: 30kHz – 80kHz V: 50Hz – 75Hz	
	Max. Pixel Clock	135MHz	
	Life Time	40,000hrs (Minimum)	
	Input	Analog	15-Pin D-Sub
Digital		29-Pin DVI-D	
USB Port	Right: USB Port	2.0/1.1 Compatible	
	Left: Power Port	DC 5V, 800mA (Max.)	
Audio	Audio In	3.5mm Audio Line-in	
	Audio Out	3.5mm Headphone Jack	
	Speaker	2W x 2	
Connector	Power	3-Pin AC Plug	
Tilt	Tilt	+10° ~ +30°	
Mounting	VESA FPMPI	Yes (100mm)	
Dimensions	Net (W x H x D)	469 x 431 x 70mm (18.5" x 17.0" x 2.8")	
	Packing (W x H x D)	567 x 530 x 196mm (22.3" x 20.9" x 7.7")	
Weight	Net Weight	5.6Kg (12.3lbs)	
	Gross Weight	8.2Kg (18.1lbs)	
Regulation Approval	Certifications & Compliance	UL/CUL, TUV/GS, NORDIC, CCC, CB, TCO 99, GOST, FCC, VCCI, CE, BSMI, ISO 13406-2, WEEE, RoHS	
		VESA	DDC 1/2B, DPMS
		Power AC Consumption	100 - 240V, 50 - 60Hz <55W (On) <8W (Stand-by) <2W (Off)
Packing	1 Pallet	32/40 Cartons	
	20' Container	464 Sets	
	40' Container	960 Sets	

All specifications are subject to change without prior notice

