

Philips  
S-video cable

12 ft

SWV3504W



# Turn up your viewing experience

with this S-video cable

Step up to a better video connection between components.

## **Protects against signal loss**

- Copper braided reinforced aluminum shielding

## **Enjoy better picture/sound quality**

- 24 carat gold-plated connectors optimize signal
- High purity copper conductor for reliable signal transfer

## **Easy installation**

- Color coded connectors for instant recognition
- Plug and play for easy use

## **Enjoy extended durability**

- Flexible PVC jacket
- Rubber strain relief
- Protective metal shell for extended durability

**PHILIPS**  
sense and simplicity

S-video cable  
12 ft

## Specifications

### Packaging dimensions

- **Packaging dimensions (W x H x D):**  
19.7 x 26.7 x 2.5 cm
- **Nett weight:** .181 kg
- **Gross weight:** .227 kg
- **Tare weight:** .046 kg

### Outer Carton

- **Outer carton (L x W x H):** 27.9 x 20.3 x 12.7 cm
- **Nett weight:** .724 kg
- **Gross weight:** .907 kg
- **Tare weight:** .183 kg

SWV3504W/27

## Product highlights

### Color-coded connectors

Color coded connections make it easy to install your cable into the correct inputs and outputs

### Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

### Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

### Braided shielding

Copper braided reinforced aluminum shielding protects against signal loss and interference.

### Plug and play

Plug and play offers easy installation of components without time-consuming installations.

### Metal shell

The metal shell protects the internal connection of the cable. It ensures durability and the reliability of your connection.

### 24 carat gold-plated connector

24 carat gold-plated connectors ensure the best signal quality for your components.

### High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.



Issue date 2008-08-19

Version: 1.0.5

12 NC: 8670 000 37042  
UPC: 6 09585 14827 7

© 2008 Koninklijke Philips Electronics N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

[www.philips.com](http://www.philips.com)