



PIONEER NEW MEDIA TECHNOLOGIES, INC.

## DRM-624X Six Disc CD-ROM Changer

### SPECIFICATIONS

<b>GENERAL</b>	
Media Type	CD-ROM, CD-Audio, XA Mode 2, Form 1 and 2
Media Diameter	120mm
Interface	SCSI-2
Block Size	2048/512 Byte (selectable)
Data Transfer Rate	676 Kbytes/Sec (Sustained)
Capacity of Data Buffer	128 Kbytes (ABS*)
Average Seek/Access Time	110/150 mSec
Disc Change Time (without Spin-Up, Spin-Down)	Less than 5 Sec
MTBF	50,000 POH
Regulatory Approval	UL, CSA, FCC Class B, VDE, TUV, SEMKO, BEAB, NEMKO, DEMKO, FIMKO, SEV, CE
<b>AUDIO PERFORMANCE</b>	
Frequency Response	4 ~ 20,000 Hz $\pm$ 2dB
Total Harmonic Distortion	0.1% (Max)
Output Voltage	1.7 V r.m.s. (line out) $\pm$ 0.5V (10K $\Omega$ )
<b>PHYSICAL CHARACTERISTICS</b>	
Dimension (W x H x D)	210 x 88.3 x 370.5 mm
Weight (Net)	3.4 Kg
Weight (Shipping)	4.8 Kg
Operating Voltage	100 ~ 240V 50/60Hz
Rated Current Consumption	AC 120V 0.11A, AC240V 0.10A
Max. Current Consumption	AC 120V 0.31A, AC240V 0.20A
<b>ENVIRONMENTAL CONDITIONS</b>	
Operating Temperature	5 ~ 40°C
Storage Temperature	-20 ~ 60°C
Humidity (non-condensing)	5 ~ 85% RH
<b>ACCESSORIES</b>	
DRM-A600	6 Disc Magazine
PCA-02	SCSI Daisy Chain Cube

\*ABS: Advanced Buffering System