

Rollei dk4010

High performance and sophisticated 4 megapixels digital camera with 10x D-VarioApogon zoom lens and 6x digital zoom. Video and voice recording possible. Designed to meet the challenges of discriminating amateur photographers.

Cat. No. 22455

Bar Code 4021136224555

- Fast continuous shooting with high speed image processing at approx. 3.3 images/s without refocusing
- Extremely fast autofocus for up to 2 images/s using refocusing
- High-speed, high-performance 10x Rollei Apogon zoom lens (equivalent to 37 – 370 mm in 35mm photography)
- Electronic color viewfinder with high resolution (300,000 pixels), image information, eyesight correction
- E52 filter thread for supplementary lenses and filters



Rollei dk4010



**HighSpeed
Imageprocessing**

B. Kamrath

Specifications

Sensor

1/2,7"

4.2 M pixels CCD

Image resolution

2272 x 1704 pixels,

1600 x 1200 pixels,

1280 x 960 pixels,

640 x 480 pixels

Video Clip, with sound

640 x 480 pixels,

320 x 240 pixels

30 and 15 fps

Image storage

SD and MM Card

Recording format

JPEG (EXIF 2.2), AVI

Built-in microphone and loudspeaker

Lens

D-VarioApogon zoom lens

5.7 – 57 mm f/2.8 – 3.1 HFT

(equivalent to approx. 37 – 370 mm
in 35mm format)

Zoom

10x optical,

6x digital

Focus range

autofocus, 0.6 m to ∞

Macro range

10 to 60 cm

Shutter speed, automatically

1 s – 1/2000 s

(CCD controlled electronic
program shutter)

Film speed setting, auto

ISO 100, 200, 400, 800

Aperture and shutter speed

10x aperture and shutter
speed steps

Programs

Sport, Portrait, Night, Nightportrait

Exposure compensation

auto, manual

+/-2.0 EV in 1/3 increments

Drive

Single and continuous shooting

AF active continuous shooting:

2 Images/s

AF saved:

3.3 Images/s in high resolution

White balance

auto, manual

light sunlight, cloudy, tungsten,

fluorescent, preset

Flash

auto, off, Anti-red-eye auto,

Anti-red-eye fill-in, daylight fill-in

Viewfinder

Ferroelectric Liquid Crystal,

ca. 300K pixels

LC monitor

1.5" DayFine TFT colour monitor

(110K pixels)

Self timer

2 s/10 s delay

Interfaces

USB, Video (NTSC, PAL), Audio,

AC/DC

PictBridge function

Power Source

4x AA Alkali-Batteries,

4x AA rechargeable NiMH batteries,

AC adapter (optional)

Tripod mount

1/4"

Dimensions (w x h x d)

107 x 73 x 87,5 mm

Weight

310 g

(without batteries and SD-card)

System requirements

**PC, Windows 98/98SE/2000/
ME/XP**

CD ROM-drive,

USB-interface

Apple Macintosh,

OS 9.0 or higher

CD ROM-drive,

USB-interface

Contents

Rollei dk4010, USB and video-

cable, 4x Alkaline batteries,

lens cap, strap, ACDSsee software,

CD-ROM with drivers and instruc-

tion manual, Quick Start Guide

Subject to change without notice.