COLOR WIRELESS SURVEILLANCE SYSTEM WITH 2 INDOOR/OUTDOOR NIGHT VISION CAMERAS





FEATURES

- 'EWT' Eliminates Interference From Most Household Devices
- Fast & Easy Installation Plug Into any AC Outlet
- Receiver Connects to any TV/VCR/DVD Recorder
- Indoor / Outdoor Night Vision Camera
- Built-in Microphone for Listening Ability
- Camera Can be Battery Operated for True Portable Wireless Operation
- Up to 300ft Wireless Transmission Range*
- Night Vision Allows for Low Light Viewing up to 23ft (7m) from Cameras**
- Receiver Automatically Switches View Between Cameras
- Desktop, Wall and Ceiling Mountable

*Maximum open space transmission range. Actual range dependent upon building materials and other obstructions in path of wireless signal.

**IR illumination range of 23ft (7m) under ideal conditions. Objects at or beyond this range may be partially or completely obscured, depending on the camera application.

This product broadcasts over public airways and its video and audio signals may be intercepted without your consent.

CONNECTS TO ANY TV







COLOR WIRELESS SURVEILLANCE SYSTEM WITH 2 INDOOR/OUTDOOR NIGHT VISION CAMERAS

$S\ P\ E\ C\ I\ F\ I\ C\ A\ T\ I\ O\ N\ S$

Camera

Imaging Sensor:	1/3" CMOS
CMOS Total Pixels:	510 x 492 (NTSC)
View Angle:	62° Diagonal
Minimum Illumination:	3.0 Lux F1.5 (IR off) / 0 Lux (IR on)
Transmission Frequency:	910 MHz - CH1, 920 MHz - CH2 (2CH)
Transmission Power:	10 dBm
Modulation Type:	FM
Bandwidth:	6.0 MHz
Power Source:	+ 9V (DC)
Unobstructed Effective Range:	330 ft. / 100 meters
Night Vision Range:	Up to 26 ft. / 8 meters
Dimensions:	45x115x160mm / 1.8x4.6x6.3"
Weight:	0.3lbs / 140 g
Operating Temperature Range:	$14^{\circ} \text{ F} \sim 104^{\circ} \text{ F}$ $-10^{\circ} \text{ C} \sim 40^{\circ} \text{ C}$

Receiver

Receiving Frequency:	910-920 MHz - 2CH
Intermediate Frequency:	32 MHz
Demodulation Type:	FM
Receiving Sensitivity:	-85 dBm
Power Supply:	9V (DC)
Consumption Current:	180 mA
Unobstructed Effective Range:	Up to 330 ft. / 100 m
Dimensions:	70x120x83mm / 2.8x4.7x3.3"
Weight:	0.3lbs / 120 g
Operating Temperature:	14 F to 104 F /- 10 C to 40 C
Operating Humidity:	85% RH



PRODUCT INFORMATION

UPC:	LW1012 - 7-78597-10120-1 LW1012F - 7-78597-10121-8
Package Weight:	1.3kg / 2.8lbs
Package Dimensions:	298mm/11.73"(w) x 81mm/3.19"(d) x 235mm/9.25"(h)
Package Cube:	0.005cbm / 0.20cft
CONTENTS	
LW1012/LW1012F	1 x Wireless Receiver 2 x Wireless Camera 3 x 9V DC Power Adapters 1 x RCA Video Output Cable 2 x Camera Battery Adapter Cable



Lorex Technology Inc.

300 Alden Road, Markham, Ontario L3R 4C1 Canada.

3700 Koppers Street Baltimore, Maryland 21227, USA. ©2008 Lorex Technology Inc. As our product is subject to continuous improvement, Lorex Technology & subsidiaries reserve the right to modify product design, specifications & prices without notice and without incurring any obligation. E&OE