#### HOME AND BUSINESS SECURITY

# **16 CHANNEL NETWORK DVR** WITH 160 GB HDD



The Lorex DXR216161 16 Channel Network DVR allows you to view and control up to 16 cameras both locally and remotely. This cost effective security solution provides advanced features including Video Motion Detection, password protection, and a variety of viewing modes.

- Supports two removable disk drives up to 250GB each (one 160 GB HDD included)
- Connect up to 16 cameras with multiple viewing options
- Network view and control capability
- Integrated video motion detection
- Continuous, alarm and scheduled recording modes
- Real time display, 25 IPS record
- Adjustable video quality settings
- Quick multiple search by date/time, alarm or full list
- Security password protection
- Video loss detection able to record 160 events on each channel
- Display modes are selectable during surveillance and playback
- Superior Wavelet compression format



www.lorexcctv.com



DXR216161

#### HOME AND BUSINESS SECURITY

# **16 CHANNEL NETWORK DVR** WITH 160 GB HDD

### S P E C I F I C A T I O N S

Network Interface	Ethernet (10/100 Base-T)
Protocols	TCPIP, ICMP, SMTP, HTTP, FTP
Triggers & Actions	E-mail images or images uploaded to FTP site / Remote recording
HDD storage	IDE type, UDMA 66 above, 2 removable HDD supported
Record mode	Manual / Alarm / Timer/Motion Trigger
Camera input signal	Composite video signal 1 Vp-p 750 BNC, 16 Channels
Camera loop back	Composite video signal 1 Vp-p 750 BNC, 16 Channels
Main monitor output	Composite video signal 1 Vp-p 750 BNC
Call monitor output	Composite video signal 1 Vp-p 750 BNC
Audio input/ output	4 audio inputs, (RCA) and 2 audio outputs, (RCA)
Motion detect area	15 X 12 Targets per camera (NTSC)/ 15*14 targets per camera (PAL)
Motion detect sensitivity	256 Levels
Video loss detection	Yes
Refresh rate	72 IPS for NTSC / 100 IPS for PAL
Recording rate	25 IPS for NTSC / 12 IPS for PAL
Dwell time	Programmable (1 - 10 Sec)
Picture in picture	Yes (Moveable)
Key lock	Yes
Picture zoom	2X (Moveable)
Camera title	6 Characters
Video adjustable	Color / Contrast / Brightness Adjustable
Alarm input / output	Input: TTL input, Hi (5V), Low (GND) Output: COM,/N.O/N.C
Time display format	YY/MM/DD, DD/MM/YY, MM/DD/YY, OFF
Power source	AC 100-240V +/- 10% switching adaptor
Power consumption	<32W
Operation temperature	14° F - 104° F ( -10° C - +40° C)
Net weight	5.4 Kgs / 11.9 lbs

### DIMENSIONS



## PRODUCT INFORMATION

Model #:	DXR216161
Description:	16 Channel Network Digital Video Recorder with 160 GB HDD
UPC:	7-78597- 21616-5
Package Dimensions:	21" (W) x 17.5" (H) x 7" (D) 533mm (W) x 445mm (H) x 178mm (D)
Package Weight:	17 LB / 7.7 kg

#### LOREX TECHNOLOGY INC.

300 Alden Road, Markham, Ontario L3R 4C1 Canada 3700 Koppers Street, Suite 504 Baltimore, Maryland 21227, USA ©2006 Lorex Technology Inc. All trademarks are properties of their respective companies. Lorex Corporation reserves the right to change models, configurations or specifications without notice or liability. Product may not be exactly as shown.