



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: 0SU22082

Minicom Smart 116 - 16-Port Cat5 KVM Switch for Rack Environments

Highlights

- 16 Ports
- BIOS level access
- Multilayer security
- Multi-platform – PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet over Cat5e cabling
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases



Description

Save Space and Money

The Smart 116 is a single-user analog Cat5 KVM switch that gives you the ability to control multiple computers or servers from a single keyboard/video/mouse console. The rack mountable, 1U-sized switch features innovative ROC (RICC on cable) dongle technology that directly connects you to each server in the rack, eliminating cable clutter and the need for multiple consoles.

From SOHO to Enterprise

The Smart 116 is ideal for multiple server environments, from the small home office to the enterprise data center. Whatever the application, a company operating several servers can now connect them all to a single keyboard, video and mouse console, and operate them with 30m/100ft of range between the server and switch.

System Requirements

Operating System

- DOS, Windows, LINUX, UNIX, MAC and all other major operating systems

Console

- VGA Monitor
- PS/2 Keyboard and Mouse

Resolution

- Supports video resolutions up to 1600 x 1200 @ 75Hz

Package Includes

- Smart 116
- RS232 Cable
- Power Cord
- Rackmount Hardware
- Owner's Manual

Features

- 16 Ports

- BIOS level access
- Multilayer security
- Multi-platform – PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet over Cat5e cabling
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
# Of Users	1
Console	No
Port Control	Push Buttons, Hotkeys, OSD
PC/Server	VGA, USB or PS/2
Cat5 KVM Switch	Yes
IP Remote Access	YES WITH B051-000
Model Type	KVM Switches
UPC Codes	
Unit Carton UPC#	654518209495
PHYSICAL	
Unit Dimensions (HWD/in)	1.6 x 8.5 x 4.8
Unit Dimensions (HWD/cm)	4.15 x 21.5 x 12.2
Unit weight (lbs)	2.2
Unit weight (kg)	1
Color	Black
Style	1U Rackmount
ENVIRONMENTAL	
Relative Humidity	80% Non-Condensing
Operating Temperature	0 to 40 C / 32 to 104 F
Storage Temperature	-40 to 70 C / -40 to 158 F
CONNECTIONS	
Ports	16
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

Related Items

Required Products

Related Model	Description	Qty.
0SU51078	Minicom ROC PS/2 - Server Interface Unit for Smart KVMs	1
0SU51079	Minicom ROC USB - Server Interface Unit for Smart KVMs	1

0SU51079/8	Minicom ROC USB (8 Pack) - Server Interface Unit for Smart KVMs	1
N201-007-GY	7-ft. Cat6 Gigabit Snagless Molded Patch Cable (RJ45 M/M) - Gray	1
N201-014-GY	14-ft. Cat6 Gigabit Snagless Molded Patch Cable (RJ45 M/M) - Gray	1
N201-025-GY	25-ft. Cat6 Gigabit Snagless Molded Patch Cable (RJ45 M/M) - Gray	1
N201-050-GY	50-ft. Cat6 Gigabit Snagless Molded Patch Cable (RJ45 M/M) - Gray	1

Optional Products

Related Model	Description	Qty.
0DT60002	Minicom - PS/2 to USB Converter	1
0SU22081	Minicom Smart 108 - 8-Port Cat5 KVM Switch for Rack Environments	1
0SU22181	Minicom Smart 108 SPU - 8-Port Cat5 KVM Switch for Rack Environments	1
0SU22182	Minicom Smart 116 SPU - 16-Port Cat5 KVM Switch for Rack Environments	1
B021-000-17	Rackmount Console - 1U Rackmount Console with 17" LCD	1
B021-000-19	Rackmount Console - 1U Rackmount Console with 19" LCD	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=5198.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.