

APPLICATION EQUIPMENT

THE TANK™
SPREADER/SPRAYER

XP STAND-ON
SPREADER

XP STAND-ON
SPREADER/SPRAYER

TR20 TURF
RENOVATOR

80-LB. SPREADER

COMMERCIAL
SPRAYERS

FEATURES

SPREADERS FOR
SEEDING, FERTILIZING
OR DE-ICING

25-, 50-, 100-, 200- AND
300-GAL. SPRAYERS

WANDS AND SPRAY
GUNS FOR ANY JOB

PREMIUM KAWASAKI®
OHV ENGINES,
ELECTRIC OR
RECOIL START

1-YEAR LIMITED
COMMERCIAL
WARRANTY†

COMMERCIAL APPLICATION EQUIPMENT



WE MEAN BUSINESS.™



THE TANK™ Spreader/Sprayer shown

A FULL LINE OF PROVEN, RELIABLE EQUIPMENT TO MAKE YOU MORE VALUABLE TO YOUR CUSTOMERS.

How can you make your business more valuable to your customers and more profitable to you? By using our complete line of proven, reliable and highly successful application equipment. Our latest addition, the new XP Stand-On Spreader/Sprayer, features an innovative design with the maneuverability and flexibility you need to be as efficient with your time as possible. Spreaders. Sprayers. Renovators. We're talking rugged, durable equipment that's built to handle any of the toughest jobs and hold up over time. So no matter which piece you're using, you can be assured that you're working with the best equipment available.

THE TANK™ SPREADER/SPRAYER

It's the ultimate machine for spreading and spraying large areas — both in the same pass, if needed. With a 40-gallon tank for spraying and a 125-lb. capacity hopper for spreading. All powered by a 17 HP* Kawasaki® V-Twin engine.

(shown above)

XP STAND-ON SPREADER/SPRAYER



Built on the same platform as the XP Spreader but equipped with dual, independent 5-gallon tanks, as well as boomless spray nozzles mounted to each side of the unit and a spray wand. This 3-in-1 application machine allows you to spread granular products and liquids all at once.

80-LB. SPREADER

The 80-lb. capacity polyethylene hopper and easy rate-adjustment mechanism give you simple but precise material flow control.



TR20 TURF RENOVATOR

Equipped with an 8 HP* Kawasaki® engine and a 35-lb. hopper capacity, the TR20 can be used to dethatch, slice and seed.



COMMERCIAL SPRAYERS

Several options ranging from 25 to 300 gallons to allow you to tackle everything from light-duty work with your

tractor or utility vehicle up to heavy-duty use from the back of your pickup. Most sprayers feature a 5.5 HP* Kawasaki® engine coupled with a hydro pump for increased productivity.

XP STAND-ON SPREADER

Powered by a 6 HP* Kawasaki® engine and hydrostatic drive, the 125-lb. hopper can spread seed or fertilizer. Plus, the sulky-style riding platform and rear-wheel drive give you increased traction and control.



*as rated by engine manufacturer †See your local Cub Cadet Commercial Independent Dealer for warranty information.

APPLICATION EQUIPMENT



	80-lb. Rotary Spreader	XP Stand-On Spreader	XP Stand-On Spreader/Sprayer	TR20 Turf Renovator	THE TANK™ Spreader/Sprayer
Engine	-	6 HP* Kawasaki®	6 HP* Kawasaki®	8 HP* Kawasaki®	17 HP* Kawasaki®
Engine series	-	Vertical OHV	Vertical OHV	Horizontal OHV	Vertical OHV
Ignition	-	Recoil start	Electric start/recoil	Recoil start	Electric start
Cylinder	-	Single	Single	Single	Twin
Gear reduction	5:1 ratio	-	Electric motor	-	-
Oil filter	-	Yes	-	-	Yes
Hopper/tank width	-	-	10 gal. total/fender mounted	20" dethatching/seeding	-
Hopper size	80 lbs.	125 lbs.	125 lbs.	35 lbs.	125 lbs.
Tank size	-	-	Dual 5-gal. tanks/independent	-	40 gal.
Tank shape	Rectangular hopper	Rectangular hopper	Rectangular hopper	Rectangular	Rectangular
Strainer	Stainless mesh screen	Stainless mesh screen	Stainless mesh screen	-	-
Agitation	Oscillating agitator	Oscillating agitator	Oscillating agitator	-	Triple jet & oscillating agitator
Hopper/tank material	Polyethylene	Polyethylene	Polyethylene	Steel	Polyethylene
Frame type	Stainless steel	Stainless/welded steel	Stainless/welded steel	Welded steel	Welded steel
Frame material	1" SS tube	1" SS tube & 7-ga. steel	1" SS tube & 7-ga. steel	11-ga. painted steel	Painted steel
Drive system	Push	Hydro-Gear™ transmission	Hydro-Gear™ transmission	Hydraulic with chain-driven differential	Kanzaki DUP-10 pumps & White® wheel motors
Speeds	-	Fwd: 5 mph, Rev: 3 mph	Fwd: 5 mph, Rev: 3 mph	Fwd: 2 mph, Rev: 1 mph	Fwd: 10 mph, Rev: 4 mph, lock-in application speed
Front wheels	13" x 5.0" - 6"	13" x 6.5" - 6"	13" x 6.5" - 6"	13" x 5.0" - 6"	13" x 6.5" - 6"
Rear wheels	-	18" x 6.5" - 8"	18" x 8.5" - 8"	13" x 5.0" - 6"	24" x 12" - 12"
Pump output	-	-	-	-	4.8-GPM, 40 psi
Pump type	-	-	12 VDC Flojet™ pump	-	12 VDC Flojet™ pump
Pump pressure	-	-	-	-	-
Hose size	-	-	25-ft. coil hose w/spot wand	-	25-ft. coil hose
Hose material	-	-	PVC	-	PVC
Pressure rating (hose)	-	-	100 psi	-	100 psi
Length x width x height	48" x 25" x 35"	56" x 35" x 48"	56" x 35" x 48"	31" wide overall	99" x 57" x 48"
Effective spray/spread width	-	120"	120"/108" boomless spray	-	120"
Weight	32 lbs. dry	340 lbs. dry	365 lbs. dry	290 lbs. dry	1,134 lbs. dry
Spray wand/gun	-	-	Spot spray wand & 3 boomless spray nozzles	-	Adj. spot spray wand & 3 section boom 5 nozzle
Warranty†	1-year limited commercial	1-year limited commercial	1-year limited commercial	1-year limited commercial	1-year limited commercial

SPRAYERS	25 Spot	50 Poly	100 Poly	200 Poly	300 Poly	200 Compact
Engine	12 VDC	4 HP* Kawasaki®	5.5 HP* Kawasaki®	5.5 HP* Kawasaki®	5.5 HP* Kawasaki®	5.5 HP* Kawasaki®
Engine series	-	Horizontal OHV	Horizontal OHV	Horizontal OHV	Horizontal OHV	Horizontal OHV
Ignition	-	Recoil start	Recoil start	Recoil start	Recoil start	Recoil start
Cylinder	-	Single	Single	Single	Single	Single
Gear reduction	-	6:1 direct-coupled	6:1 direct-coupled	6:1 direct-coupled	6:1 direct-coupled	6:1 direct-coupled
Tank size	25 gal.	50 gal.	100 gal.	200 gal.	300 gal.	200 gal.
Tank shape	•-----Rectangular-----•					
Strainer	In-line SS on inlet side of pump	Stainless steel mesh	Stainless steel mesh	Stainless steel mesh	Stainless steel mesh	Stainless steel mesh
Agitation	-	Triple jet spray	Triple jet spray	Triple jet spray	Triple jet spray	Triple jet spray
Hopper/tank material	•-----Polyethylene-----•					
Frame type	-	Welded steel	Welded steel	Welded steel	Welded steel	Welded steel
Frame material	-	Painted steel	Painted steel	Painted steel	Painted steel	Painted steel
Pump output	4.8-GPM/40 psi	Max. 6-GPM	Max. 9.5-GPM	Max. 9.5-GPM	Max. 9.5-GPM	Max. 9.5-GPM
Pump type	Diaphragm	Twin diaphragm	Twin diaphragm	Twin diaphragm	Twin diaphragm	3-diaphragm
Pump pressure	60 psi	Max. 275 psi	Max. 550 psi	Max. 550 psi	Max. 550 psi	Max. 550 psi
Hose reel	-	Hannay® electric	Hannay® electric	Hannay® electric	Hannay® electric	Hannay® electric
Hose size	1/4" i.d. x 25'	3/8" i.d. x 300'	1/2" i.d. x 300'	3/8" i.d. x 400'	1/2" i.d. x 300'	1/2" i.d. x 300'
Hose material	Flexcoil - PVC	PVC	PVC urethane core	PVC urethane core	PVC urethane core	PVC urethane core
Pressure rating (hose)	100 psi	300 psi	800 psi	800 psi	800 psi	800 psi
Length x width x height	30" x 20" x 19"	54" x 19" x 26"	48" x 38" x 34"	65" x 39" x 40"	88" x 38" x 47"	62" x 40" x 40"
Weight w/o hose & reel	22 lbs. dry	125 lbs.	237 lbs.	336 lbs.	422 lbs.	330 lbs.
Weight w/hose & reel	-	200 lbs.	371 lbs.	470 lbs.	556 lbs.	454 lbs.
Spray wand/gun	Trigger jet w/conejet nozzle	Order as needed	Order as needed	Order as needed	Order as needed	Order as needed
Warranty†	1-year limited commercial	1-year limited commercial	1-year limited commercial	1-year limited commercial	1-year limited commercial	1-year limited commercial

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.

*as rated by engine manufacturer † See your local Cub Cadet Commercial Independent Dealer for warranty details. Commercial products are intended for professional use.

773-03687 Printed in U.S.A. 12/08 © 2009 Cub Cadet