

Subscriber Networks

Model DPC2203 Cable Modem with Embedded MTA

Description

The DPC2203 Cable Modem (DPC2203) is a high-speed cable modem with an embedded media terminal adapter (EMTA). The DPC2203 features two RJ-11 telephone ports for Voice over Internet Protocol (VoIP) service along with a 10/100BASE-T Ethernet port and a USB 1.1 port for high-speed data connectivity.

The DPC2203 is designed to meet PacketCable™ 1.5, PacketCable 1.0, and DOCSIS® 2.0 specifications as well as being backward compatible with DOCSIS 1.1 and DOCSIS 1.0 networks. The DPC2203 uses advanced line-interface technology to provide multi-country, toll-quality, telephone service using existing in-home wiring. The DPC2203 supports full 5 REN phone loading on each phone line (10 REN total).

The DPC2203 fully supports the CODECs specified in PacketCable 1.5. Additional CODECs are available through a software upgrade that includes a high fidelity CODEC option for toll-quality plus service. Standard VoIP call signaling is compliant with PacketCable's (MGCP/NCS) specifications. Software upgrades are available to support Session Initiation Protocol (SIP) call signaling.

WebWizard

The DPC2203 includes WebWizard, a browser-based graphical user interface. WebWizard is a powerful tool that facilitates installation and troubleshooting by eliminating the need to load setup software on the customer premises equipment (CPE).



Description continued next page

Features


- Cable modem with an Embedded MTA that provides two lines of voice services
- Toll-quality, high-compression, and high-fidelity (exceeding toll quality) CODEC options
- IPsec and AES-128 encryption options
- Attractive compact design and versatile orientation to stand vertically, lie flat on the desktop, or mount easily on the wall
- Front panel LEDs provide visual feedback of real-time data transmission and cable modem status
- Bridged 10/100BASE-T auto-sensing/auto-MDIX Ethernet port and USB 1.1 data port
- Battery backup housing (optional models only) allows standby powering on loss of AC power
- 2200 mAh Li-Ion battery cartridge provides up to 8 hours of battery backup operation per cartridge¹

¹ The listed battery backup time (8 hours) is the nominal initial time that the battery pack can provide standby power after loss of AC power and after fully charging the battery. Due to variations in individual units, the actual initial standby time can vary +/- 10%. Other factors can also influence battery standby power times such as CPE data activity, variations in DOCSIS traffic, telephone port activity, battery aging, and temperature.

Description, continued

Battery Backup (Optional)

The DPC2203 can be ordered with or without the capability to provide battery backup powering. Units with battery backup capability are available in housings that have either one or two battery bays. Each bay holds a single, user replaceable, rechargeable Li-Ion battery cartridge that provides backup power in the event of an AC power failure.



Ordering Information

Contact your Sales Representative for product availability in your area.

Description	Part Number
<p>“C” housing with one (1) battery bay</p> <p>2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes:</p> <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Battery backup housing (1 battery bay, bottom loaded) • 120 VAC / 60 Hz, 15 VDC / 1A Class 2 desktop linear power supply with attached power cord for North America • No battery included (battery ordered separately) • Ethernet and USB cables • CD-ROM containing user’s guide and USB drivers 	4016431
<p>2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes:</p> <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Battery backup housing (1 battery bay, bottom loaded) • 100-120 VAC / 50-60 Hz, 15 VDC / 1A desktop linear-switching power supply with attached power cord for North America • No battery included (battery ordered separately) • Ethernet and USB cables • CD-ROM containing user guide and USB drivers 	4024178
<p>2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes:</p> <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Battery backup housing (1 battery bay, bottom loaded) • 120 VAC / 60 Hz, 15 VDC / 1A Class 2 desktop linear power supply with attached power cord for North America • No battery included (battery ordered separately) • Ethernet and USB cables • CD-ROM containing user guide and USB drivers <p>Customer Specific Configuration</p>	4013087
<p>2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes:</p> <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Battery backup housing (1 battery bay, bottom loaded) • 100-120 VAC / 50-60 Hz, 15 VDC / 1A desktop linear-switching power supply with attached power cord for North America • No battery included (battery ordered separately) • Ethernet and USB cables • CD-ROM containing user guide and USB drivers <p>Customer Specific Configuration</p>	4024179

Ordering Information, continued

Description, continued "C" housing with one (1) battery bay	Part Number
2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Extended flash memory option • Battery backup housing (1 battery bay, bottom loaded) • 120 VAC / 60 Hz, 15 VDC / 1A Class 2 desktop linear power supply with attached power cord for North America • No battery included (battery ordered separately) • Ethernet and USB cables • CD-ROM containing user guide and USB drivers Customer Specific Configuration	4025728
2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Extended flash memory option • Battery backup housing (1 battery bay, bottom loaded) • 100-120 VAC / 50-60 Hz, 15 VDC / 1A desktop linear-switching power supply with attached power cord for North America • No battery included (battery ordered separately) • Ethernet and USB cables • CD-ROM containing user guide and USB drivers Customer Specific Configuration	4025729
2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Battery backup housing (1 battery bay, bottom loaded) • 120 VAC / 60 Hz, 15 VDC / 1A Class 2 desktop linear power supply with attached power cord for North America • One (1) 2200 mAh Li-Ion battery • Ethernet and USB cables • CD-ROM containing user guide and USB drivers 	4016432
2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Battery backup housing (1 battery bay, bottom loaded) • 100-120 VAC / 50-60 Hz, 15 VDC / 1A desktop linear-switching power supply with attached power cord for North America • One (1) 2200 mAh Li-Ion battery • Ethernet and USB cables • CD-ROM containing user guide and USB drivers 	4024176

Ordering Information, continued

Description, continued "C" housing with one (1) battery bay	Part Number
2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Battery backup housing (1 battery bay, bottom loaded) • 120 VAC / 60 Hz, 15 VDC / 1A Class 2 desktop linear power supply with attached power cord for North America • One (1) 2200 mAh Li-Ion battery • Ethernet and USB cables • CD-ROM containing user guide and USB drivers Customer Specific Configuration	4013088
2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Battery backup housing (1 battery bay, bottom loaded) • 100-120 VAC / 50-60 Hz, 15 VDC / 1A desktop linear-switching power supply with attached power cord for North America • One (1) 2200 mAh Li-Ion battery • Ethernet and USB cables • CD-ROM containing user guide and USB drivers Customer Specific Configuration	4025381
2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Extended flash memory option • Battery backup housing (1 battery bay, bottom loaded) • 120 VAC / 60 Hz, 15 VDC / 1A Class 2 desktop linear power supply with attached power cord for North America • One (1) 2200 mAh Li-Ion battery • Ethernet and USB cables • CD-ROM containing user guide and USB drivers Customer Specific Configuration	4025730
2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Extended flash memory option • Battery backup housing (1 battery bay, bottom loaded) • 100-120 VAC / 50-60 Hz, 15 VDC / 1A desktop linear-switching power supply with attached power cord for North America • One (1) 2200 mAh Li-Ion battery • Ethernet and USB cables • CD-ROM containing user guide and USB drivers Customer Specific Configuration	4025731

Ordering Information, continued

Description, continued "C" housing with one (1) battery bay	Part Number
2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Battery backup housing (1 battery bay, bottom loaded) • 120 VAC / 60 Hz, 15 VDC / 1A Class 2 desktop linear power supply with attached power cord for North America • One (1) 2200 mAh Li-Ion battery • Ethernet and USB cables • CD-ROM containing user guide and USB drivers Customer Specific Configuration	4025302
2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Battery backup housing (1 battery bay, bottom loaded) • 100-120 VAC / 50-60 Hz, 15 VDC / 1A desktop linear-switching power supply with attached power cord for North America • One (1) 2200 mAh Li-Ion battery • Ethernet and USB cables • CD-ROM containing user's guide and USB drivers Customer Specific Configuration	4024177
2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 (PAL/NTSC) • Battery backup housing (1 battery bay, bottom loaded) • 230 VAC / 50 Hz, 15 VDC / 1A Class 2 wall-mount linear-switching power supply for Europe • One (1) 2200 mAh Li-Ion battery • Ethernet and USB cables • CD-ROM containing user guide and USB drivers 	4017981
<i>International Configuration – PAL/NTSC</i>	
2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 (PAL/NTSC) • Battery backup housing (1 battery bay, bottom loaded) • 230-240 VAC / 15 VDC / 1A High Efficiency wall-mount linear-switching power supply • No battery included (battery ordered separately) • Ethernet and USB cables • CD-ROM containing user guide and USB drivers Australia	4024333

Ordering Information, continued

Description, continued "C" housing with one (1) battery bay	Part Number
<i>International Configuration – PAL/NTSC</i>	
2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 (PAL/NTSC) • Battery backup housing (1 battery bay, bottom loaded) • 230-240 VAC / 15 VDC / 1A High Efficiency wall-mount linear-switching power supply • One (1) 2200 mAh Li-Ion battery • Ethernet and USB cables • CD-ROM containing user guide and USB drivers Australia	4025394
2-Line VoIP Cable Modem with EMTA for International markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 (PAL/NTSC) • Battery backup housing (1 battery bay, bottom loaded) • 100-240 VAC / 50-60 Hz, 12 VDC / 1A Class 2 desktop switching mode power supply • 2-conductor North American style power cord (NEMA 1-15 to C7 non-polarized) • One (1) 2200 mAh Li-Ion battery • Ethernet and USB cables • CD-ROM containing user guide and USB drivers 	4013089
2-Line VoIP Cable Modem with EMTA for International markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 (PAL/NTSC) • Battery backup housing (1 battery bay, bottom loaded) • 100-240 VAC / 50-60 Hz, 15 VDC / 1A Class 2 desktop switching mode power supply • 2-conductor European style detachable power cord (CEE7/16 to C7) • One (1) 2200 mAh Li-Ion battery • Ethernet and USB cables • CD-ROM containing user guide and USB drivers 	4013090
2-Line VoIP Cable Modem with EMTA for International markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 (PAL/NTSC) • Battery backup housing (1 battery bay, bottom loaded) • 230 VAC / 50 Hz, 15 VDC / 1A Class 2 desktop linear power supply with attached power cord for Europe • One (1) 2200 mAh Li-Ion battery • Ethernet and USB cables • CD-ROM containing user guide and USB drivers 	4013793

Ordering Information, continued

Description, continued "C" housing with one (1) battery bay	Part Number
<i>International Configuration – Japanese Diplexer (5-55 MHz/88-860 MHz)</i>	
2-Line VoIP Cable Modem with EMTA for Japan. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 (NTSC Japan) • Battery backup housing (1 battery bay, bottom loaded) • 100-120 VAC / 50-60 Hz, 15 VDC / 1A wall-mount Class 2 linear-switching power supply • One (1) 2200 mAh Li-Ion battery • No USB 1.1 port • Ethernet cable • Paper Japanese user guide Japan - Importer Specific Configuration	4016465

Description "C2" housing with two (2) battery bays	Part Number
2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Battery backup housing (2 battery bays, front loaded) • 120 VAC / 60 Hz, 15 VDC / 1A Class 2 wall-mount linear-switching power supply with polarized connector for North America • One (1) 2200 mAh Li-Ion battery • No Ethernet cable • No USB cable • CD-ROM containing user guide and USB drivers 	4015069
2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Battery backup housing (2 battery bays, front loaded) • 100-120 VAC / 50-60 Hz, 15 VDC / 1A desktop linear-switching power supply with attached power cord for North America • One (1) 2200 mAh Li-Ion battery • No Ethernet cable • No USB cable • CD-ROM containing user guide and USB drivers 	4024180

Ordering Information, continued

Description	Part Number
<p>Housing with no battery backup capability</p> <p>2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes:</p> <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Standard housing (no battery backup capability) • 120 VAC / 60 Hz, 12 VDC / 1A Class 2 desktop linear power supply with attached power cord for North America • Ethernet and USB cables • CD-ROM containing user guide and USB drivers 	4011094
<p>2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes:</p> <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Standard housing (no battery backup capability) • 100-120 VAC / 50-60 Hz, 12 VDC / 1A desktop linear-switching power supply with attached power cord for North America • Ethernet and USB cables • CD-ROM containing user guide and USB drivers 	4025738
<p>2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes:</p> <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Standard housing (no battery backup capability) • 120 VAC / 60 Hz, 12 VDC / 1A Class 2 desktop linear power supply with attached power cord for North America • Ethernet and USB cables • CD-ROM containing user guide and USB drivers <p>Customer Specific Configuration</p>	4016466
<p>2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes:</p> <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Standard housing (no battery backup capability) • 100-120 VAC / 50-60 Hz, 12 VDC / 1A desktop linear-switching power supply with attached power cord for North America • Ethernet and USB cables • CD-ROM containing user guide and USB drivers <p>Customer Specific Configuration</p>	4025739
<p>2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes:</p> <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Extended flash memory option • Standard housing (no battery backup capability) • 120 VAC / 60 Hz, 12 VDC / 1A Class 2 desktop linear power supply with attached power cord for North America • Ethernet and USB cables • CD-ROM containing user guide and USB drivers <p>Customer Specific Configuration</p>	4025726

Ordering Information, continued

Description, continued Housing with no battery backup capability	Part Number
2-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> ▪ PacketCable 1.0 / DOCSIS 2.0 ▪ Extended flash memory option ▪ Standard housing (no battery backup capability) ▪ 100-120 VAC / 50-60 Hz, 12 VDC / 1A desktop linear-switching power supply with attached power cord for North America ▪ Ethernet and USB cables ▪ CD-ROM containing user guide and USB drivers Customer Specific Configuration	4025727
1-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Standard housing (no battery backup capability) • 100-120 VAC / 50-60 Hz, 12 VDC / 1A Class 2 desktop linear power supply • 2-conductor detachable power cord for Brazil • No USB port, no USB Cable • Ethernet cable • CD-ROM containing user guide and USB drivers Columbia	4019840
1-Line VoIP Cable Modem with EMTA for NTSC markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Standard housing (no battery backup capability) • 220 VAC / 60 Hz, 12 VDC / 1A Class 2 wall-mount linear-switching power supply • No USB port, no USB Cable • No Ethernet cable • CD-ROM containing user guide and USB drivers Argentina	4019841
<i>International Configuration – PAL/NTSC</i>	
2-Line VoIP Cable Modem with EMTA for International markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 (PAL/NTSC) • Standard housing (no battery backup capability) • 230 VAC / 50 Hz, 12 VDC / 1A Class 2 desktop linear power supply with attached power cord for Europe • Ethernet and USB cables • CD-ROM containing user's guide and USB drivers Europe	4013808

Ordering Information, continued

Description, continued Housing with no battery backup capability	Part Number
2-Line VoIP Cable Modem with EMTA for International markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 (PAL/NTSC) • Standard housing (no battery backup capability) • 230 VAC / 50 Hz, 12 VDC / 1A Class 2 desktop linear power supply with attached power cord for Europe • Ethernet and USB cables • Danish telephone cable • Custom CD-ROM containing user guide and USB drivers Denmark – Customer Specific Configuration	4017664
2-Line VoIP Cable Modem with EMTA for International markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 (NTSC) • Standard housing (no battery backup capability) • 100-240 VAC / 50-60 Hz, 12 VDC / 1A Class 2 desktop switching mode power supply • 2-conductor North American style detachable power cord (NEMA 1-15 to C7 non-polarized) • Ethernet and USB cables • CD-ROM containing user guide and USB drivers Brazil	4011102
2-Line VoIP Cable Modem with EMTA for International markets. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 • Standard housing (no battery backup capability) • 100-240 VAC / 50-60 Hz, 12 VDC / 1A Class 2 desktop switching mode power supply • 2-conductor European style detachable power cord (CEE7/16 to C7) • Ethernet and USB cables • CD-ROM containing user guide and USB drivers Europe	4013091
<i>International Configuration – Japanese Diplexer (5-55 MHz/88-860 MHz)</i>	
2-Line VoIP Cable Modem with EMTA for Japan. Includes: <ul style="list-style-type: none"> • PacketCable 1.0 / DOCSIS 2.0 (NTSC Japan and North America) • Standard housing (no battery backup capability) • 100-120 VAC / 50-60 Hz, 12 VDC / 1A Class 2 wall-mount linear-switching power supply • Power cord, Brazil • No USB 1.1 port • Ethernet cable • Paper Japanese user guide Japan – Importer Specific Configuration	4016464

Replacement Components

AC Power Supplies, 12 VDC	Part Number
<i>12 VDC High Efficiency Linear-Switching, Class 2</i>	
100-120 VAC / 50-60 Hz, 12 VDC / 1A desktop linear-switching power supply with attached power cord and connector for North America and Japan	4018777
100-120 VAC / 50-60 Hz, 12 VDC / 1A wall-mount linear-switching power supply for North America and Japan	4015452
220 VAC / 50-60 Hz, 12 VDC / 1A wall-mount linear-switching power supply for Argentina	4015457
230 VAC / 50-60 Hz, 12 VDC /1A wall-mount linear-switching power supply for Australia	4018797
230 VAC / 50-60 Hz, 12 VDC /1A wall-mount linear-switching power supply with Euro style connector	4015453
220 VAC / 50-60 Hz, 12 VDC / 1A wall-mount linear-switching power supply for Korea	4015458
230-240 VAC / 50-60 Hz, 12 VDC /1A wall-mount linear-switching power supply with BS-1363 United Kingdom style 3-pin connector	4018794
<i>12 VDC Universal Switching Mode, Class 2</i>	
100-240 VAC / 50-60 Hz, 12 VDC / 1A desktop universal switching mode power supply, Class II, C7 AC connector, 2 conductor (power cord not included, order power cord separately)	4009116
<i>12 DC, Linear, Class 2</i>	
120 VAC / 60 Hz, 12 VDC / 1A desktop linear power supply with attached power cord and connector for North America	749826
220 VAC / 50 Hz, 12 VDC / 1A desktop linear power supply with attached power cord and connector for Argentina	4012871
220 VAC / 60 Hz, 12 VDC / 1A desktop linear power supply with attached power cord and connector for Korea	4004222
230 VAC / 50 Hz, 12 VDC / 1A desktop linear power supply with attached power cord and CEE7/16 Euro plug connector	4002193
230-240 VAC / 50 Hz, 12 VDC / 1A desktop linear power supply with attached power cord and BS-1363 United Kingdom style 3-pin connector	4004768

AC Power Supplies, 15 VDC	Part Number
<i>15 VDC High Efficiency Linear-Switching, Class 2</i>	
100-120 VAC / 50-60 Hz, 15 VDC /1A desktop linear-switching power supply with attached power cord for North America	4018776
100-120 VAC / 50-60 Hz, 15 VDC /1A wall-mount linear-switching power supply with non-polarized connector for North America and Japan	4015454
100-120 VAC / 50-60 Hz, 15 VDC /1A wall-mount linear-switching power supply with polarized AC connector for North America	4018796
230 VAC / 50-60 Hz, 15 VDC /1A wall-mount linear-switching power supply with Euro style connector	4015453
230-240 VAC / 50-60 Hz, 15 VDC /1A wall-mount linear-switching power supply with BS-1363 United Kingdom style 3-pin connector	4018795

Replacement Components, continued

AC Power Supplies, 15 VDC, continued	Part Number
230-240 VAC / 50-60 Hz, 15 VDC / 1A wall-mount linear-switching power supply for Australia	4020503
<i>15 VDC, Universal Switching Mode, Class 2</i>	
100-240 VAC / 50-60 Hz, 15 VDC / 1A desktop universal switching mode power supply, Class II, C7 AC connector, 2 conductor power cord (power cord not included, order power cord separately)	4007274
<i>15 VDC Linear, Class 2</i>	
120 VAC / 60 Hz, 15 VDC / 1A desktop linear power supply with attached power cord and connector for North America	4004854
230 VAC / 50 Hz, 15 VDC / 1A desktop linear power supply with attached cord and CEE7/16 Euro plug power connector	4004855
230 VAC / 50 Hz, 15 VDC / 1A desktop linear power supply with attached cord and BS-1363 style 3-pin United Kingdom power connector	4006872

Power Cords	Part Number
<i>Class 2</i>	
Power cord, 2 conductor, North America, NEMA 1-15 to C7, non-polarized	1002239
Power cord, 2 conductor, Japan, NEMA 1-15 to C7, non-polarized	207586
Power cord, 2 conductor, European, Euro plug CEE7/16 to C7	503414
Power cord, 2 conductor, United Kingdom, BS1363 to C7	1002798
Power cord, 2 conductor, Brazil Euro plug CEE7/16 to C7, INMETRO	4009115
Power cord, 2 conductor, Korea	4010439
Power cord, 2 conductor, Argentina	4012938

Battery Cartridge	Part Number
2200 mAh Li-Ion Battery Cartridge	4008300

Cables	Part Number
Ethernet cable, standard length, 48 inches long	740580
Ethernet cable, 2 meters long	4018790
USB cable	740579

User's Guide and USB Drivers	Part Number
CD-ROM with user guide and USB drivers	4001911



Cisco, Cisco Systems, the Cisco logo, the Cisco Systems logo, and Scientific Atlanta are registered trademarks or trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries.

DOCSIS is a registered trademark of Cable Television Laboratories, Inc.

PacketCable is a trademark of Cable Television Laboratories, Inc.

All other trademarks mentioned in this document are the property of their respective owners.

Specifications and product availability are subject to change without notice.

© 2006-2008 Cisco Systems, Inc. All rights reserved.

Cisco Systems, Inc.
1-800-722-2009 or 770-236-6900
www.scientificatlanta.com

Part Number 7008320 Rev H
April 2008