

New Holland Rotary Tiller Specifications

105A



MODEL	40-inch	52-inch	60-inch
Approximate working width, in. (mm)	40 (1016)	52 (1320.8)	60 (1524)
Tilling depth adjustment with guide shoes, in. (mm)	0 to 4.5 (0 to 114.3)		
Maximum tilling depth with guide shoes, in. (mm)	7.25 (184.2)		
Hitch category	I		
Offset adjustment to right, in. (mm)	11 (279.4)		
PTO hp rating	45		
Rotor drive type	Chain		
Drive protection	Slip clutch		
Rotor speed @ 540 rpm PTO	231	231	236
Number of blades	20	24	28
Blade tip speed (fpm) @ 540 rpm	1,043	1,043	1,063
Weight, lbs. (kg)	352 (159.7)	431 (195.5)	495 (224.5)

MODEL	72-inch	72-inch HD	80-inch HD
Approximate working width, in. (mm)	72 (1828.8)	72 (1828.8)	80 (2032)
Tilling depth adjustment with guide shoes, in. (mm)	0 to 4.5 (0 to 114.3)		
Maximum tilling depth with guide shoes, in. (mm)	7.25 (184.2)	7 (177.8)	7 (177.8)
Hitch category	I	I or II	I or II
Offset adjustment to right, in. (mm)	11 (279.4)		
PTO hp rating	45	60	60
Rotor drive type	Chain	Gear	Gear
Drive protection	Slip clutch		
Rotor speed @ 540 rpm PTO	236	211	211
Number of blades	36	36	40
Blade tip speed (fpm) @ 540 rpm	1,063	944	944
Weight, lbs. (kg)	596 (270.3)	765 (347)	810 (367)

Visit our Web site at www.newholland.com/na. Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.