

Proxima DP6810 Projector

Technical and Functional Specifications

Computer Compatibility	<ul style="list-style-type: none">● IBM PC, PS/2, Pentium and compatibles● Apple Macintosh, Power Macintosh, PowerBook and compatibles
Video Compatibility	<ul style="list-style-type: none">● PAL, PAL-M, SECAM, NTSC, NTSC 4.3
Sources	<ul style="list-style-type: none">● 2 computer, 4 audio, 2 video or 2 S-video
Brightness	<ul style="list-style-type: none">● 900 ANSI lumens (typical)
Contrast Ratio	<ul style="list-style-type: none">● 200: 1 full on, full off
Display Technology	<ul style="list-style-type: none">● 1.3 in. polysilicon TFT LCD x 3
Resolution	<ul style="list-style-type: none">● XGA (1024 x 768)
Resolutions Supported	<ul style="list-style-type: none">● VGA (640 x 480) Fit-to-View®● SVGA (800 x 600) Fit-to-View● XGA (1024 x 768) native● SXGA (1280 x 1024) Fit-to-View
H-Sync Range	<ul style="list-style-type: none">● 15.8 to 80 KHz
V-Sync Range	<ul style="list-style-type: none">● 50 to 85 Hz
Horizontal Resolution	<ul style="list-style-type: none">● 400 TV Lines
Lens	<ul style="list-style-type: none">● Power zoom and focus lens 1.5:1 ratio● Focal length: 48mm to 72mm, F/2.3 to F/3.0
Projection Distance (From Screen)	<ul style="list-style-type: none">● 4 ft to 35 ft (1.2 m to 10.7 m)
Image Size (Diagonal)	<ul style="list-style-type: none">● 1.8 ft to 23.5 ft (0.5 m to 7.2 m)
Keystone Correction	<ul style="list-style-type: none">● 8.8°
Number of Colors	<ul style="list-style-type: none">● 16.7 million
Lamp	<ul style="list-style-type: none">● 150 watt UHB● Lamp life: 1500 hours to 50% brightness
Audio	<ul style="list-style-type: none">● 2 x 2-watt stereo
Remote Control	<ul style="list-style-type: none">● Wireless IR remote with mouse control and laser pointer
Dimensions	<ul style="list-style-type: none">● 16.3 in. W x 12.5 in. L x 6.2 in. H● 41.5 cm W x 31.5 cm L x 15.7 cm H
Weight	<ul style="list-style-type: none">● 17 lbs. (7.8 kg)
Power Requirements	<ul style="list-style-type: none">● 100 - 120V / 220 - 240V at 50/60 Hz
Power Consumption	<ul style="list-style-type: none">● 250 watts
Operating Temperature (Sea Level)	<ul style="list-style-type: none">● 32° F to 95° F (0° C to 35° C)
Approvals	<ul style="list-style-type: none">● CE, C-UL, UL, FCC Class A
Warranty	<ul style="list-style-type: none">● Two year warranty on parts and labor (excluding lamp)