



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: S446-006

SCSI/Fibre Channel - 6-ft. SCSI Cable VHDCI68M to VHDCI68M

Highlights

- Premium double-shielded cable
- 34 twisted-pair conductors



Description

Multi-platform SCSI III external peripheral cable VHDCI68M/M. This 6ft cable is designed to connect two SCSI III (fast and wide) devices together. Manufactured using double shielded 34 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

System Requirements

- Any external SCSI device or HOST controller card requiring VHDCI68M/M interface

Package Includes


- 6-ft. SCSI Cable VHDCI68M to VHDCI68M

Features

- Backwards compatibility with previous SCSI generations
- Double shielded (foil and braid)
- 34 twisted pair conductors
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

OVERVIEW	
Intended Application	Connecting Drives
PHYSICAL	
Color	Black
Style	SCSI
Length	6 ft.

CONNECTIONS	
Connector A	 VHDCI68 (MALE)
Connector B	 VHDCI68 (MALE)

Related Items

SCSI Cables		
S140-000	SCSI/Fibre Channel - External SCSI U320 LVD/SE Active Terminator HD68M (single-ended)	Qty: [optional]
S450-006	SCSI/Fibre Channel - 6-ft. SCSI U2/U160/U320 LVD/SE cable HD68M to HD68M w/thumbscrews	Qty: [optional]
S454-006	SCSI/Fibre Channel - 6-ft. SCSI U320/U160 LVD/SE cable, Offset VHDCI68M to HD68M	Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2403.