Tired of buying large runs of flexo or offset color labels just to get reasonable costs on quality color output?

Output Technology has your solution. Start printing your high resolution product labels and tags on demand—as you need them. With Output Technology's new CM1700 Color Label Printer it is simple and easy. Your label center can now print your product labels, box labels, barcodes and tags in-house, on one printer that can do it all. Print full-color photos on your box and shelf labels, combining the benefits of high resolution color images along with your part numbers and product codes. You will reduce inventory and shipping errors by making it easy for everyone to know what is inside the box. With the CM1700's ability to print on a wide variety of label media, you will find your label applications are now limited only by your imagination.

Charge

# CM1700 Color Label System<sup>™</sup>

## Professional Color Label System

- Prints Roll Fed Labels Up To 8.25" Wide x 24" Long
- Sturdy Industrial Design
- High Resolution to 4800 x 1200 dpi
- Fast Drying Inkjet Process
- Prints On Wide Variety of Materials Including High-Gloss, Synthetics, Tags and Even Water Resistant Label Stocks.



## CM1700 Color Label Printer Specifications

### Print Method: Inkjet

Print Resolutions: 4800 x 1200 dpi, 2400 x 1200 dpi, 600 x 600 dpi

Print Speeds: Approximately 2" (51mm) per second for black Approximately 1.5" (38mm) per second for color + black Approximately 10" per second feed rate

Ink Cartridges: CM1700C103 Color (CMY) (8ml per color) CM1700C104 Black Dye-Based (Kd) (19ml) CM1700C105 Black Pigment-Based (Kp) (24ml)

Colors: 16.7 million

Color Ink Management Photo Based Color Pallet Graphics Based Color Pallet

**Built in Ink Estimator** 

**Min. Print Width:** 0.75" (19mm)

Max. Print Width: 8.25" (210mm)

Min. Media Length: 0.75" (19mm)

Max. Print Length: 24" (609mm) \*\* Banner Length Printing Available

Media Types: Roll-fed pressure-sensitive labels, roll-fed tags

Media Sensing: Moveable see-through sensor for die-cut labels; Reflective for tags with black stripe sensing; Continuous label stock; Preprinted label stock.

Supply Roll: 6" (152mm) maximum diameter on 3" (76mm) core Indicator Lights: Power, Pause, Ink Low

Controls: Pause, Load/ Feed, Unload

**Operating Systems:** Windows XP/2000 Mac OSX, 10.2 or higher

Data Interface: USB 2.0/ 1.1

#### Minimum System Requirements:

Pentium® IV computer or better AMD Athlon XP/Barton 2500+ or better Mac 700 Mhz G4 or better 512MB RAM 5GB free hard drive space USB 2.0/ 1.1 port

Label Design Software:

NiceLabel<sup>™</sup> SE Demo Edition included Can be used with most popular Windows-based label design software programs..

Electrical Rating: 12VDC, 5.0A

Power Requirements: 100-240VAC, 50/60 Hz, 60 watts

Certifications: UL, UL-C, CE, FCC Class B

Weight: 29 lbs. (13.2 Kg)

Dimensions: 17"W x 9.1"H x 15.5"D (432mmW x 231mmH x 394mmD)

Specifications subject to change without notice.

OUTPUT TECHNOLOGY High Performance Business Printers from OTC

Corporate Office 3808 N. Sullivan Rd. Bldg #3 Spokane, WA 99212-1381 509-536-0468 800-393-7693 (USA Only) FAX: 509-533-1285

All company and product names are trademarks of their respective owners.

www.output.com

060-00510-00

Mathems Figuena Cartier

DIGIGICIC

Wester