

4 head mono VCR


VR400

4 head mono VCR

- **Plug & Play** installation including automatic time download and correction
- **2 additional Video heads** for high quality long play recordings and perfect Still pictures
- **Follow TV** sorts the channels in the same order as your TV
- **Digital Studio Picture Control** for an excellent picture quality
- **Laser-Cut Video Heads** - the maximum precision for the ultimate recording quality
- **Automatic Tape Length Recognition**

**TURBO
DRIVE**

SHOWVIEW



Let's make things better.



PHILIPS

Product Information

Reception

- Tuner: Full (UHF + VHF + Hyperband) Tuner
- Tuning: PLL, CH - FREQ entry, 99 presets
- Tuning/Install Features: Manual Search/Store, Plug & Play

User Interface

- Time and Date Download: PDC, Text (Time)
- Picture Improvement System: Digital Studio Picture Control, Edge Noise Canceller
- Additional Playback Standard: NTSC
- Audio Recording System: Linear
- Audio Recording Level: Automatic
- TV Related Functions: Follow TV, Direct Record

Programming

- Number of Events: 6/month
- Programming Mode: OTR, Remote
- Record Control & Transmitter Identification: PDC, VPS
- Programming System: Daily/Weekly, Showview
- Automatic Sat. Recording: From Ext. 2
- Record Speed: Long Play, Standard Play

Tape Deck

- Number of Video / FM Audio / Flying Erase Heads: 4 / 0 / 0
- Play: +1, -1, Repeat
- Additional Playback Features: Perfect Still, Multiple Search Speeds, Variable Slow Motion Speed
- Index Related Functions: Blank Tape Search, Next/Previous index search
- Tape Length Recognition: Automatic
- Tape Counter: Linear relative, Time left
- Automatic Functions at Tape End: Rewind after Play - Eject after Record
- Winding / Rewinding Time (E180): 100 sec.
- Head Cleaning Mode: Automatic, Manual

Connectors Rear

- EXT1: Black, Euro CVBS in/out
- EXT2: Blue, Euro Decoder, RGB loop through
- Terrestrial Antenna In & Out: 75 Ohms (IECtype)
- Mains Connector: Standard (IECtype)

General

- Voltage / Frequency: 198-264 V / 50Hz
- Backup Presets: 1yr
- Backup Clock, Timer Events & Calendar: 7hrs
- Power Cons. in Play / Std-By / Low Power Std By: 12,5W / 9,5W / <6W
- Remote Control - Code Emission: TV-RC5, VCR1-RC5
- Equipment Supplied: Aerial cable, Mains cord, Remote Control, Batteries
- Weight incl. / excl. package in kg: 5,5 / 3,6
- Set Size - W x D x H (mm): 380 x 260 x 93
- Packaging - W x D x H (mm): 450 x 382 x 180

Product Highlights

• Plug & Play

Let the VCR guide you through the installation steps and within short your videorecorder will be installed without the need of the user manual. Installing a VCR has never been easier!

• Automatic Time download

The Teletext contains an extremely precise time information. Your videorecorder knows that and during the installation, it automatically reads out this precious information.

You can then use your VCR as the clock reference in your home, as the time is readjusted every day. You even don't have to worry about changing from summer to winter time!

• Follow TV

You can now easily arrange your VCR channels in the same order as your TV.

• Automatic Satellite Recording

All you need to do is connect your Satellite Tuner to SCART 2 and programme what you want to record on your VCR. When time has come, the Satellite Tuner wakes the VCR up and starts the recording.

• Direct Record

Record instantly what you see on your TV just by pressing the Record button. You don't need to select the right channel: the VCR will do it by itself.

• Digital Studio Picture Control

Thanks to a digitally controlled Noise-Reduction Circuit, you are sure to obtain the best picture quality with any kind of tape.

• TURBO DRIVE

Enjoy the ease of use and the comfort of one of the fastest VCR decks in the world.

• Automatic Head Cleaning

Clean heads ensure an optimum picture quality. Each time you put a tape in your VCR, the heads will be cleaned automatically.

| | /02 | /39 | /58 |
|--------------------------|---|---|---|
| TV System Off Air | PAL B/G | PAL B/G, PAL I, SECAM B/G, SECAM L/LI | PAL B/G, PAL D/K, SECAM B/G, SECAM D/K |
| Modulator System | Pal G | Splitter | Pal GK (switchable) |
| Modulator Range | Ch 21 - Ch 55 | --- | Ch 21 - Ch 55 |
| Modulator Preadjustment | 591.25 MHz (Ch 36) | --- | 591.25 MHz (Ch 36) |
| OSD Menu Languages | Dutch, English, French, German, Italian, Spanish, Swedish | Dutch, English, French, German, Italian, Spanish, Swedish | Czech, English, Hungarian, Polish, Russian Cyrillic |
| Delivery Menu Language | English | French | English |
| Record/Playback Standard | PAL | MESECAM, PAL, SECAM | MESECAM, PAL |
| Remote Control RT192 | /101 | /104 | /101 |

Subject to modification without notice

ShowView and VideoPlus are Trademarks of Gemstar Development Group