


17" (16.0" VIS) Design Line Real Flat monitor

Dare to compare -- LightFrame™3 for the sharpest and brightest displays ever !

- LightFrame™3 - 2 x Normal Brightness
- 17-inch (16.0" VIS) Design Lince Real Flat color monitor with excellent front of screen performance for use with MACs and PCs
- Autoscan covers horizontal frequencies up to 71kHz offering a maximum resolution of 1280 x 1024 with flicker free display of 1024 x 768 at up to 89Hz
- Real Flat High Contrast CRT with high-resolution 0.25 mm dot pitch(0.21 hdp)



Let's make things better.



PHILIPS

17" (16.0" VIS) Design Line Real Flat monitor



Technical Specifications

CRT

- Size (inch/cm) 17"/ 41 cm
- Deflection angle (degrees) 90°
- Dot pitch 0.25 mm
- Horizontal pitch 0.21 mm
- Tube type Shadow mask, Real Flat, High Contrast, Anti Glare, Anti Static, Anti reflection, Light Transmission 45%
- Phosphor P22
- Recom. display area(mm) 306 x 230 mm
- Recom. display area(inch) 12.0" x 9.0"
- Max. display area(mm) 325 x 244 mm
- Max. display area(inch) 12.8" x 9.6"

Scanning

- Horizontal scanning 30 - 71 kHz
- Vertical scanning 50 - 160 Hz

Video

- Video dot rate 108 MHz
- Input impedance
- Video 75 Ohm
- Sync 2.2k Ohm
- Input signal levels 0.7 Vpp
- Sync input signal Separate sync
Composite sync
- Sync polarities Positive and negative

White color temperature

Chromaticity CIE coordinates:

- at 9300 K: x=0.283, y=0.297
- at 6500 K: x=0.313, y=0.329

Resolution and preset modes

- Max. resolution 1280 x 1024
 - Recom. resolution 1024 x 768
 - 16 user definable modes
 - 22 factory preset modes:
- | | H.freq (kHz)/ V.freq (Hz) |
|-------------|---------------------------|
| 640 x 350 | 31.5K/70 |
| 640 x 350 | 37.9K/85 |
| 640 x 480 | 31.5K/60 |
| 640 x 480 | 37.9K/72 |
| 640 x 480 | 37.5K/75 |
| 640 x 480 | 43.3K/85 |
| 640 x 480 | 50.6K/100 |
| 720 x 400 | 31.5K/70 |
| 720 x 400 | 37.9K/85 |
| 800 x 600 | 37.9K/60 |
| 800 x 600 | 48.1K/72 |
| 800 x 600 | 46.9K/75 |
| 800 x 600 | 53.7K/85 |
| 800 x 600 | 63.9K/100 |
| 832 x 624 | 49.7K/75 |
| 1024 x 768 | 48.4K/60 |
| 1024 x 768 | 56.5K/70 |
| 1024 x 768 | 60.0K/75 |
| 1024 x 768 | 68.7K/85 |
| 1152 x 864 | 67.5K/75 |
| 1280 x 960 | 60.0K/60 |
| 1280 x 1024 | 64.0K/60 |

Plug and play compatibility

- Display Data Channel DDC 2B (VESA)
- Microsoft® Windows® 95/98/Me & 2000/NT/XP compatible
- sRGB

Power management

- Complies with EPA Energy Star and NUTEK specifications
- Operation 68 W (typical)
 - Suspend/Stand By mode < 2 W
 - Off mode/Deep Sleep < 2 W

Low-emission characteristics

- Complies with TCO '95

Monitor controls and functions

- Main 5-button OSD
Brightness +/- direct access
Contrast +/- direct access
Language (English, Spanish, French, German, Italian, Chinese, Portuguese, Korean), zoom, horizontal, vertical, pincushion, balanced, trapezoid, parallelogram, color, reset, degauss, moire, serial number, resolution, frequency, sRGB
- On Screen Display For improving the picture display of multi media content such as photos, videos and games. Will boost brightness and sharpness performance on user selected areas/ windows on the screen. With automatic detection of graphical content in Internet Explorer for the web browsing. Can process up to 16 images simultaneously. One-button full screen mode. Advanced user adjustments via Windows control panel. Easy to use control software for Windows 98, Me, XP and 2000. Software in English, French, German, Spanish, Italian, Portuguese, Dutch, Chinese and Korean
- LightFrame™3

Connections and Cables

- Connections
- Video 15-pin D-sub
- Cables D-Sub Video cable(fixed), power cord

Regulatory approvals

- TÜV/GS, TÜV/Ergo, TÜV/9241-3
- FCC-B, UL, CSA, DHHS
- SEMKO, Poland-B sign, C-Tick
- CE, BCIQ, PSB
- NUTEK, Energy Star

Physical specifications

- Dim. incl. base (WxHxD)(mm) 410.2 x 435 x 443.5
- Dim. incl. base (WxHxD)(inch) 16.1" x 17.1" x 17.5"
- Weight (kg) 18 kg
- Power supply 90 - 264 VAC, 50/60Hz
- Temperature (operational) 0°C to 40°C/ 32°F to 104° F
- Temperature (storage) -25°C to 65°C/ -13°F to 149°F
- Relative humidity 5% to 95%
- MTBF > 75,000 H

As an Energy Star partner, Philips has determined that this product meets the Energy Star guidelines for energy efficiency. Microsoft and Windows are registered trademarks of Microsoft Corporation. MacOS is a registered trademark of Apple Computer, Inc. All trademark acknowledged. Copyright 2001 Koninklijke Philips Electronics N.V.

All data subject to change without notice

Release date: May 2002

www.philips.com

Let's make things better.



PHILIPS