


WEATHERPROOF 3.5~8MM IR CAMERA



CRR-1101H
CRR-1101



Built-in 3.5~8mm vari-focal lens



Features

- 1/3" SONY Super HAD CCD,540TVL
- 3.5~8mm varifocal lens
- Exquisite design, precise circuitry & structure, incorporating today's most advanced technology
- Varifocal lens for easy to fit to a wide range of requirements and conditions
- Aluminum structure, All-sealed water-proof body
Sunshield used for outdoor supplied
- Longer working distance in night(90'), is the best choice for large zone surveillance system such as border& warehouse etc

Dimensions



Specifications

Model	CRR-1101H	CRR-1101
Image Pick up Device	1/3" SONY Super HAD CCD	
Signal system	PAL or NTSC Color system	
Horizontal Resolution	540 TVLines	420 TVLines
No. of Effective Pixels	PAL:752(H) × 582(V); NTSC:768(H) × 494(V)	PAL:500(H) × 582(V); NTSC:510(H) × 492(V)
Minimum Illumination	0.5Lux/F1.2 (LED OFF) ; 0Lux (LED ON)	
Day/Night Automatically Switch	Illumination < 3 ~ 5 Lux/F1.2	
White Balance	Automatic	
S/N Ratio	52dB	
Electronic Shutter	1/50 ~ 1/100,000sec(PAL), 1/50 ~ 1/100,000sec(NTSC)	
AGC/BLC	Automatic	
Lens	3.5~8MM varifocal lens	
IR-LED	42 PCS, 860um	
IR Series Distance	90'	
IR LED Life	100,000Hours	
Gamma	0.45	
Sync mode	INT	
Video Output	1.0Vp-p, 75 Ohm	
Power Supply	DC12V±10%	
Operating Temperature	-10℃ ~ +50℃ RH95%MAX	
Body	Aluminum	
Weight	2.1 lbs	



SVA Group USA Inc.
1316 John Reed Court, City of Industry, CA 91745
Tel: 626-363-9500 | Fax: 626-363-9508
1-888-8-ASK-SVA
<http://www.sva-usa.com>