

Speed Queen®

Softmount Washer-Extractors

18-30 lb



A Passion to Lead


Softmount Washer-Extractors

- **High spin speed.** Since all fabrics have different extract speed requirements, our line of softmount washer-extractors has variable extract speeds. A low extract speed is ideal for synthetics, permanent press and blends. A mid-range extract speed is perfect for mattress pads, blankets and spreads. A high extract speed is preferred for terry and cotton items.

A higher G-Force during extraction lowers the water retention of the fabrics being processed. Lower water retention also reduces the gas or electricity used during the drying process, saving money on utilities and improving customer turnover.

- **Easy installation.** Speed Queen's 18 lb and 30 lb capacity softmount washer-extractors fit through 36" door openings. Softmount washer-extractors require no additional cement base, making installation easier and less costly.

- **Superior suspension.** Extensive engineering efforts have developed a heavy-duty suspension system designed for superior washing performance and absorbing out-of-balance load vibrations without the need for special foundations.



- **Stainless quality.** Our rugged steel cabinet and top construction resists corrosion with normal use; it's also extremely rust resistant. This makes the SX a reliable performer for your on-premises laundry.



Softmount Washer-Extractors Specifications

	SX18	SX30
Capacity - lb (kg)	18 (8.2)	30 (13.6)
Cylinder Volume - cu. ft. ³ (liters)	2.68 (76)	4.66 (132)
Cylinder Diameter - in (mm)	20 7/8" (530)	25 9/16" (650)
Cylinder Depth - in (mm)	13" (330)	15 3/4" (400)
Door Opening Size - in (mm)	11 13/16" (300)	11 13/16" (300)
Wash Speed - RPM	10-50	10-50
Distribution Speed - RPM	85	85
Extract Speed - RPM	500-1000	250-1000
Extract G-Force	296	380
Water Inlet Connection - in (mm)	3 x 3/4" (19)	3 x 3/4" (19)
Drain Connection Size - in (mm)	2" (50)	2" (50)
Motor Size - HP (kW)	1 (.75)	2 (1.5)
Voltage/Hz/Phase Non-heat Circuit Breaker	200-240/50-60/1-3 15	200-240/50-60/1-3 15
Voltage/Hz/Phase* Electric Heat Circuit Breaker	200-240/50-60/3 30	200-240/50-60/3 60
Voltage/Hz/Phase* Non-heat Circuit Breaker	380-415/50-60/3 15	380-415/50-60/3 15
Voltage/Hz/Phase Circuit Breaker	380-415/50-60/3 20	380-415/50-60/3 40
Width - in (mm)	26" (660)	30 11/16" (780)
Depth - in (mm)	31 5/16" (796)	35 3/8" (898)
Height - in (mm)	39 13/16" (1011)	46 1/4" (1175)
Weight - lb (kg)	481 (218)	728 (330)
Shipping Weight - lb (kg)	514 (233)	789 (358)
Agency Approval	CE, ETLus, ETLc	CE, ETLus, ETLc

*Special order may require longer time, consult with factory.

For more detailed technical information, please visit the Product section at www.speedqueen.com.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000


©Copyright 2007 Alliance Laundry Systems LLC

Printed in the U.S.A.



Printed on paper manufactured with virgin pulp from certified sources and a minimum of 10% post-consumer recovered fiber.

- **Flexible control.** Our advanced microprocessor control is designed to offer eight pre-programmed cycles. These cycles can be customized to fit your specific needs. Customized cycles can significantly reduce water consumption and turnaround time by doing the maximum amount of cleaning in the shortest amount of time. The micro control is easy to operate, utilizing a separate start pad and cycle symbols designed to match garment care labels.



Fully Programmable Electronic Control

www.speedqueen.com

Speed Queen.
Alliance Laundry Systems